



AMH35

AMH40



AMH45

AMH50
(see next page for AMH51
and AMH55 WSD image)

- 1 year warranty
- Accurate detergent and rinse aid peristaltic dosing pumps with dosing setup by fascia controls on all models
- Easy clean parallel wash and rise arm assembly on all models
- AMH55 WSD with internal automatic water softener and drain pump as standard
- Drain pump version available on AMH35, AMH40, AMH45, AMH50* & AMH51*
- AMH51 & AMH55 WSD with internal breaktank as standard
- Surface scrap trays standard on AMH45 and optional on all other models
- AMH35, AMH40, AMH45 & AMH50 Supplied with two open cup/glass racks and cutlery insert as standard
- AMH51 & AMH55 WSD supplied with one open cup/glass rack, one pegged plate rack and cutlery insert

Technical

- Standard voltage 230V – single phase
- AMH50, AMH51 & AMH55 WSD can be supplied for 3 phase operation – **please specify at time of order**
- Suitable for hot (max 50°C) or cold water supply, typically at 2 to 4 bar dynamic supply pressure, refer to specification sheets for individual requirements
- Wash temperature 60°C – adjustable on AMH51 & AMH55 WSD
- Rinse temperature for AMH35, AMH40, AMH45 & AMH50 65°C
- Rinse temperature for AMH51 & AMH55 WSD 82°C – adjustable

* Drain pump cannot be retro fitted to AMH50 & AMH51. Drain pump versions require a waste up stand for correct operation.

Restrictive waste connections should be avoided for all installations.

All machines supplied 13 amp will come with molded plug and cable.

Machines configured for 13 amp supply or fitted to cold water supply will not be capable of running repeated short cycles. The cycle time will automatically be extended to allow recovery of correct operating temperatures.

Model	Rack size mm	Useable Height mm	Dimensions mm W x D x H	Cycle Time Sec	Power kW	Amps Required	Price
AMH35	350	240	400 x 495 x 590 [#]	120	2.8	13	£1,340
AMH35 D			As AMH35 above with fitted drain pump				£1,510
AMH40	390	300	440 x 540 x 670 [#]	120	2.8	13	£1,640
AMH40 D			As AMH40 above with fitted drain pump				£1,810
AMH45	450	280	525 x 560 x 705 [#]	120	2.8	13	£2,300
AMH45 D			As AMH45 above with fitted drain pump				£2,500
AMH50*	500	340	580 x 610 x 810 [#]	90/180	2.6/4.5/6.5	13/20/30 ^{##}	£2,470
AMH50 D			As AMH50 above with fitted drain pump				£2,670
AMH51*	500	340	580 x 610 x 810 [#]	90/180	2.6/4.5/6.5	13/20/30 ^{##}	£2,700
AMH51 D			As AMH51 above with fitted drain pump				£2,900
AMH55 WSD	500	340	580 x 610 x 810 [#]	90/180	2.6/4.5/6.5	13/20/30 ^{##}	£3,300
AMH55 WSD supplied with drain pump as standard							

Height excludes adjustable feet which will add 10 to 20mm.

Machines will be supplied for 30 amp supply as standard. If supplied 13 amp machine will come fitted with molded plug and cable.

20 amp machines will be supplied with original cable and without plug. Standard 13 amp UK 3 pin plugs will be **unsuitable** for cable supplied.

It is strongly recommended that for busy sites to achieve optimum performance that machines are installed on hot fill (max 50°C).