www.burco.co.uk





BURCO 20L COUNTERTOP AUTO FILL WATER BOILER







- Extra large 20L tank Capacity
 Ideal for premises requiring a large volume of instant hot water.
- ✓ Manufactured in the British Isles
- ✓ Touch controller Features an On/Off Switch, On/Off LED and "Descale Now" warning LED.
- ✓ Heats and dispenses water at 98°C
- Patented plastic tap can be changed from controllable to constant flow
- ✓ Powerful 2.8kW heating element
 For rapid heat-up time.
- Removable dishwasher-friendly drip tray With chrome insert for easy cleaning.
- ✓ Sturdy stainless steel construction
- ✓ Comes with 1 years parts and labour warranty



SKU CODE:	PRODUCT CODE:	DESCRIPTION:
444442470	BC AF CT 20L UK	Burco 20L Countertop Auto Fill Water Boiler

Burco Boilers.

Part of Glen Dimplex Heating and Ventilation.

Millbrook House, Grange Drive, Hedge End, Southampton, SO30 2DF.

Tel: 0344 879 3470 Email: gdhvsalesorders@glendimplex.com

BURCO

www.burco.co.uk



FULL SPECIFICATION - Burco 20L Countertop Auto Fill Water Boiler

SKU code444442470GDPA codeBC AF CT 20L UKEAN code5052263024700TypeCountertopCapacity (L)20Unit dimensions (W x D x H) (mm)344 x 464 x 689 (depth includes tap & drip tray)Packed dimensions (W x D x H) (mm)773 x 490 x 432Product weight (kg)11.2Packed weight (kg)11.3Body construction430 grade Stainless SteelTank construction304 grade Stainless SteelDrip tray size (W x D x H) (mm)345 x 220 x 92Trim & drip tray plastic typeABSPower rating (kW)3Water delivery temperature98°CTypical Heating and Cooling timesHeat up time to 98° C: 56 minutesMater delivery temperature98°COutput per hourLitres: 0.1Pints: 55Coups: 206Rapid draw offLitres: 22Pints: 0.8Pints: 0.8Tap height2200mm from drip tray (tbc)Water inlet connection fitting%" BSPWater inlet connection fitting%" BSPWater inlet pressure (bar)10Voltage supply230V 50-60HzElectrical Supply 1N*+E current (A)13Plug typeUKFitted cable length (m)1.5None slip feet for safetyYesBoil dry thermal cut outYesCountry of manufactureMade in the British IslesCountry of manufactureMade in the British IslesMater inter cut outYesSoil dry thermal cut outYes		
EAN code5052263024700TypeCountertopCapacity (L)20Unit dimensions (W x D x H) (mm)344 x 464 x 689 (depth includes tap & drip tray)Packed dimensions (W x D x H) (mm)773 x 490 x 432Product weight (kg)11.2Packed weight (kg)14.33Body construction430 grade Stainless SteelTank construction304 grade Stainless SteelDrip tray size (W x D x H) (mm)345 x 220 x 92Trim & drip tray plastic typeABSPower rating (kW)3Water delivery temperature98°CTypical Heating and Cooling timesHeat up time to 98° C: 56 minutesUitres: 31Pints: 55Cups: 145.7Cups: 145.7Recovery per minuteLitres: 0.5Pints: 0.38200m from drip tray (tbc)Water field to ender the pressure (bar)10Voltage supply230V 50-60HzElectrical Suppl 1N~+E current (A)13Plug typeUKFitted cable length (m)1.5None slip feet for safetyYesBoil dry thermal cut outYesBoil dry thermal cut outYesCourty of manufactureMake in the British Isles	SKU code	-
TypeCountertopCapacity (L)20Unit dimensions (W x D x H) (mm)344 x 464 x 669 (depth includes tap & drip tray)Packed dimensions (W x D x H) (mm)773 x 490 x 432Product weight (kg)11.2Packed weight (kg)14.33Body construction430 grade Stainless SteelTank construction304 grade Stainless SteelTrim & drip tray plastic typeABSPower rating (kW)3Water delivery temperature98° CTypical Heating and Cooling timesHeat up time to 98° C: 56 minutesUtput per hourLitres: 31Pints: 55Cups: 206Rapid draw offLitres: 0.5Tap height220mm from drip tray (tbc)Water inlet connection fitting%" BSPWater field to connection fitting%" BSPWater field to pressure (bar)10Voltage supply230V 50-60HzElectrical Supply 1N~+E current (A)13Pluty typeUKFitted cable length (m)1.5None slip feet for safetyYesBoil dry thermal cut outYesBoil dry thermal cut outYes	GDPA code	BC AF CT 20L UK
Capacity (L)20Unit dimensions (W x D x H) (mm)344 x 464 x 689 (depth includes tap & drip tray)Packed dimensions (W x D x H) (mm)773 x 490 x 432Product weight (kg)11.2Packed weight (kg)14.33Body construction430 grade Stainless SteelTank construction304 grade Stainless SteelDrip tray size (W x D x H) (mm)345 x 220 x 92Trim & drip tray plastic typeABSPower rating (kW)3Water delivery temperature98°CTypical Heating and Cooling timesHeat up time to 98° C: 167 minutesCutput per hourLitres: 31 Pints: 55 Cups: 206Rapid draw offLitres: 0.5 Pints: 0.88Tap height220mm from drip tray (tbc)Water inlet connection fitting%" BSPWater inlet connection fitting%" BSPWater inlet connection fitting13 Pints: 0.5 Pints: 0.38Tap height2300V 50-60HzUsage supply230V 50-60HzElectrical Supply 1N"+E current (A) Plug type13 Plug typePlug typeUKFitted cable length (m) None slip feet for safety Points: 0.5 Plug type10 VesNone slip feet for safety PointsYes PointsBoil dry thermal cut out Country of manufactureYes PointsBoil dry thermal cut out Country of manufactureYes PointsBoil dry thermal cut out Country of manufactureYes PointsBoil dry thermal cut out Country of manufactureMade in the British Isles Points	EAN code	5052263024700
Unit dimensions (W x D x H) (mm) $344 x 464 x 689 (depth includes tap & drip tray)Packed dimensions (W x D x H) (mm)773 x 490 x 432Product weight (kg)11.2Packed weight (kg)11.3Body construction430 grade Stainless SteelTank construction304 grade Stainless SteelDrip tray size (W x D x H) (mm)345 x 220 x 92Trim & drip tray plastic typeABSPower rating (kW)3Water delivery temperature98'CTypical Heating and Cooling timesHeat up time to 98^\circ C: 167 minutesCoutput per hourLitres: 31Pints: 55Cups: 206Rapid draw offLitres: 22Pints: 38.7Cups: 145.77Recovery per minuteLitres: 0.5Pints: 0.88Tap height220mm from drip tray (tbc)%" BSPWater inlet connection fittingVater feed hose length (Supplied) (m)Voltage supply230V 50-60HzVoltage supply1.3Plug typeUkFitted cable length (m)None slip feet for safetyVes1.5None slip feet for safetyVesNone slip feet for safetyVesYesBoil dry thermal cut outCourty of manufactureMade in the British IslesStafe101100$	Туре	Countertop
Packed dimensions (W x D x H) (mm)773 x 490 x 432Product weight (kg)11.2Packed weight (kg)14.33Body construction430 grade Stainless SteelTank construction304 grade Stainless SteelDrip tray size (W x D x H) (mm)345 x 220 x 92Trim & drip tray plastic typeABSPower rating (kW)3Water delivery temperature98°CTypical Heating and Cooling timesHeat up time to 98° C: 56 minutesHeat up time to 98° C: 12 minutesCool down from 98° c: 260° C: 167 minutesCool down from 98° c: 120° C: 167 minutesCoups:206Rapid draw offLitres:Stress22Pints:55Cups:206Rapid draw offLitres:Uater site of the site of the site of the site of site o	Capacity (L)	20
Product weight (kg)11.2Packed weight (kg)14.33Body construction430 grade Stainless SteelTark construction304 grade Stainless SteelDrip tray size (W x D x H) (mm)345 x 220 x 92Trim & drip tray plastic typeABSPower rating (kW)3Water delivery temperature98°CTypical Heating and Cooling timesHeat up time to 98° C: 56 minutes Heat from 80-98° C: 12 minutes Cool down from 98° C-80° C: 167 minutesOutput per hourLitres: 31 Pints: 55 Cups: 206Rapid draw offLitres: 22 Pints: 38.7Recovery per minuteLitres: 0.5 Pints: 0.88Tap height220mm from drip tray (tbc)Water feed hose length (Supplied) (m)2Vater feed hose length (Supplied) (m)2Voltage supply230V 50-60HzElectrical Supply 1N~+E current (A)13Plug typeUKFitted cable length (m)1.5None slip feet for safetyYesBoil dry thermal cut outYesBoil dry thermal cut outYesStation Country of manufactureMade in the British Isles Station1100	Unit dimensions (W x D x H) (mm)	344 x 464 x 689 (depth includes tap & drip tray)
Packed weight (kg)14.33Body construction430 grade Stainless SteelTank construction304 grade Stainless SteelDrip tray size (W x D x H) (mm)345 x 220 x 92Trim & drip tray plastic typeABSPower rating (kW)3Water delivery temperature98°CTypical Heating and Cooling timesHeat up time to 98° C: 56 minutesHeat grow 80-98° C: 12 minutesCool down from 98° C-80° C: 167 minutesCool down from 98° C-80° C: 167 minutesCool down from 98° C-80° C: 167 minutesCutput per hourLitres: 31Pints: 55Cups: 145.7Recovery per minuteLitres: 0.5Pints: 0.88Tap height220mm from drip tray (tbc)Water feed hose length (Supplied) (m)2Voltage supply230V 50-60HzElectrical Supply 1N~+E current (A)13Plug typeUKFitted cable length (m)1.5None slip feet for safetyYesBoil dry thermal cut outYesCountry of manufactureMade in the British IslesTariff code8516101100	Packed dimensions (W x D x H) (mm)	773 x 490 x 432
Body construction430 grade Stainless SteelTank construction304 grade Stainless SteelDrip tray size (W x D x H) (mm)345 x 220 x 92Trim & drip tray plastic typeABSPower rating (kW)3Water delivery temperature98°CTypical Heating and Cooling timesHeat up time to 98° C: 56 minutes Heat from 80°98° C: 12 minutes Cool down from 98° C: 60° C: 167 minutesOutput per hourLitres: 31 Pints: 55 Cups: 206Rapid draw offLitres: 22 Pints: 38.7 Cups: 145.7Recovery per minuteLitres: 0.5 Pints: 0.88Tap height220mm from drip tray (tbc) %' BSPWater inlet pressure (bar)10 10Voltage supply230V 50-60HzElectrical Supply 1N°+E current (A) Pints: 0.5 Pints: 0.5813 Ping 13 Ping 230V 50-60HzPlug typeUK Fitted cable length (m) Fitted cable length (m)1.5 None slip feet for safety Yes Boil dry thermal cut out YesYes S516101100	Product weight (kg)	11.2
Tank construction304 grade Stainless SteelDrip tray size (W x D x H) (mm)345 x 220 x 92Trim & drip tray plastic typeABSPower rating (kW)3Water delivery temperature98°CTypical Heating and Cooling timesHeat up time to 98° C: 56 minutes Heat from 80-98° C: 12 minutes Cool down from 98° C-80° C: 167 minutesOutput per hourLitres: 31 Pints: 55 Cups: 206Rapid draw offLitres: 22 Pints: 38.7 Cups: 145.7Recovery per minutePints: 0.88Tap height220mm from drip tray (tbc)Water inlet connection fitting Water inlet pressure (bar)%" BSPWater inlet pressure (bar)10Voltage supply230V 50-60HzElectrical Supply 1N°+E current (A) Plug type13Plug typeUK Fitted cable length (m) None slip feet for safety Boil dry thermal cut out Country of manufactureYesBoil dry thermal cut out Country of manufactureYes	Packed weight (kg)	14.33
Drip tray size (W x D x H) (mm)345 x 220 x 92Trim & drip tray plastic typeABSPower rating (kW)3Water delivery temperature98°CTypical Heating and Cooling timesHeat up time to 98° C: 56 minutes Heat from 80-98° C: 12 minutes Cool down from 98° C-80° C: 167 minutesOutput per hourLitres: 31 Pints: 55 Cups: 206Rapid draw offLitres: 0.5 Pints: 0.58Tap height220mm from drip tray (tbc)Water inlet connection fitting Water inlet connection fitting Voltage supply%" BSPWater inlet pressure (bar)10 Voltage supplyVoltage supply Plug type230V 50-60HzElectrical Supply 1N~+E current (A) Boil dry thermal cut out Country of manufacture1.5 None slip feet for safety Yes Boil dry thermal cut out YesTair ficode8516101100	Body construction	430 grade Stainless Steel
Trim & drip tray plastic typeABSPower rating (kW)3Water delivery temperature98°CTypical Heating and Cooling timesHeat up time to 98° C: 56 minutesHeat up time to 98° C: 12 minutesCoutput per hourLitres: 31Pints: 55Cups: 206Rapid draw offLitres: 0.5Pints: 38.7Cups: 145.7Recovery per minuteLitres: 0.5Pints: 0.88Tap height220mm from drip tray (tbc)Water inlet connection fitting¾" BSPWater inlet pressure (bar)10Voltage supply230V 50-60HzElectrical Supply 1N~+E current (A)13Plug typeUKFitted cable length (m)1.5None slip feet for safetyYesBoil dry thermal cut outYesCountry of manufactureMade in the British IslesTariff code8516101100	Tank construction	304 grade Stainless Steel
Power rating (kW)3Water delivery temperature98°CTypical Heating and Cooling timesHeat up time to 98° C: 56 minutes Heat from 80-98° C: 12 minutes Cool down from 98° C-80° C: 167 minutesOutput per hourLitres: 31 Pints: 55 Cups: 206Rapid draw offLitres: 22 Pints: 38.7 Cups: 145.7Recovery per minuteLitres: 0.5 Pints: 0.58Tap height220mm from drip tray (tbc)Water inlet connection fitting Water inlet pressure (bar)%" BSPWater inlet pressure (bar)10 Voltage supplyVoltage supply230V 50-60HzElectrical Supply 1N~+E current (A) Fitted cable length (m)1.5 None slip feet for safety Yes Boil dry thermal cut out Yes Country of manufactureMace in the British Isles Tariff code8516101100	Drip tray size (W x D x H) (mm)	345 x 220 x 92
Water delivery temperature98°CTypical Heating and Cooling timesHeat up time to 98° C: 56 minutes Heat from 80-98° C: 12 minutes Cool down from 98° C-80° C: 167 minutesOutput per hourLitres: 31 Pints: 55 Cups: 206Rapid draw offLitres: 22 Pints: 38.7 Cups: 145.7Recovery per minuteLitres: 0.5 Pints: 0.88Tap height220mm from drip tray (tbc)Water inlet connection fitting Water feed hose length (Supplied) (m) Voltage supply2Kettrical Supply 1N~+E current (A) Fitted cable length (m)13 Plug typePlug type Boil dry thermal cut out Country of manufactureUK Yes StationBoil dry thermal cut out Tariff codeYes	Trim & drip tray plastic type	ABS
Typical Heating and Cooling timesHeat up time to 98° C: 56 minutes Heat from 80-98° C: 12 minutes Cool down from 98° C-80° C: 167 minutesOutput per hourLitres: 31 Pints: 55 Cups: 206Rapid draw offLitres: 22 Pints: 38.7 Cups: 145.7Recovery per minuteLitres: 0.5 Pints: 0.88Tap height220mm from drip tray (tbc)Water inlet connection fitting Water inlet pressure (bar)%" BSPWater inlet pressure (bar)10 Voltage supplyVoltage supply230V 50-60HzElectrical Supply 1N~+E current (A) Fitted cable length (m) None slip feet for safety Boil dry thermal cut out Country of manufactureYes S516101100	Power rating (kW)	
Heat from 80-98° C: 12 minutes Cool down from 98° C-80° C: 167 minutesOutput per hourLitres: 31 Pints: 55 Cups: 206Rapid draw offLitres: 22 Pints: 38.7 Cups: 145.7Recovery per minuteLitres: 0.5 Pints: 0.88Tap height220mm from drip tray (tbc)Water inlet connection fitting Water feed hose length (Supplied) (m) Voltage supply230V 50-60HzElectrical Supply 1N~+E current (A) Fitted cable length (m)1.5 None slip feet for safety VesNone slip feet for safety Country of manufactureYes Stiftion1100	Water delivery temperature	
Cool down from 98° C-80° C: 167 minutesOutput per hourLitres: 31 Pints: 55 Cups: 206Rapid draw offLitres: 22 Pints: 38.7 Cups: 145.7Recovery per minuteLitres: 0.5 Pints: 0.88Tap height220mm from drip tray (tbc)Water inlet connection fitting¾" BSP 10Water inlet pressure (bar)10Voltage supply230V 50-60HzElectrical Supply 1N~+E current (A)13 1.5Pitted cable length (m)1.5None slip feet for safetyYes Soil dry thermal cut outTariff codeMade in the British Isles S516101100	Typical Heating and Cooling times	
Output per hourLitres: 31Pints: 55Cups: 206Rapid draw offLitres: 22Pints: 38.7Cups: 145.7Recovery per minuteLitres: 0.5Pints: 0.88Tap height220mm from drip tray (tbc)Water inlet connection fitting¾" BSPWater feed hose length (Supplied) (m)2Voltage supply230V 50-60HzElectrical Supply 1N~+E current (A)13Plug typeUKFitted cable length (m)1.5None slip feet for safetyYesBoil dry thermal cut outYesCountry of manufactureMade in the British IslesTariff code8516101100		
Pints:55Cups:206Rapid draw offLitres:22Pints:38.7Cups:145.7Litres:0.5Pints:0.88Pints:120mm from drip tray (tbc)Water inlet connection fitting%" BSPWater feed hose length (Supplied) (m)2Max Water inlet pressure (bar)10Voltage supply230V 50-60HzElectrical Supply 1N~+E current (A)13Plug typeUKFitted cable length (m)1.5None slip feet for safetyYesBoil dry thermal cut outYesCountry of manufactureMade in the British IslesTariff code8516101100		
Cups:206Rapid draw offLitres:22Pints:38.7Cups:145.7Recovery per minuteLitres:0.5Pints:0.88Tap height220mm from drip tray (tbc)Water inlet connection fitting¾" BSPWater feed hose length (Supplied) (m)2Max Water inlet pressure (bar)10Voltage supply230V 50-60HzElectrical Supply 1N~+E current (A)13Plug typeUKFitted cable length (m)1.5None slip feet for safetyYesBoil dry thermal cut outYesCountry of manufactureMade in the British IslesTariff code8516101100	Output per hour	
Rapid draw offLitres: 22Pints: 38.7Cups: 145.7Recovery per minuteLitres: 0.5Pints: 0.88Tap height220mm from drip tray (tbc)Water inlet connection fitting¾" BSPWater feed hose length (Supplied) (m)2Max Water inlet pressure (bar)10Voltage supply230V 50-60HzElectrical Supply 1N~+E current (A)13Plug typeUKFitted cable length (m)1.5None slip feet for safetyYesBoil dry thermal cut outYesCountry of manufactureMade in the British IslesTariff code8516101100		
Pints:38.7Cups:145.7Recovery per minuteLitres:0.5Pints:0.88Tap height220mm from drip tray (tbc)Water inlet connection fitting¾" BSPWater feed hose length (Supplied) (m)2Max Water inlet pressure (bar)10Voltage supply230V 50-60HzElectrical Supply 1N~+E current (A)13Plug typeUKFitted cable length (m)1.5None slip feet for safetyYesBoil dry thermal cut outYesCountry of manufactureMade in the British IslesTariff code8516101100		
Cups:145.7Recovery per minuteLitres:0.5Pints:0.88220mm from drip tray (tbc)Water inlet connection fitting¾" BSPWater feed hose length (Supplied) (m)2Max Water inlet pressure (bar)10Voltage supply230V 50-60HzElectrical Supply 1N~+E current (A)13Plug typeUKFitted cable length (m)1.5None slip feet for safetyYesBoil dry thermal cut outYesCountry of manufactureMade in the British IslesTariff code8516101100	Rapid draw off	
Recovery per minuteLitres: 0.5 Pints: 0.88Tap height220mm from drip tray (tbc)Water inlet connection fitting¾" BSPWater feed hose length (Supplied) (m)2Max Water inlet pressure (bar)10Voltage supply230V 50-60HzElectrical Supply 1N~+E current (A)13Plug typeUKFitted cable length (m)1.5None slip feet for safetyYesBoil dry thermal cut outYesCountry of manufactureMade in the British IslesTariff code8516101100		
Pints:0.88Tap height220mm from drip tray (tbc)Water inlet connection fitting¾" BSPWater feed hose length (Supplied) (m)2Max Water inlet pressure (bar)10Voltage supply230V 50-60HzElectrical Supply 1N~+E current (A)13Plug typeUKFitted cable length (m)1.5None slip feet for safetyYesBoil dry thermal cut outYesCountry of manufactureMade in the British IslesTariff code8516101100		•
Tap height220mm from drip tray (tbc)Water inlet connection fitting¾" BSPWater feed hose length (Supplied) (m)2Max Water inlet pressure (bar)10Voltage supply230V 50-60HzElectrical Supply 1N~+E current (A)13Plug typeUKFitted cable length (m)1.5None slip feet for safetyYesBoil dry thermal cut outYesCountry of manufactureMade in the British IslesTariff code8516101100	Recovery per minute	
Water inlet connection fitting%/" BSPWater feed hose length (Supplied) (m)2Max Water inlet pressure (bar)10Voltage supply230V 50-60HzElectrical Supply 1N~+E current (A)13Plug typeUKFitted cable length (m)1.5None slip feet for safetyYesBoil dry thermal cut outYesCountry of manufactureMade in the British IslesTariff code8516101100		
Water feed hose length (Supplied) (m)2Max Water inlet pressure (bar)10Voltage supply230V 50-60HzElectrical Supply 1N~+E current (A)13Plug typeUKFitted cable length (m)1.5None slip feet for safetyYesBoil dry thermal cut outYesCountry of manufactureMade in the British IslesTariff code8516101100		
Max Water inlet pressure (bar)10Voltage supply230V 50-60HzElectrical Supply 1N~+E current (A)13Plug typeUKFitted cable length (m)1.5None slip feet for safetyYesBoil dry thermal cut outYesCountry of manufactureMade in the British IslesTariff code8516101100	-	
Voltage supply230V 50-60HzElectrical Supply 1N~+E current (A)13Plug typeUKFitted cable length (m)1.5None slip feet for safetyYesBoil dry thermal cut outYesCountry of manufactureMade in the British IslesTariff code8516101100	• • • • • •	
Electrical Supply 1N~+E current (A)13Plug typeUKFitted cable length (m)1.5None slip feet for safetyYesBoil dry thermal cut outYesCountry of manufactureMade in the British IslesTariff code8516101100		
Plug typeUKFitted cable length (m)1.5None slip feet for safetyYesBoil dry thermal cut outYesCountry of manufactureMade in the British IslesTariff code8516101100		
Fitted cable length (m)1.5None slip feet for safetyYesBoil dry thermal cut outYesCountry of manufactureMade in the British IslesTariff code8516101100		
None slip feet for safetyYesBoil dry thermal cut outYesCountry of manufactureMade in the British IslesTariff code8516101100		
Boil dry thermal cut outYesCountry of manufactureMade in the British IslesTariff code8516101100		
Country of manufactureMade in the British IslesTariff code8516101100		
Tariff code 8516101100	·	
Warranty 1 year Parts & Labour		
	Warranty	1 year Parts & Labour

