



## BURCO 20L TWIN TAP COUNTERTOP AUTO FILL WATER BOILER - With Filtration

WRAS  
APPROVED  
PRODUCT



- ✓ **Easy-to-replace internal filtration system**  
Inhibits limescale build-up and other impurities to prolong the life of the appliance and provide the best tasting beverage.
- ✓ **Extra Large 20L tank capacity & 2 independently controlled taps**  
Ideal for high traffic areas and premises requiring a large volume of instant hot water.
- ✓ **Manufactured in the British Isles**
- ✓ **Advanced LCD touch control screen**  
Provides great user functionality and the advanced diagnostics alert the user when the filter cartridge needs to be replaced.
- ✓ **Variable water temperature range**  
Simply select your preferred setting between 80°C and 98°C.
- ✓ **Energy saving "Eco" Mode**  
Reduces running costs.
- ✓ **Powerful 6kW heating element**  
For rapid heat-up time.
- ✓ **Hard-wiring required – single phase**
- ✓ **WRAS Approved**



SKU CODE:	PRODUCT CODE:	DESCRIPTION:
444442465	BC PLS AF CT 20L TT 6KW UK	Burco 20L Twin Tap Countertop Auto Fill Water Boiler – with filtration



## FULL SPECIFICATION - Burco 20L Twin Tap Countertop Auto Fill Water Boiler – with filtration

SKU code	444442465
GDPA code	BC PLS AF CT 20L TT 6KW UK
EAN code	5052263024656
Type	Countertop
Capacity (L)	20
Unit dimensions (W x D x H) (mm)	344 x 464 x 689 (depth includes taps & drip tray)
Packed dimensions (W x D x H) (mm)	773 x 490 x 432
Product weight (kg)	11.7
Packed weight (kg)	14.73
Body construction	430 grade Stainless Steel
Tank construction	304 grade Stainless Steel
Drip tray size (W x D x H) (mm)	345 x 220 x 92
Trim & drip tray plastic type	ABS
Power rating (kW)	6
Water delivery temperature	80°C - 98°C
Typical Heating and Cooling times	Heat up time to 98° C: 34 minutes Heat from 80-98° C: 7 minutes Cool down from 98° C-80° C: 167 minutes
Output per hour	Litres: 60 Pints: 106 Cups: 400
Tap height	220mm from drip tray
Inline water filter	Yes
Replaceable water filter	Yes
Water inlet connection fitting	¾" BSP
Water feed hose length (Supplied) (m)	2
Max Water inlet pressure (bar)	10
Voltage supply	220-240V 50-60Hz
Hardwiring required	Yes – single phase only
Electrical Supply 1N~+E current (A)	26 amp
Plug type	N/A - Hard Wired
Fitted cable length (m)	N/A - Hard Wired
None slip feet for safety	Yes
Boil dry thermal cut out	Yes
Country of manufacture	Made in the British Isles
Tariff code	8516101100
WRAS approved	Yes
Warranty	Up to 2 years Parts & Labour

