



- 2 year warranty
- **NEW** molded rack guide on 350mm and 400mm units, giving partial double skin
- **NEW** molded wash tank for easy cleaning
- **NEW** Surface scrap Tray filters on all new models.
- **NEW** dual flow wash pump on 400 & 450 models
- **NEW** Alarms menu
- **NEW** Parallel quick release wash & rinse arm design
- Bright LED display with soft touch controls
- Accurate detergent and rinse aid peristaltic dosing as standard
- Supplied with two open cup/glass racks
- Three standard cycle time options. SP button for further cycle options
- Cycle times can be tailored to site requirements
- Selectable energy saving mode
- Selectable thermostop ensures optimum rinse temperatures
- Automatic self-cleaning at end of service
- Operational self-diagnostics
- Twin traffic light display indicates machine status
- Drain pump optional on all models
- Reduced water consumption compared to previous models



## Technical

- Standard voltage 240V – single phase
- Supplied with molded 13amp plug
- Suitable for hot (max 50°C) or cold\* water supply at 2 to 4 bar dynamic supply pressure
- Wash temperature 60°C (adjustable)
- Rinse temperature 65°C (adjustable)
- Cycle times 90/120/150 seconds



Drain pump versions require a waste up-stand for correct operation.

Restrictive waste connections should be avoided for all installations.

\*Machines fitted to cold water supplies will not be capable of running repeated short cycles, the cycle time will automatically be extended to allow recovery of correct operating temperatures.

Model	Rack size mm	Useable Height mm	Dimensions mm W x D x H	Cycle Options	Power kW	Amps Required
<b>C352</b>	350	240	400 x 495 x 590 <sup>#</sup>	3 Cycles	2.9	13
<b>C352D</b>	As C352 above with fitted drain pump					
<b>C402</b>	390	300	440 x 540 x 665 <sup>#</sup>	3 Cycles	2.8	13
<b>C402D</b>	As C402 above with fitted drain pump					
<b>C452</b>	450	280	525 x 560 x 705 <sup>#</sup>	3 Cycles	2.9	13
<b>C452D</b>	As C452 above with fitted drain pump					

# Height excludes adjustable feet which will add 5 to 15mm.