

C Range | undercounter



7



C501



C511




C515 WSD

- 2 year warranty
- C515 WSD with internal automatic water softener and drain pump as standard
- C511 & C515 WSD with breaktank
- Bright LED display with soft touch controls
- Accurate detergent and rinse aid peristaltic dosing as standard
- C501 supplied with two open cup/glass racks
- C511 & C515 WSD supplied with one pegged and one open rack
- Three selectable cycle options plus special application cycles options on 500mm rack machines
- Cycle times can be tailored to site requirements
- Selectable energy saving mode
- Selectable thermostop ensures optimum rinse temperatures
- Automatic self-cleaning at end of service
- Surface scrap tray filters on 500mm rack models
- Operational self-diagnostics
- Twin traffic light display indicate machine status
- Drain pump optional on all models
- Partial double skinned reducing noise and heat loss

Technical

- Standard voltage 240V – single phase
- 500mm rack models can be supplied for 3 phase
- Suitable for hot (max 50°C) or cold* water supply at 2 to 4 bar dynamic supply pressure
- Wash temperature 60°C (adjustable)
- Rinse temperature C501 65°C (adjustable)
- Rinse temperature C511 & C515 WSD 78°C (adjustable)
- Cycle times between 70 & 240 secs, dependent on model

*Machines fitted to cold water supplies will not be capable of running repeated short cycles, the cycle time will automatically be extended to allow recovery of correct operating temperatures.



Model	Rack size mm	Useable Height mm	Dimensions mm W x D x H	Cycle Options	Power kW	Amps Required	Price
C501	500	320	580 x 610 x 815 [#]	3 Cycles	2.6/4.5/6.5	13/20/30 ^{##}	£2,720
C501D	As C501 above with fitted drain pump						£2,880
C511	500	320	580 x 610 x 815 [#]	3 Cycles	2.6/4.5/6.5	13/20/30 ^{##}	£2,890
C511D	As C511 above with fitted drain pump						£3,080
C515 WSD	500	320	580 x 610 x 815 [#]	3 cycles	2.6/4.5/6.5	13/20/30 ^{##}	£3,170

[#] Height excludes adjustable feet which will add 10 to 20mm.

^{##} Machines will be supplied for 30 amp supply as standard, if 13 or 20 amp ordered they will be supplied with original cable and without plug. Standard 13 amp UK 3 pin plugs will be **unsuitable** for cable supplied.

See page 10 for ancillary items.