

British Manufacturing since 1957



The Professionals Choice

CTS11F

SureFlow Counter-Top Water Boiler with built in Filtration



FULL SPECIFICATION



SureFlow Counter-Top Automatic Fill Water Boiler with Built in Filtration

| - | 0 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 |
|---|---|
| Type | Countertop - Standard Range |
| Country of Design & Manufacture | UK |
| CAPACITY, WEIGHTS & DIMENSIONS: | |
| Capacity (Litres) | 11 |
| Unit dimensions (W x D x H) mm | 243 x 510 x 610 (depth includes drip-tray) |
| Packed dimensions (W x D x H) mm | 360 x 595 x 735 |
| Tap clearance mm | 190mm |
| Product weight - empty (kg) | 13.2 |
| Product weight – full (kg) | 26 |
| Packed weight (kg) | 17 |
| CONSTRUCTION: | |
| Outer fabrication (body) construction | 304 grade Stainless Steel (Superbrush polish) |
| Tank construction | 304 & 316 grade Stainless Steel |
| Tank wall thickness | 0.9mm |
| Drip-tray | 304 grade Stainless Steel – (Mirror polish) |
| ELECTRICAL: | Grand Comment Control (minute prince) |
| Power rating (kW) | 3 |
| Voltage supply | 220-230 V (50-60Hz) |
| Electrical supply | Single-phase, N & E (13A) |
| Plug type | UK standard 3-pin |
| Fitted cable length (m) | 1.7m |
| PLUMBING: | 1.7(11 |
| | 2/4" DCD |
| Water inlet connection: | 3/4" BSP |
| Food quality, flexible mains water hose | 1.6 metre long, (3/4"BSP) |
| Mains water pressure range | 2 – 7 bar (28psi – 100psi) |
| Overflow/waste connection: | Front via drip-tray (or rear using kit not supplied) |
| PERFORMANCE: | |
| Water temperature delivered | 96°C (default) – can be adjusted if required |
| Heat up time to working temperature | 32 mins (full tank capacity) |
| Output per hour (@ default temperature setting) | 27 Litres (higher output/hour if set @ lower temperature) |
| Rapid draw-off | 10 Litres |
| Recovery per minute | 0.5 Litres |
| Stand-by power loss (idle mode) | 0.087 kW/h |
| FILTRATION: | |
| Multi-Filter (taste & odour, sediment & reduces lime-scale) | Yes |
| Filter Benefits | Latest triple-action; removes sediment & impurities such as |
| | chlorine and reduces limescale build-up |
| Mechanical sediment filtration | 3 micron |
| Filter counter programmable | Yes (soft, medium & hard water settings) |
| OTHER FEATURES: | , |
| Tank-baffle plates – unique design aids heat recovery & | Yes |
| reduces steam emissions to atmosphere | |
| Early warning lime-scale diagnostics (via display) | Yes - Basic (from Jan 2015) |
| Dual safety protection | Yes - Over-boil & boil-dry protection |
| STANDARDS & APPROVALS: | Post Star Son a Son ary protostion |
| WRAS approved | Yes |
| EMC Tested and Certified (EN 55014 & EN 61000) | Yes |
| Electrical Safety Tested and Certified to BS standard | Yes (BS EN 60335-1 & 2) |
| · · · · · · · · · · · · · · · · · · · | 1 63 (D3 EN 00333-1 & 2) |
| WARRANTY & AFTER-SALES: | 2 Veer parte 9 Johann |
| Guarantee | 2 Year parts & labour |
| Spare parts, filters & accessories | Same day despatch (if ordered before 3pm) |

Instanta Limited T: 01704 501114 F: 01704 501115 E: sales@instanta.com



