

Technical data sheet for

## EC40M10 ON THE SK40-10A STAND

Full Size 10 Tray Manual / Electric Combi Oven on a Stainless Steel Stand



### STANDARD FEATURES

- Electric direct steam version
- 10 x 1/1 GN tray capacity
- 10 x 600mm x 400mm tray capacity
- 70mm tray spacing
- Compact 812mm wide
- 14kW heating power
- Hand shower with fittings and connections included
- Electro-mechanical controls to set time, temperature and operation mode
- Temperature range 50-260°C
- Manual timer range up to 120 minutes
- Selector for convection, steam and combi modes
- Door open rapid cool down function
- Manual cleaning system with externally-connected hand shower
- Autoreverse (automatic inversion of the direction of the fan) for perfectly uniform cooking
- Manual chamber venting
- LED chamber lighting
- Perfectly smooth cooking chamber walls with rounded edges
- Double-glazed door with thermo-reflective tempered glass
- Adjustable hinges for optimal door seal
- Triple action water filter cartridge and filter head included

### ACCESSORIES

- Turbofan SK40-10A Oven Stand



#### EC40M10

Unit shall be a Blue Seal electrically heated Turbofan direct steam injection combination convection steam oven. The oven shall have a stainless steel oven chamber with 10 x 1/1 GN capacity, 14.5kW power rating and two auto-reversing direction fans. Oven door shall be vented safe touch and feature LED oven chamber lighting. Electro-mechanical controls shall provide Convection, Steam, and Combi cooking mode selection, door open rapid cool down function, temperature control 50-260 C, manual timer for up to 120 minutes, and a manual oven vent open/close switch. A water hand shower shall be included as standard. Oven shall be able to be bench mounted on 100mm feet or mounted on Turbofan oven stand model SK40-10A. Unit shall be supplied in 100% recyclable shipping packaging.

#### SK40-10A

Unit shall be a Blue Seal Turbofan stainless steel oven stand. The stand shall be constructed from stainless steel tube with 4 adjustable feet. It shall be fitted with 6 tray runners suitable for 1/1 GN pans and 600 x 400 trays. The stand shall be fully compatible with, and support, Turbofan Combi Oven models EC40M10 and EC40D10. Unit shall be supplied in 100% recyclable shipping packaging.

### EC40M10 Full Size Manual/ Electric Combi Oven on a Stainless Steel Stand

#### Dimensions

Width	812mm
Depth	725mm
Height	1170mm
Weight	104kg

#### Packed Dimensions

Width	910mm
Depth	865mm
Height	1265mm
Weight	117kg
Volume	1.0 m <sup>3</sup>

#### Shelves

1/1 GN	10
Shelf Spacings	70mm

#### Power connection requirements

Multi pole circuit breaker and all pole disconnection isolator switch installed near the appliance.

#### Electrical requirements

400-415V, 50Hz, 3P+N+E, 14.5kW, 20A/ph

#### Water Supply

1 x R3/4 connections  
Cold Water  
Flow pressure 200-500 kPa  
Shut off valve with back flow prevention

#### Water Quality

- total hardness 60-90 ppm
- pH > 7.5
- Cl-(chloride) <30 ppm
- temperature < 50°C

#### Drain

- Funnel waste trap/tundish required
- 40 mm outlet
- Minimum fall/slope for waste 4°

### SK40-10A Stainless Steel Stand

All stainless steel welded frame oven stand for Turbofan EC4010 tray Series Combi ovens  
6 position tray runners standard  
4 height adjustable feet  
Supplied CKD for assembly on site

#### External Dimensions (SK40-10A Oven Stand)

Width	810mm
Height	697mm
Depth	650mm

#### Nett Weight (SK40-10A Oven Stand)

19kg

#### Packing Data (SK40-10A Oven Stand)

22kg	
0.11m <sup>3</sup>	
Width	830mm
Height	880mm
Depth	160mm

#### INSTALLATION CLEARANCES

Installation requirements (for precise installation instructions, please refer to the unit's installation manual).

- rear 50mm
- right 50mm\*
- left 50mm\*

\*For recessed installations a minimum of 500mm clearance must be maintained on one of the sides.

If heat sources are located near the Turbofan Combi, ensure that a minimum distance of 400mm is maintained.

Install in accordance with local body regulations only on horizontal surfaces and not against combustible walls.




blue-seal.co.uk  
turbofanoven.com

United Kingdom  
Blue Seal Limited  
Unit 67  
Gravelly Business Park  
Gravelly  
Birmingham B24 8TQ  
England  
Telephone 0121-327 5575  
Facsimile 0121-327 9711  
sales@blue-seal.co.uk  
www.blue-seal.co.uk

Australia  
Moffat Pty Limited  
740 Springvale Road  
Mulgrave, Victoria 3170  
Australia  
Telephone 03-9518 3888  
Facsimile 03-9518 3833  
vsales@moffatcom.au  
www.moffatcom.au

New Zealand  
Moffat Limited  
Christchurch  
45 Illinois Drive  
Izone Business Hub  
Rolleston 7675  
Telephone +64 3-983 6600  
Facsimile +64 3-983 6660  
sales@moffatco.nz  
www.moffatco.nz



Manufactured by:  
Moffat Limited  
45 Illinois Drive, Izone Business Hub  
Rolleston 7675, New Zealand

In line with policy to continually develop and improve its products, Moffat Limited reserves the right to change specifications and design without notice.