

SILVERLINK 600



GS6/TR - Lincat Silverlink 600 Electric Counter-top Griddle - Twin Zone - Half-Ribbed Plate - W 600 mm - 4.0 kW Whether you're cooking eggs, bacon, burgers or vegetables, the versatile Silverlink 600 Electric Griddle won't let you down.

- Flexibility of a half smooth, half ribbed plate to give attractive branding lines to your food whilst being able to cook eggs on the smooth half of the plate
- Two separately controlled heat zones give you the option of operating either zone independently to provide a smaller cooking area during quiet periods as well as offering versatility when cooking two separate meals simultaneously
- Hard wearing 12 mm think machined steel plate providing even heat distribution and excellent heat retention
- Thermostatically controlled to give accurate temperatures during the cooking process for consistent results
- Removable front drainer drawer which also makes for easy cleaning. Ideal for busy establishments
- The plate is fully welded into the frame to prevent leaks and places where food and carbon can build up

Specifications

Number of Heat Zones

Grill Plate Surface Type

Grill Plate Material

2

Steel

Half-ribbed

Summary **Power and Performance** Total Power kW **Brand** Lincat 4.0 Range Silverlink 600 Temperature Range °C 50-250 **Power Type** Electric **IP Rating** IP23 **Unit Type** Counter-top Cooking Area (Width x Depth) mm 562 x 405 Available in UK Only **Temperature Control** Nο Mechanical **UK Warranty** 2 Years Parts and Labour Warranty **Export Warranty** Contact your local dealer GTIN 5056105104858 **Key Specifications**

| Weights and Dimensions | | Supply Connections | Supply Connections | |
|---------------------------|-----|---------------------------------------|------------------------|--|
| Unit Height (External) mm | 330 | Requires Installation | Yes | |
| Unit Width (External) mm | 600 | Requires Electrical Supply | Yes | |
| Unit Depth (External) mm | 620 | UK 3 Pin Plug | No | |
| Net Weight Kg | 40 | Requires Hardwiring | Yes | |
| | | Electrical Supply Rating Watts | 4,000 | |
| | | Single Phase Amps | 17.4 | |
| | | Single Phase Voltage | 230 | |
| | | Three Phase Amps | L1=8.7; L2=8.7; L3=N/A | |
| | | Three Phase Voltage | 400 | |
| | | | | |

| | | Three Phase Voltage | 400 |
|------------------|------|---------------------|-----|
| Shipping | | | |
| Packed Weight Kg | 53.1 | | |
| Packed Height cm | 63.5 | | |
| Packed Width cm | 70 | | |
| Packed Depth cm | 70 | | |

Product Code: GS6/TR Page Number: 1 Print Date: 05/02/2020



SILVERLINK 600


Available Accessories


| CC6 | Lincat Silverlink 600 Free-standing Ambient Open-Top Pedestal with Doors - W 600 mm |
|------|---|
| CN6 | Lincat Silverlink 600 Free-standing Ambient Open-Top Pedestal without Doors - W 600 mm |
| HC6 | Lincat Silverlink 600 Free-standing Heated Open-Top Pedestal with Doors - W 600 mm - 0.5 kW |
| HCL6 | Lincat Silverlink 600 Free-standing Heated Pedestal with Legs and Doors - W 600 mm - 0.5 kW |
| SB6 | 600 GRIDDLE SPLASHB |


Lincat Silverlink 600 Free-standing Floor Stand - for units W 600 mm $\,$

Technical Picture

SLS6













Lincat Limited

Whisby Road,

Lincoln, LN6 3QZ,

United Kingdom

Company No: 2175448

A member company of

Customer Care

Tel: +44 1522 875500

Email: care@lincat.co.uk

Export Customers

Tel: +44 1522 503250

Email: export@lincat.co.uk

Opening Hours

Monday - Friday:

8.30am - 5pm



Print Date: 05/02/2020 Product Code: GS6/TR Page Number: 3