

## **SILVERLINK 600**



GS7/C - Lincat Silverlink 600 Electric Counter-top Griddle - Chrome Plate -W 750 mm - 6.0 kW

Whether you're cooking eggs, bacon, burgers or vegetables, the versatile Silverlink 600 Electric Griddle won't let you down.

- Two separately controlled heat zones give you the option of operating either zone independently to provide a smaller cooking area during quiet periods as well as offering versatility when cooking two separate meals simultaneously
- Chrome surface heats up quicker than standard griddles with less energy loss as well as reduced energy radiation, keeping the kitchen cooler for staff and reducing pressure on the ventilation
- Transfers heat to food more efficiently than a standard griddle

- Thermostatically controlled to give accurate temperatures during the cooking process for consistent results
- Removable front drainer drawer which also makes for easy cleaning. Ideal for busy establishments
- The plate is fully welded into the frame to prevent leaks and places where food and carbon can build up

_				400	
S	ne	CIT	ica	HO	ns

	Power and Performance	
Lincat	Total Power kW	6.0
Silverlink 600	Temperature Range °C	50-250
Electric	IP Rating	IP23
Counter-top	Cooking Area (Width x Depth) mm	712 × 405
No	Temperature Control	Mechanical
2 Years Parts and Labour Warranty		
Contact your local dealer		
5056105104902		
	Silverlink 600 Electric Counter-top No 2 Years Parts and Labour Warranty Contact your local dealer	Silverlink 600  Electric  Counter-top  No  2 Years Parts and Labour Warranty Contact your local dealer  Temperature Range °C  IP Rating  Cooking Area (Width x Depth) mm  Temperature Control

Key Specifications		Capacity	
Number of Heat Zones	2	Product Output per Hour	190 x 115g [4oz] burgers [frozen], 140 x
Grill Plate Surface Type	Smooth	·	225g[8oz
Grill Plate Material	Chrome		

Grill Plate Surface Type Grill Plate Material	Smooth Chrome	Product Output per Hour	225g[8oz
Weights and Dimensions		Supply Connections	
Unit Height (External) mm	330	Requires Installation	Yes
Unit Width (External) mm	750	Requires Electrical Supply	Yes
Unit Depth (External) mm	620	UK 3 Pin Plug	No
Net Weight Kg	48	Requires Hardwiring	Yes
		Electrical Supply Rating Watts	6,000
		Single Phase Amps	26.1
		Single Phase Voltage	230
		Three Phase Amps	L1=13.0; L2=13.0; L3=N/A
		Three Phase Voltage	400
Shipping			

Packed Weight Kg	67.7
Packed Height cm	63.5
Packed Width cm	85.5
Packed Depth cm	70

### **Available Accessories**

Product Code: GS7/C Page Number: 1 Print Date: 05/02/2020



# **SILVERLINK 600**


### **Available Accessories**


CN7	Lincat Silverlink 600 Free-standing Ambient Open-Top Pedestal without Doors - W 750 mm
HC7	Lincat Silverlink 600 Free-standing Heated Open-Top Pedestal with Doors - W 750 mm - 0.5 kW
HCL7	Lincat Silverlink 600 Free-standing Heated Pedestal with Legs and Doors - W 750 mm - 0.75 kW
SB7	750 GRIDDLE SPLASHB


Lincat Silverlink 600 Free-standing Floor Stand - for units W 750 mm

### **Technical Picture**

SLS7













**Lincat Limited** 

Whisby Road,

Lincoln, LN6 3QZ,

United Kingdom

**Company No:** 2175448

A member company of

**Customer Care** 

**Tel:** +44 1522 875500

Email: care@lincat.co.uk

**Export Customers** 

**Tel:** +44 1522 503250

Email: export@lincat.co.uk

**Opening Hours** 

Monday - Friday:

8.30am - 5pm



**Print Date:** 05/02/2020 Product Code: GS7/C Page Number: 3