

# **SILVERLINK 600**



GS7/R - Lincat Silverlink 600 Electric Counter-top Griddle - Half-Ribbed Plate - W 750 mm - 6.0 kW Whether you're cooking eggs, bacon, burgers or vegetables, the versatile Silverlink 600 Electric Griddle won't let you down.

- Flexibility of a half smooth, half ribbed plate to give attractive branding lines to your food whilst being able to cook eggs on the smooth half of the plate
- Two separately controlled heat zones give you the option of operating either zone independently to provide a smaller cooking area during quiet periods as well as offering versatility when cooking two separate meals simultaneously
- Hard wearing 12 mm think machined steel plate providing even heat distribution and excellent heat retention
- Thermostatically controlled to give accurate temperatures during the cooking process for consistent results
- Removable front drainer drawer which also makes for easy cleaning. Ideal for busy establishments
- The plate is fully welded into the frame to prevent leaks and places where food and carbon can build up

Sn	ACII	icat	ne
UΡ	CUII	IGa	LC

Summary		Power and Performance	
Brand	Lincat	Total Power kW	6.0
Range	Silverlink 600	Temperature Range °C	50-250
Power Type	Electric	IP Rating	IP33
Unit Type	Counter-top	Cooking Area (Width x Depth) mm	712 x 405
Available in UK Only	No	Temperature Control	Mechanical
UK Warranty	2 Years Parts and Labour Warranty		
Export Warranty	Contact your local dealer		
GTIN	5056105104940		

Key Specifications		Capacity		
Number of Heat Zones	2	Product Output per Hour	190 x 115g [4oz] burgers [frozen], 140 x	
Grill Plate Surface Type	Half-ribbed	. rounds output poi moui	225g[8oz	
Grill Plate Material	Steel			

Weights and Dimensions		Supply Connections	
Unit Height (External) mm	330	Requires Installation	Yes
Unit Width (External) mm	750	Requires Electrical Supply	Yes
Unit Depth (External) mm	620	UK 3 Pin Plug	No
Net Weight Kg	49.2	Requires Hardwiring	Yes
		<b>Electrical Supply Rating Watts</b>	6,000
		Single Phase Amps	26.1
		Single Phase Voltage	230
		Three Phase Amps	L1=13.0; L2=13.0; L3=N/A
		Three Phase Voltage	400

## Shipping

Packed Weight Kg	69
Packed Height cm	63.5
Packed Width cm	85.5
Packed Depth cm	70

#### **Available Accessories**

. . . . .

Product Code: GS7/R Page Number: 1 Print Date: 05/02/2020



# **SILVERLINK 600**

### **Available Accessories**

CN7 Lincat Silverlink 600 Free-standing Ambient Open-Top Pedestal without Doors - W 750 mm


HC7 Lincat Silverlink 600 Free-standing Heated Open-Top Pedestal with Doors - W 750 mm - 0.5 kW


HCL7 Lincat Silverlink 600 Free-standing Heated Pedestal with Legs and Doors - W 750 mm - 0.75 kW


SB7 750 GRIDDLE SPLASHB

**SLS7** Lincat Silverlink 600 Free-standing Floor Stand - for units W 750 mm

### **Technical Picture**













**Lincat Limited** 

Whisby Road,

Lincoln, LN6 3QZ,

United Kingdom

**Company No:** 2175448

A member company of

**Customer Care** 

**Tel:** +44 1522 875500

Email: care@lincat.co.uk

**Export Customers** 

**Tel:** +44 1522 503250

Email: export@lincat.co.uk

**Opening Hours** 

Monday - Friday:

8.30am - 5pm

