Halcyon AMH35 D

undercounter



Halcyon **AMH35 D** Features

- 1 year warranty
- Drain pump as standard
- Accurate detergent and rinse aid peristaltic dosing pumps
- Dosing set up by fascia controls
- Easy clean parallel wash and rinse arm assembly
- Optional surface scrap tray filters
- Large three button control



Two 350 x 350mm open cup/ glass racks supplied as standard – capable of holding 10 pint glasses.

Additional racks can be purchased at point of order:

Q902302B



Gravity drain version available: **AMH35**

For additional information contact our Sales Team on

T: 0345 130 8070 E: sales@maidaid-halcyon.co.uk or visit www.maidaid.co.uk

Halcyon AMH35 D

undercounter







Technical Data


Dimensions (W x D x H)	mm	400 x 495 x 590 + Feet
Feet height	mm	10-20
Rack size	mm	350 x 350
Maximum useable height	mm	240
Door opening	mm	260
Theoretical productivity	Racks/h	30
Effective productivity	Racks/h	24*


Wash tank element	kW	1.4
Boiler element	kW	2.6
Wash pump	kW	0.18
Tank capacity	L	7
Noise emission	dB	≤ 55

Packaging Specs

Gross weight	Kg	31
Cubic volume	m³	0.25
Dim. $(W \times D \times H)$	mm	470 x 590 x 750

Installation Diagram - All services must be within 1 meter





Power Supply

Installed power	AMP	kW	
230V - 50Hz - 1N	13*	2.8	

^{*}Supplied with 13A moulded plug and lead

Pumped waste into upstand, maximum height 700mm



Water Connection

Inlet water pressure	Bar	2 to 4
Flow rate L/Min	L/Min	6
Water inlet temp	°C	10 to 50
Water connection	BSP	3/4"
Waste connection	Ø	Int 16.8/ext 21.6

Cycle Information

Number of standard cycles		1
Standard cycles times	Sec	120
Special cycle		N/A
Self-cleaning cycle		Partial
Water consumption per cycle	L	1.9
Wash temperature	°C	60
Rinse temperature	°C	65

For additional information contact our Sales Team on

T: 0345 130 8070 E: sales@maidaid-halcyon.co.uk or visit www.maidaid.co.uk

^{*}Allowing 30 seconds for reloading Cycle times may vary depending on local conditions/services