



## PRO-LITE

# LD1 Two Ring Boiling Top

### Key features

- Two fast-acting circular hotplates
  - Fast heat up and good heat retention
- One piece stainless steel plunged hob
  - Contains spillages and easy to clean
- Supplied with 13A plug
  - Easy install, ready to go as soon as unpacked
- Compact at only 300mm wide
  - Ideal for smaller, less demanding kitchens
  - Can be mounted on a suitable counter or stand

### Accessories

- LD129 open shelf unit
- LD115 hotcupboard pedestal

### Similar Models

- LD2 four hotplate boiling top
- E350/32 two hotplate boiling top
- E3122 two hotplate boiling top

## Specification *details*

Electrical rating (kW)	3
Electrical supply voltage	230V ~
Electrical current split (A)	L1: 13
Weight (kg)	11
Packed weight (kg)	13
Dimensions (w x d x h - mm)	300 x 630 x 285
Packed dimensions (w x d x h - mm)	350 x 650 x 450
GTIN number	5056466905637

### Installation notes

Adequate ventilation must be provided to supply sufficient fresh air for combustion and to allow easy removal of any such products that may present a risk to health. Please consult current legislation for details that relate to specific locations.

Install unit on a level, fireproof surface in a well-lit, draught free position. A clearance of 150mm should be observed between appliance and any combustible wall.