



PRO-LITE

Hotcupboard Pedestals

Key features

- Spring-loaded door hinges
 - Minimises energy loss during operation
- Ideal for hot holding food or plate warming
 - Offers flexibility & additional functionality to cookline
- Easy install
 - Comes supplied with 13A plug
- Pro-Lite countertop models can be mounted atop these units
 - More versatility within the same footprint

Models

- LD115 - 300mm wide
- LD117 - 600mm wide



Specification details

	LD115	LD117
Electrical rating (kW)	0.48	0.48
Electrical supply voltage	230V~	230V~
Electrical current split (A)	L1: 2.1	L1: 2.1
Internal dimensions (w x d x h - mm)		
Weight (kg)	18	28
Packed weight (kg)	20	30
Dimensions (w x d x h - mm)	300 x 550 x 650	600 x 550 x 650
Packed dimensions (w x d x h - mm)	350 x 600 x 800	650 x 600 x 800
GTIN number	5056466905651	5056466905668

Installation notes

Adequate ventilation must be provided to supply sufficient fresh air for combustion and to allow easy removal of any such products that may present a risk to health. Please consult current legislation for details that relate to specific locations.

Install unit on a level, fireproof surface in a well-lit, draught free position. A clearance of 150mm should be observed between appliance and any combustible wall.