



LDF - Lincat Lynx 400 Electric Counter-top Single Tank General Purpose Fryer - 1 Basket -W 270 mm - 3.0 kW

The 3kW Lynx 400 Electric Counter Top Fryer is designed to plug in and play, which means that you'll be producing perfect fried chips in no time at all.

- Removable control head to aid easy cleaning and maintenance
- Thermostatically controlled to give better and more consistent cooking results
- Safety thermostat to prevent overheat
- Stainless steel tanks for easy cleaning


- Comes with batter plate to allow open frying
- Nickel plated baskets for easy cleaning
- Plug and play for an easy installation


Againg Lincat Total Power kW 3.0 Againg Lynx 400 Temperature Range °C 130-190 Power Type Electric IP Rating IP23 Unit Type Counter-top Temperature Control Mechanical Available in UK Only No UK Warranty 2 Years Parts and Labour Warranty Export Warranty Contact your local dealer STIN 5056105101024 Cey Specifications Capacity Aumber of Baskets 1 Aumber of Tanks 1 Aumber of Tanks 1 Capacity Litres 4.0 Product Output per Hour 12mm[frozen]. 1lkg chips Stravity Filtration No Pumped Filtration No Weights and Dimensions Supply Connections Supply Connections Requires Installation No Init Width (External) mm 270 Requires Electrical Supply Yes Unit Depth (External) mm 417 UK 3 Pin Plug Yes				
Range Lynx 400 Temperature Range °C 130-190 Power Type Electric IP Rating IP23 Unit Type Counter-top Temperature Control Mechanical Available in UK Only No UK Warranty 2 Years Parts and Labour Warranty Export Warranty Contact your local dealer GTIN 5056105101024 Key Specifications Capacity Number of Baskets 1 Siravity Filtration No Pumped Filtration No Weights and Dimensions Supply Connections Unit Height (External) mm 270 Requires Installation No Unit Weight (External) mm 417 Requires Electrical Supply Yes Unit Depth (External) mm 417 Requires Hardwiring No Net Weight Kg Requires Hardwiring No Electrical Supply Rating Watts 3,000 Single Phase Amps 13.0	Summary		Power and Performance	
Power Type Electric IP Rating IP23 Unit Type Counter-top Temperature Control Mechanical Available in UK Only No UK Warranty 2 Years Parts and Labour Warranty Export Warranty Contact your local dealer GTIN 5056105101024 Key Specifications Capacity Number of Baskets 1 Number of Tanks 1 Gravity Filtration No Pumped Filtration No Weights and Dimensions Supply Connections Unit Height (External) mm 270 Requires Electrical Supply Yes Unit Depth (External) mm 417 UK 3 Pin Plug Yes Net Weight Kg 8 Requires Installation No Electrical Supply Rating Watts 3,000 Electrical Supply Rating Watts 3,000 Single Phase Amps 13.0	Brand	Lincat	Total Power kW	3.0
Unit Type Available in UK Only UK Warranty Export Warranty Contact your local dealer 6TIN Capacity Capacity No Weights and Dimensions Unit Height (External) mm Unit Width (External) mm Unit Width (External) mm No Unit Depth (External) mm No	Range	Lynx 400	Temperature Range °C	130-190
Available in UK Only UK Warranty Export Warranty Export Warranty GTIN Contact your local dealer 5056105101024 Key Specifications Capacity Number of Baskets 1 Product Output per Hour 2mm[chil] Capacity Litres 4.0 Weights and Dimensions Supply Connections Unit Height (External) mm Unit Width (External) mm Unit Width (External) mm Vorume Hour Vorume Interpolation Vorume Hour Vorume Hour Vorume Interpolation Vorume Vorume Interpolation Vorume Vorume Hour Vorume Interpolation Vorume Vorume Interpolation Vorume	Power Type	Electric	IP Rating	IP23
UK Warranty Export Warranty GTIN Contact your local dealer 5056105101024 Key Specifications Capacity Number of Baskets 1 Product Output per Hour I2mm [chill Capacity Litres 4.0 Weights and Dimensions Unit Height (External) mm Unit Width (External) mm Unit Depth (External) mm Voluti D	Unit Type	Counter-top	Temperature Control	Mechanical
Export Warranty GTIN Contact your local dealer 5056105101024 Key Specifications Capacity Number of Baskets Number of Tanks Gravity Filtration No No Capacity Litres 4.0 Weights and Dimensions Supply Connections Unit Height (External) mm Unit Width (External) mm 270 Requires Installation No	Available in UK Only	No		
Key Specifications Capacity	UK Warranty	2 Years Parts and Labour Warranty		
Key Specifications Capacity Number of Baskets Number of Tanks I Gravity Filtration No Pumped Filtration No Weights and Dimensions Unit Height (External) mm Unit Width (External) mm Various Electrical Supply Ves Ves Net Weight Kg 8kg chips - 12mm[frozen], 11kg chips 12mm[chil 4.0 Supply Connections Requires Installation No Ves Ves Ves Ves Ves Net Weight (External) mm Ves	Export Warranty	Contact your local dealer		
Number of Baskets Number of Tanks 1 Capacity Filtration No Pumped Filtration No Weights and Dimensions Unit Height (External) mm Unit Width (External) mm Variety Electrical Supply Unit Depth (External) mm Variety Electrical Supply Ves	GTIN	5056105101024		
Number of Tanks Gravity Filtration No Weights and Dimensions Unit Height (External) mm Unit Width (External) mm 270 Requires Electrical Supply Unit Depth (External) mm 417 No Weight Kg 8 Requires Hardwiring Requires Hardwiring Requires Hardwiring Electrical Supply Rating Watts 3,000 Single Phase Amps 12mm[chil 12mm[chil	Key Specifications		Capacity	
Number of Tanks Gravity Filtration Pumped Filtration No Weights and Dimensions Unit Height (External) mm Unit Width (External) mm Unit Weight (External) mm Very Market (External) market (External) mm Very Market (External) market (Ext	Number of Baskets	1	Product Output per Hour	8kg chips - 12mm [frozen], 11kg chips
Pumped Filtration No Weights and Dimensions Supply Connections Unit Height (External) mm 315 Requires Installation No Unit Width (External) mm 270 Requires Electrical Supply Yes Unit Depth (External) mm 417 UK 3 Pin Plug Yes Net Weight Kg 8 Requires Hardwiring No Electrical Supply Rating Watts 3,000 Single Phase Amps 13.0	Number of Tanks	1	1 Todaet Output per Tioui	12mm [chil
Weights and Dimensions Supply Connections Requires Installation No Unit Weight (External) mm 270 Requires Electrical Supply Yes Unit Depth (External) mm 417 UK 3 Pin Plug Yes Net Weight Kg 8 Requires Hardwiring No Electrical Supply Rating Watts 3,000 Single Phase Amps 13.0	Gravity Filtration	No	Capacity Litres	4.0
Unit Height (External) mm 315 Requires Installation No Unit Width (External) mm 270 Requires Electrical Supply Yes Unit Depth (External) mm 417 UK 3 Pin Plug Yes Net Weight Kg Requires Hardwiring No Electrical Supply Rating Watts 3,000 Single Phase Amps 13.0	Pumped Filtration	No		
Unit Width (External) mm 270 Requires Electrical Supply Yes Unit Depth (External) mm 417 UK 3 Pin Plug Yes Net Weight Kg Requires Hardwiring Electrical Supply Rating Watts 3,000 Single Phase Amps 13.0	Weights and Dimensions		Supply Connections	
Unit Depth (External) mm 417 UK 3 Pin Plug Yes Net Weight Kg 8 Requires Hardwiring No Electrical Supply Rating Watts 3,000 Single Phase Amps 13.0	Unit Height (External) mm	315	Requires Installation	No
Net Weight Kg 8 Requires Hardwiring No Electrical Supply Rating Watts 3,000 Single Phase Amps 13.0	Unit Width (External) mm	270	Requires Electrical Supply	Yes
Electrical Supply Rating Watts 3,000 Single Phase Amps 13.0	Unit Depth (External) mm	417	UK 3 Pin Plug	Yes
Single Phase Amps 13.0	Net Weight Kg	8	Requires Hardwiring	No
			Electrical Supply Rating Watts	3,000
Single Phase Voltage 230			Single Phase Amps	13.0
			Single Phase Voltage	230
	Shipping			
Snipping	Packed Weight Kg	13		
	Packed Height cm	42		
Packed Weight Kg 13	Packed Width cm	48		


Technical Picture

Packed Depth cm











Lincat Limited

Whisby Road,

Lincoln, LN6 3QZ,

United Kingdom

Company No: 2175448

A member company of

Customer Care

Tel: +44 1522 875500

Email: care@lincat.co.uk

Export Customers

Tel: +44 1522 503250

Email: export@lincat.co.uk

Opening Hours

Monday - Friday:

8.30am - 5pm

