

www.lec-commercial.co.uk

# **EFFICIEN-C SINGLE DOOR BOTTLE COOLER HINGED 150L BLACK**

122262 3422









- Enables faster temperature recovery after door
- Environmentally friendly refrigerant
- **Double glazed safety glass** Designed to withstand the demands of a busy back bar area
- **Self-closing doors** Maximises energy efficiency to keep stock cool
- 1 Removable and replaceable door seal For easy cleaning and increased product life-span
- $\checkmark$ 2 adjustable shelves For added versatility for bottles and cans of different sizes
- $\checkmark$ **External temperature display** No need to open the door to check the temperature
- ✓ **LED Internal light** Shows contents more effectively with a simple on/off switch
- Lockable For security of contents

**DESCRIPTION:** 

#### SKU CODE: **PRODUCT CODE:**

44443190 BC6097K LED

## EfficienC Single Door Bottle Cooler Hinged 150L Black LED

**Glen Dimplex Professional Appliances** Stoney Lane, Prescot, Merseyside, L35 2XW

() ()

Tel: 0844 815 3755 Email: info@gdpa.co.uk



## www.lec-commercial.co.uk

3955

清潔無影

### FULL SPECIFICATION – BC6097K LED EfficienC Single Door Bottle Cooler Hinged 150L Black



SKU code	44443190
EAN code	5052263031906
GDPA code	BC6097K LED
Number of doors	1
Door opening type	Hinged
Colour	Black
Product dimensions (mm) (WxDxH)	600x500x900
Packed dimensions (mm) (WxDxH)	640x580x950
Product weight (kg)	48
Packed weight (kg)	55
Material – exterior finish	Black painted steel
Material – interior finish	Stainless steel
Gross capacity (L)	150
Capacity (330ml bottles)	106
Capacity (330ml cans)	154
Internal dimensions (WxDxH)	520x385x750
Internal temperature Range	$+2^{\circ}$ C to $+10^{\circ}$ C
Maximum ambient operating temperature	Up to +38°C
Defrost type	Automatic
Forced air cooling (fan)	Yes
Self closing door(s)	Yes
Door open depth (mm)	1090
Replacement door seal	Yes
Controller type	Electronic
External temperature type	Yes
Number of shelves	2
Shelf size (mm) (WxD)	500x345
Shelf material	Chrome finish wire shelves
Front adjustable feet	Yes
LED Interior light	Yes
Light activation	Switch on exterior
Fitted lock	Yes
Insulation thickness (mm)	40
Insulation material	Pentane
Voltage supply (V)	220/240
UK 3 pin plug	Yes
Fitted cable length (m)	1.5
Refrigerant type	R600a
CFC free	Yes
HFC free	Yes
HCFC free	Yes
Ammonia free	Yes