







DOUBLE DOOR BOTTLE COOLER HINGED 225L SILVER







- ✓ Temperature range of +2° C to +10° C

 Ideal for storing a variety of drinks and wine at preferred temperature
- Forced air cooling
 Enables faster temperature recovery after door opening or restocking
- ✓ R600a refrigerant

 Environmentally friendly refrigerant
- ✓ **Double glazed safety glass**Designed to withstand the demands of a busy back bar area
- ✓ Self-closing doors

 Maximises energy efficiency to keep stock cool
- ✓ Removable and replaceable door seal For easy cleaning and increased product life-span
- ✓ 4 adjustable shelves
 For added versatility for bottles and cans of different sizes
- ✓ External temperature display

 No need to open the door to check the temperature
- ✓ LED Internal light

 Shows contents more effectively with a simple on/off switch
- ✓ Lockable

 For security of contents



SKU CODE: PRODUCT CODE: DESCRIPTION:

444443197 BC9007G LED LED Double Door Bottle Cooler Hinged 225L Silver







FULL SPECIFICATION – BC9007G LED Double Door Bottle Cooler Hinged 225L Silver



Tel: 0844 815 3755

Email: info@gdpa.co.uk

SKU code	444443197
EAN code	5052263031975
GDPA code	BC9007G LED
Number of doors	2
Door opening type	Hinged
Colour	Silver
Product dimensions (mm) (WxDxH)	900x500x900
Packed dimensions (mm) (WxDxH)	910x575x1000
Product weight (kg)	59
Packed weight (kg)	69
Material – exterior finish	Silver painted steel
Material – interior finish	Metal
Gross capacity (L)	225
Capacity (330ml bottles)	180
Capacity (330ml cans)	252
Internal dimensions (WxDxH)	820x385x750
Internal temperature Range	+2° C to +10° C
Maximum ambient operating temperature	Up to +38° C
Defrost type	Automatic
Forced air cooling (fan)	Yes
Self closing door(s)	Yes
Door open depth (mm)	960
Replacement door seal	Yes
Controller type	Electronic
External temperature type	Yes
Number of shelves	4
Shelf size (mm) (WxD)	385x345
Shelf material	Chrome finish wire shelves
Front adjustable feet	Yes
LED Interior light	Yes
Light activation	Switch on exterior
Fitted lock	Yes
Insulation thickness (mm)	40
Insulation material	Pentane
Voltage supply (V)	220/240
UK 3 pin plug	Yes
Fitted cable length (m)	1.5
Refrigerant type	R600a
CFC free	Yes
HFC free	Yes
HCFC free	Yes
Ammonia free	Yes