


www.lec-commercial.co.uk

DOUBLE DOOR BOTTLE COOLER SLIDING 225L BLACK



lee





- **Temperature range of +2° C to +10° C** Ideal for storing a variety of drinks and wine at preferred temperature
- **Forced air cooling** Enables faster temperature recovery after door opening or restocking
- R600a refrigerant
 Environmentally friendly refrigerant
- Double glazed safety glass
 Designed to withstand the demands of a busy back bar area
- Self-closing doors
 Maximises energy efficiency to keep stock cool
- 4 adjustable shelves
 For added versatility for bottles and cans of different sizes
- External temperature display
 No need to open the door to check the temperature
- LED Internal light Shows contents more effectively with a simple on/off switch
- Lockable
 For security of contents

 SKU CODE:
 PRODUCT CODE:

 444443198
 BC9027K LED

DESCRIPTION:

LED Double Door Bottle Cooler Sliding 225L Black

Glen Dimplex Professional Appliances Stoney Lane, Prescot, Merseyside, L35 2XW Tel: 0844 815 3755 Email: info@gdpa.co.uk



www.lec-commercial.co.uk

3955

清潔無影

FULL SPECIFICATION – BC9027K LED Double Door Bottle Cooler Sliding 225L Black



SKU code	44443198
EAN code	5052263031982
GDPA code	BC9027K LED
Number of doors	2
Door opening type	Sliding
Colour	Black
Product dimensions (mm) (WxDxH)	900x500x900
Packed dimensions (mm) (WxDxH)	910x575x1000
Product weight (kg)	59
Packed weight (kg)	69
Material – exterior finish	Black painted steel
Material – interior finish	Metal
Gross capacity (L)	225
Capacity (330ml bottles)	180
Capacity (330ml cans)	252
Internal dimensions (WxDxH)	820x385x750
Internal temperature Range	+2° C to +10° C
Maximum ambient operating temperature	Up to +38°C
Defrost type	Automatic
Forced air cooling (fan)	Yes
Self closing door(s)	Yes
Door open depth (mm)	- N-
Replacement door seal	No
Controller type	Electronic
External temperature type	Yes
Number of shelves	4 295-245
Shelf size (mm) (WxD)	385x345 Chrome finish wire shelves
Shelf material	Yes
Front adjustable feet LED Interior light	Yes
Light activation	Switch on exterior
Fitted lock	Yes
Insulation thickness (mm)	40
Insulation material	Pentane
Voltage supply (V)	220/240
UK 3 pin plug	Yes
Fitted cable length (m)	1.5
Refrigerant type	R600a
CFC free	Yes
HFC free	Yes
HCFC free	Yes
Ammonia free	Yes