

www.lec-commercial.co.uk









- Temperature range of +2° C to +10° C
 Ideal for storing a variety of drinks and wine at preferred temperature
- **Forced air cooling** Enables faster temperature recovery after door opening or restocking
- R600a refrigerant
 Environmentally friendly refrigerant
 - **Double glazed safety glass** Designed to withstand the demands of a busy back bar area
- **Self-closing doors** Maximises energy efficiency to keep stock cool
- Removable and replaceable door seal
 For easy cleaning and increased product life-span
- 2 adjustable shelves
 For added versatility for bottles and cans of different sizes
- External temperature display
 No need to open the door to check the temperature
- LED Internal light
 Shows contents more effectively with a simple on/off switch
 - Lockable For security of contents

SKU CODE: PRODUCT CODE:

444443193 BC9097ST LED

DESCRIPTION:

EfficienC Double Door Bottle Cooler Hinged 225L Stainless Steel

Glen Dimplex Professional Appliances Stoney Lane, Prescot, Merseyside, L35 2XW Tel: 0844 815 3755 Email: info@gdpa.co.uk





www.lec-commercial.co.uk

3821

清潔無影

FULL SPECIFICATION – BC9097ST LED EfficienC Double Door Bottle Cooler Hinged 225L Stainless Steel



SKU code444443193EAN code5052263031937GDPA codeBC/9075TNumber of doors2Door opening typeHingedColourStainless steelProduct dimensions (mm) (WxDxH)900x500x900Packed dimensions (mm) (WxDxH)940x580x9500Product weight (kg)62Packed diveight (kg)69Material - exterior finishStainless steelMaterial - interior finishStainless steelGross capacity (L)225Capacity (30ml cans)252Internal dimensions (WxDxH)820x385x750Internal temperature Range42° C Cto 410° CMaxima ambient operating temperatureUp to 438° CDofrost typeAutomaticPorced air cooling (fan)YesSelf closing door(s)YesSubmer of shelves4Number of shelves4Shelf size (mm) (WxD)385x345Shelf materialChrome finish wire shelvesFront adjustable feetYesLiD Internal dimensions (mm)960Replacement door sealYesLiD Internal temperatureYesNumber of shelves4Shelf size (mm) (WxD)220/240Voltage supply (V)220/240Ukt astivationSwitch on exteriorFitted colabeYesInsulation thickness (mm)40Insulation thickness (mm)40Insulation thickness (mm)40Insulation thickness (mm)400Insulation thickness (mm)<		LEP#F3023F
GDPA codeBC9097STNumber of doors2Door opening typeHingedColourStainless steelProduct dimensions (mm) (WxDxH)900x500x000Packed dimensions (mm) (WxDxH)940x580x950Product weight (kg)62Packed weight (kg)69Material - exterior finishStainless steelMaterial - interior finishStainless steelGross capacity (L)225Capacity (330m) cans)252Internal dimensions (MxDxH)820x385x750Internal dimensions (MxDxH)820x385x750Internal temperature Range+2° C to +10° CMaterial - interior finishStainless steelGoros capacity (1)252Internal temperature Range+2° C to +10° CMaximu ambient operating temperatureUp to +38° CDefrost typeAutomaticForced air cooling (fan)YesSelf closing door(s)YesDoor open depth (mm)960Replacement door sealYesNumber of shelves4Shelf faze (mm) (WxD)385x345Shelf materialChrome finish wire shelvesFront adjustable feetYesLight activationSwitch on exteriorFitted lockYesLight activationSwitch on exteriorFitted lock (mm)40Insulation thickness (mm)40Insulation thickness (mm)40Insulation thickness (mm)1.5Fitted cable length (m)1.5Fitted cable length (m) <th>SKU code</th> <th>44443193</th>	SKU code	44443193
Number of doors2Door opening typeHingedColourStainless steelProduct dimensions (mm) (WxDxH)900x500x900Packed dimensions (mm) (WxDxH)940x580x950Product weight (kg)62Packed weight (kg)69Material – interior finishStainless steelGross capacity (L)225Capacity (330ml bottles)180Capacity (340ml bottles)180Capacity (350ml bottles)180Door open depth (mn)960Replacement door sealYesController typeYesController typeYesNumber of shelves4Shelf size (mm) (WxD)385x345Shelf materialChrome finish wire shelvesFront adjustable feetYesLib Unterior lightYesHitted lockYesInsulation materialPentaneVoltage supply (V)	EAN code	5052263031937
Door opening typeHingedColourStainless steelProduct dimensions (mm) (WxDxH)900x500x900Packed dimensions (mm) (WxDxH)940x580x950Product weight (kg)62Packed weight (kg)69Material – exterior finishStainless steelMaterial – exterior finishStainless steelGross capacity (L)225Capacity (330ml cons)252Internal dimensions (WxDxH)820x385x750Internal dimensions (WxDxH)820x385x750Internal dimensions (WxDxH)820x385x750Self colsing door(s)YesDefrost typeAutomaticForced air cooling (fan)YesSelf colsing door(s)YesOor open depth (mm)960Replacement door sealYesNumber of shelves4Shelf size (mm) (WxD)385x345Shelf fize (mm) (WxD)385x345Shelf fize (mm) (WxD)385x345Shelf ize (mm) (WxD)325x245Ib Interior lightYesLiD Interior lightYesLiD Interior lightYesUp to +32/240YesLiD Interior lightYesKitd colse (mm)40Insulation materialPentaneVoltage supply (V)220/240UK 3 pin plugYesFitted colse length (m)1.5Refrigerant typeKesHCC freeYesHCC freeYes	GDPA code	BC9097ST
ColourStainless steelProduct dimensions (mm) (WxDxH)900x500x900Packed dimensions (mm) (WxDxH)940x580x950Product weight (kg)62Packed weight (kg)69Material – exterior finishStainless steelMaterial – interior finishStainless steelGross capacity (L)225Capacity (330ml bottles)180Capacity (330ml bottles)180Capacity (330ml bottles)252Internal dimensions (WxDxH)820x385x750Internal dimensions (WxDxH)960Replacement door sealYesDoor open depth (mm)960Replacement door sealYesShelf size (mm) (WxD)385x345Shelf size (mm) (WxD)385x345Shelf materialChrome finish wire shelvesFront adjustable feetYesLib Interior lightYesLib Interior lightYesLib Interior lightYesLib Interior lightPentaneVohtage supply (V)220/240UK3 pin plugYesFitted cookYes <th>Number of doors</th> <th>2</th>	Number of doors	2
ColourStainless steelProduct dimensions (mm) (WxDxH)900x500x900Packed dimensions (mm) (WxDxH)940x580x950Product weight (kg)62Packed weight (kg)69Material – exterior finishStainless steelMaterial – interior finishStainless steelGross capacity (L)225Capacity (330ml bottles)180Capacity (330ml bottles)180Capacity (330ml bottles)252Internal dimensions (WxDxH)820x385x750Internal dimensions (WxDxH)960Replacement door sealYesDoor open depth (mm)960Replacement door sealYesShelf size (mm) (WxD)385x345Shelf size (mm) (WxD)385x345Shelf materialChrome finish wire shelvesFront adjustable feetYesLib Interior lightYesLib Interior lightYesLib Interior lightYesLib Interior lightPentaneVohtage supply (V)220/240UK3 pin plugYesFitted cookYes <th>Door opening type</th> <th>Hinged</th>	Door opening type	Hinged
Packed dimensions (mm) (WxDxH)940x580x950Product weight (kg)62Packed weight (kg)69Material – exterior finishStainless steelMaterial – interior finishStainless steelGross capacity (L)225Capacity (330ml bottles)180Capacity (330ml bottles)180Capacity (330ml bottles)252Internal dimensions (WxDxH)820x385x750Internal dimensions (WxDxH)820x385x750Internal temperature Range+2° C to +10° CMaximum ambient operating temperatureUp to +38° CDefrost typeAutomaticForced air cooling (fan)YesSelf closing door(s)YesDoor open depth (mm)960Replacement door sealYesController typeElectronicExternal temperature typeYesNumber of shelves4Shelf materialChrome finish wire shelvesFront adjustable feetYesLight activationSwitch on exteriorFitted lockYesInsulation thicknes (mm)40Insulation materialPentaneVoltage supply (V)220/240UK3 pin plugYesFitted cable length (m)1.5Refrigerant typeR600aCFreeYesHICC freeYes		Stainless steel
Product weight (kg)62Packed weight (kg)69Material – exterior finishStainless steelMaterial – interior finishStainless steelGross capacity (L)225Capacity (30ml bottles)180Capacity (30ml cans)252Internal dimensions (WxDxH)820x385x750Internal temperature Range+2° C to +10° CMakimum ambient operating temperatureUp to +38° CDefrost typeAutomaticForced air cooling (fan)YesSelf closing door(s)YesDoor open depth (mm)960Replacement door sealYesController typeElectronicExternal temperature typeYesNumber of shelves4Shelf size (mm) (WxD)385x345Shelf materialChrome finish wire shelvesFront adjustable feetYesLight activationSwitch on exteriorFitted lockYesInsulation thickness (mm)40Insulation thickness (mm)40Insulation thickness (mm)1.5Kefrigerant typeRefoloaVoltag esupply (V)220/240UX 3 pin plugYesFitted cable length (m)1.5Refrigerant typeRefoloaCCf freeYesHFC freeYesHFC freeYes	Product dimensions (mm) (WxDxH)	900x500x900
Packed weight (kg)69Material – exterior finishStainless steelMaterial – interior finishStainless steelGross capacity (L)225Capacity (330ml bottles)180Capacity (330ml cans)252Internal dimensions (WxDxH)820x385x750Internal temperature Range+2° C to +10° CMaximum ambient operating temperatureUp to +38° CDefrost typeAutomaticForced air cooling (fan)YesSelf closing door(s)YesDoor open depth (mm)960Replacement door sealYesController typeYesNumber of shelves4Shelf size (mm) (WxD)385x345Shelf size (mm) (WxD)385x345Shelf size (mm) (MxD)Switch on exteriorFitted lockYesLight activationSwitch on exteriorFitted lockYesUnsulation materialPentaneVoltage supply (V)220/240UK3 pin plugYesFitted cale length (m)1.5Refrigerant typeKesHFC freeYesHFC freeYesHFC freeYes		940x580x950
Material - exterior finishStainless steelMaterial - interior finishStainless steelGross capacity (1)225Capacity (330ml bottles)180Capacity (330ml cans)252Internal temperature Range+2° C to +10° CMaximum ambient operating temperatureUp to +38° CDefrost typeAutomaticForced air cooling (fan)YesSelf closing door(s)YesDoor open depth (nm)960Replacement door sealYesController typeElectronicExternal temperature typeYesNumber of shelves4Shelf size (nm) (WxD)385x345Shelf materialChrome finish wire shelvesFront adjustable feetYesLight activationSwitch on exteriorHitted lockYesUight activation40Insulation materialPentaneVoltage supply (V)220/240UK 3 pin plugYesFitted cable length (m)1.5Refrigerant typeR600aCF freeYesHFC freeYes	Product weight (kg)	62
Material – interior finishStainless steelGross capacity (1)225Capacity (330ml bottles)180Capacity (330ml cans)252Internal dimensions (Wx0xH)820x385x750Internal temperature Range+2° C to +10° CMaximum ambient operating temperatureUp to +38° CDefrost typeAutomaticForced air cooling (fan)YesSelf closing door(s)YesDoor open depth (mm)960Replacement door sealYesController typeElectronicExternal temperature typeYesNumber of shelves4Shelf size (mm) (WxD)385x345Shelf materialChrome finish wire shelvesFront adjustable feetYesLight activationSwitch on exteriorFitted lockYesInsulation materialPentaneVoltage supply (V)220/240UX3 pin plugYesFitted cable length (m)1.5Refrigerant typeR600aCFfreeYesHFC freeYesHFC freeYes		69
Gross capacity (L)225Capacity (30ml bottles)180Capacity (30ml cans)252Internal dimensions (WxDxH)820x385x750Internal temperature Range $+2^\circ$ C to $+10^\circ$ CMaximum ambient operating temperatureUp to $+38^\circ$ CDefrost typeAutomaticForced air cooling (fan)YesSelf closing door(s)YesDoor open depth (mm)960Replacement door sealYesController typeElectronicExternal temperature typeYesNumber of shelves4Shelf size (mm) (WxD)385x345Shelf materialChrome finish wire shelvesFront adjustable feetYesLight activationSwitch on exteriorFitted lockYesUight activation220/240Uk3 pin plugYesVoltage supply (V)220/240UK3 pin plugYesFitted cable length (m)1.5Refrigerant typeR600aCFreeYesHCF freeYesHCF freeYes	Material – exterior finish	Stainless steel
Capacity (330ml bottles)180Capacity (330ml bottles)252Internal dimensions (WxDxH)820x385x750Internal temperature Range \pm^2 ° C to $\pm 10^\circ$ ° CMaximum ambient operating temperatureUp to $\pm 38^\circ$ ° CDefrost typeAutomaticForced air cooling (fan)YesSelf closing door(s)YesDoor open depth (mm)960Replacement door sealYesController typeElectronicExternal temperature typeYesNumber of shelves4Shelf size (mm) (WxD)385x345Shelf materialChrome finish wire shelvesFront adjustable feetYesLight activationSwitch on exteriorFitted lockYesInsulation materialPentaneVoltage supply (V)220/240UK 3 pin plugYesFitted cable length (m)1.5Refrigerant typeYesHFC freeYesHFC freeYes	Material – interior finish	Stainless steel
Capacity (330ml cans)252Internal dimensions (WXDXH)820x385x750Internal temperature Range+2° C to +10° CMaximum ambient operating temperatureUp to +38° CDefrost typeAutomaticForced air cooling (fan)YesSelf closing door(s)YesDoor open depth (mm)960Replacement door sealYesController typeElectronicExternal temperature typeYesNumber of shelves4Shelf size (mm) (WXD)385x345Shelf size (mm) (WXD)385x345Shelf materialChrome finish wire shelvesFront adjustable feetYesLED Interior lightYesLight activationSwitch on exteriorFitted lockYesInsulation materialPentaneVoltage supply (V)220/240UK 3 pin plugYesFitted cable length (m)1.5Refrigerant typeR600aCFC freeYesHFC freeYesHCFC freeYes	Gross capacity (L)	225
Internal dimensions (WxDxH)820x385x750Internal temperature Range+2° C to +10° CMaximum ambient operating temperatureUp to +38° CDefrost typeAutomaticForced air cooling (fan)YesSelf closing door(s)YesDoor open depth (mm)960Replacement door sealYesController typeElectronicExternal temperature typeYesNumber of shelves4Shelf size (mm) (WxD)385x345Shelf materialChrome finish wire shelvesFront adjustable feetYesLight activationSwitch on exteriorFitted lockYesInsulation thickness (mm)40Insulation thickness (mm)40Insulation thickness (mm)1.5Fitted cable length (m)1.5Refrigerant typeRefolaceFitted cable length (m)1.5Refrigerant typeYesHFC freeYesHFC freeYes		180
Internal temperature Range+2° C to +10° CMaximum ambient operating temperatureUp to +38° CDefrost typeAutomaticForced air cooling (fan)YesSelf closing door(s)YesDoor open depth (mm)960Replacement door sealYesController typeElectronicExternal temperature typeYesNumber of shelves4Shelf size (mm) (WxD)385x345Shelf materialChrome finish wire shelvesFront adjustable feetYesLight activationSwitch on exteriorFitted lockYesInsulation thickness (mm)40Insulation thickness (mm)40UX 3p in plugYesFitted cable length (m)1.5Refrigerant typeR600aCFC freeYesHFC freeYesHFC freeYes	Capacity (330ml cans)	252
Maximum ambient operating temperatureUp to +38° CDefrost typeAutomaticForced air cooling (fan)YesSelf closing door(s)YesDoor open depth (mm)960Replacement door sealYesController typeElectronicExternal temperature typeYesNumber of shelves4Shelf size (mm) (WxD)385x345Shelf materialChrome finish wire shelvesFront adjustable feetYesLED Interior lightYesInsulation thickness (mm)40Insulation materialPentaneVoltage supply (V)220/240UK 3pin plugYesFitted cable length (m)1.5Refrigerant typeR600aCFF reeYesHFC freeYesHCFC freeYes	Internal dimensions (WxDxH)	
Defrost typeAutomaticForced air cooling (fan)YesSelf closing door(s)YesDoor open depth (mm)960Replacement door sealYesController typeElectronicExternal temperature typeYesNumber of shelves4Shelf size (mm) (WxD)385x345Shelf size (mm) (WxD)385x345Shelf materialChrome finish wire shelvesFront adjustable feetYesLED Interior lightYesLight activationSwitch on exteriorFitted lockYesInsulation materialPentaneVoltage supply (V)220/240UK 3 pin plugYesFitted cable length (m)1.5Refrigerant typeRefoloaaHFC freeYesHFC freeYesHFC freeYes	Internal temperature Range	
Forced air cooling (fan)YesSelf closing door(s)YesDoor open depth (mm)960Replacement door sealYesController typeElectronicExternal temperature typeYesNumber of shelves4Shelf size (mm) (WxD)385x345Shelf materialChrome finish wire shelvesFront adjustable feetYesLight activationSwitch on exteriorFitted lockYesInsulation thickness (mm)40Insulation materialPentaneVoltage supply (V)220/240UK 3 pin plugYesFitted cable length (m)1.5Refrigerant typeR600aCF freeYesHFC freeYesHFC freeYes	Maximum ambient operating temperature	Up to +38°C
Self closing door(s)YesDoor open depth (mm)960Replacement door sealYesController typeElectronicExternal temperature typeYesNumber of shelves4Shelf size (mm) (WxD)385x345Shelf materialChrome finish wire shelvesFront adjustable feetYesLight activationSwitch on exteriorFitted lockYesInsulation thickness (mm)40Insulation materialPentaneVoltage supply (V)220/240UK 3 pin plugYesFitted cable length (m)1.5Refrigerant typeR600aCF freeYesHFC freeYesHFC freeYes		Automatic
Door open depth (mm)960Replacement door sealYesController typeElectronicExternal temperature typeYesNumber of shelves4Shelf size (mm) (WxD)385x345Shelf materialChrome finish wire shelvesFront adjustable feetYesLED Interior lightYesLight activationSwitch on exteriorFitted lockYesInsulation thickness (mm)40Insulation materialPentaneVoltage supply (V)220/240UK 3 pin plugYesFitted cable length (m)1.5Refrigerant typeRe600aCFC freeYesHFC freeYes		Yes
Replacement door sealYesController typeElectronicExternal temperature typeYesNumber of shelves4Shelf size (mm) (WxD)385x345Shelf materialChrome finish wire shelvesFront adjustable feetYesLED Interior lightYesLight activationSwitch on exteriorFitted lockYesInsulation thickness (mm)40Insulation materialPentaneVoltage supply (V)220/240UK 3 pin plugYesFitted cable length (m)1.5Refrigerant typeR600aCFC freeYesHFC freeYesHFC freeYes		Yes
Controller typeElectronicExternal temperature typeYesNumber of shelves4Shelf size (mm) (WxD)385x345Shelf materialChrome finish wire shelvesFront adjustable feetYesLED Interior lightYesLight activationSwitch on exteriorFitted lockYesInsulation thickness (mm)40Insulation materialPentaneVoltage supply (V)220/240UK 3 pin plugYesFitted cable length (m)1.5Refrigerant typeR600aCFC freeYesHFC freeYes	Door open depth (mm)	960
External temperature typeYesNumber of shelves4Shelf size (mm) (WxD)385x345Shelf materialChrome finish wire shelvesFront adjustable feetYesLED Interior lightYesLight activationSwitch on exteriorFitted lockYesInsulation thickness (mm)40Insulation materialPentaneVoltage supply (V)220/240UK 3 pin plugYesFitted cable length (m)1.5Refrigerant typeR600aCFC freeYesHFC freeYesHCFC freeYes		Yes
Number of shelves4Shelf size (mm) (WxD)385x345Shelf materialChrome finish wire shelvesFront adjustable feetYesLED Interior lightYesLight activationSwitch on exteriorFitted lockYesInsulation thickness (mm)40Insulation materialPentaneVoltage supply (V)220/240UK 3 pin plugYesFitted cable length (m)1.5Refrigerant typeR600aCFC freeYesHFC freeYesHFC freeYes		Electronic
Shelf size (mm) (WxD)385x345Shelf materialChrome finish wire shelvesFront adjustable feetYesLED Interior lightYesLight activationSwitch on exteriorFitted lockYesInsulation thickness (mm)40Insulation materialPentaneVoltage supply (V)220/240UK 3 pin plugYesFitted cable length (m)1.5Refrigerant typeR600aCFC freeYesHFC freeYesHCFC freeYes	External temperature type	Yes
Shelf materialChrome finish wire shelvesFront adjustable feetYesLED Interior lightYesLight activationSwitch on exteriorFitted lockYesInsulation thickness (mm)40Insulation materialPentaneVoltage supply (V)220/240UK 3 pin plugYesFitted cable length (m)1.5Refrigerant typeR600aCFC freeYesHFC freeYesHCFC freeYesHCFC freeYes		4
Front adjustable feetYesLED Interior lightYesLight activationSwitch on exteriorFitted lockYesInsulation thickness (mm)40Insulation materialPentaneVoltage supply (V)220/240UK 3 pin plugYesFitted cable length (m)1.5Refrigerant typeR600aCFC freeYesHFC freeYesHFC freeYesHFC freeYes	Shelf size (mm) (WxD)	385x345
LED Interior lightYesLight activationSwitch on exteriorFitted lockYesInsulation thickness (mm)40Insulation materialPentaneVoltage supply (V)220/240UK 3 pin plugYesFitted cable length (m)1.5Refrigerant typeR600aCFC freeYesHFC freeYesHFC freeYesHCFC freeYes		Chrome finish wire shelves
Light activationSwitch on exteriorFitted lockYesInsulation thickness (mm)40Insulation materialPentaneVoltage supply (V)220/240UK 3 pin plugYesFitted cable length (m)1.5Refrigerant typeR600aCFC freeYesHFC freeYesHFC freeYesHCFC freeYes		Yes
Fitted lockYesInsulation thickness (mm)40Insulation materialPentaneVoltage supply (V)220/240UK 3 pin plugYesFitted cable length (m)1.5Refrigerant typeR600aCFC freeYesHFC freeYesHFC freeYesHCFC freeYes		Yes
Insulation thickness (mm)40Insulation materialPentaneVoltage supply (V)220/240UK 3 pin plugYesFitted cable length (m)1.5Refrigerant typeR600aCFC freeYesHFC freeYesHFC freeYesHFC freeYes	Light activation	Switch on exterior
Insulation materialPentaneVoltage supply (V)220/240UK 3 pin plugYesFitted cable length (m)1.5Refrigerant typeR600aCFC freeYesHFC freeYesHFC freeYesHCFC freeYes		Yes
Voltage supply (V)220/240UK 3 pin plugYesFitted cable length (m)1.5Refrigerant typeR600aCFC freeYesHFC freeYesHFC freeYesHCFC freeYes		40
UK 3 pin plugYesFitted cable length (m)1.5Refrigerant typeR600aCFC freeYesHFC freeYesHFC freeYesHCFC freeYes		
Fitted cable length (m)1.5Refrigerant typeR600aCFC freeYesHFC freeYesHFC freeYesHCFC freeYes	Voltage supply (V)	220/240
Refrigerant typeR600aCFC freeYesHFC freeYesHCFC freeYes		Yes
CFC free Yes HFC free Yes HCFC free Yes		1.5
HFC free Yes HCFC free Yes		R600a
HCFC free Yes	CFC free	Yes
	HFC free	Yes
Ammonia free Yes	HCFC free	Yes
	Ammonia free	Yes