



PLATINUM

UNDER-COUNTER PLATINUM FRIDGE GLASS DOOR 200L STAINLESS STEEL



- ✓ **Large 200L Capacity**
maximises available under-counter storage space
- ✓ **0°C to +10°C Temperature Range**
allows user to select ideal temperature
- ✓ **2 Removable Wire Shelves**
with 7 variable shelf positions
- ✓ **Easy Grab Handle**
- ✓ **Fitted Rollers**
easy to manoeuvre the unit for cleaning
- ✓ **Lockable**
- ✓ **Replaceable Door Seal**
- ✓ **Internal LED Light**
switches on automatically when door opens
- ✓ **Automatic Defrost**
for low on-going maintenance
- ✓ **Stackable**
- ✓ **Warning Alarms**
high/low temperature and door open alarms to alert users to a problem

SKU CODE:	PRODUCT CODE:	DESCRIPTION:
444441137	CRG200ST	Under-counter Platinum Fridge Glass Door 200L Stainless Steel



FULL SPECIFICATION – CRG200ST UNDER-COUNTER PLATINUM FRIDGE GLASS DOOR 200L STAINLESS STEEL

Description	Under-counter
SKU Code	444441137
EAN Code	5052263011373
GDPA Code	CRG200ST
Unit External Width (mm)	595
Unit External Depth (mm)	667 (includes handle depth of 40mm)
Unit External Height (mm)	838
Packed Width (mm)	650
Packed Depth (mm)	690
Packed Height (mm)	870
Product Weight (kg)	40
Packed Weight (kg)	45
Internal Dimensions (mm) (WxDxH)	477x482x652
Gross Capacity (L)	200
Net Capacity (L)	150
Material - Exterior Finish	Stainless Steel
Material - Interior Finish	Plastic (HIPS/ABS Mix)
Stackable	Yes
Gastronorm Compatible	-
Colour	Stainless Steel
Internal Temperature Range	0 to +10°C
Maximum Ambient Operating Temperature	Up to 38°C
Defrost Type	Automatic
Forced Air Cooling (Fan)	Yes
Door Type	Glass
Door Style	Hinged, reversible
Self Closing Door	No
Door Open Depth (mm)	1200
Replacement Door Seal	Yes
Controller type	Electronic
Open Door Sensor/Alarm	Yes
Hi/Low Temperature Alarm	Yes
External Temperature Display	Yes
Rollers/Castors	2 adjustable feet, 2 rear rollers
Number of Shelves	2
Number of Shelf Positions	7
Shelf Size (mm) (WxD)	517x400
Shelf Material	White plastic-coated wire
Internal LED Light	Yes
Light Activation	Automatic - on door open
Fitted Lock	Yes
Insulation Thickness (mm)	45
Insulation Material	Pentane
Voltage Supply	220/240v
Power Rating (kW)	0.19
Supplied with Fitted UK Plug	Yes
Fitted Cable Length (m)	1.8
Refrigerant Type	R600a
CFC Free	Yes
HFC Free	Yes
HCFC Free	Yes
Ammonia Free	Yes
Heat Rejection (Watts)	160
Energy Consumption (Kw/h) (24hrs)	1.6