## lincat





OG8002/N - Lincat Opus 800 Natural Gas Freestanding Oven Range - 6 Burners - W 900 mm -55.0 kW

- Powerful 7.5kW dual concentric burners for focused heat distribution from a fast boil to a low simmer
- Individual heavy-duty single cast iron supports, built to withstand the rigours of the busiest kitchen

**Power and Performance** 

O Low flue to allow use of the complete hob top

This powerful Opus 800 gas oven range is built to deliver high volumes of top quality food and will withstand the rigours of even the busiest kitchen.

Powerful 9.5kW oven

- Large 4 x GN1/1 capacity oven enabling four different foods to be cooked simultaneously
- 👩 Gas Oven Ranges

## **Specifications**

#### Summary

Brand	Lincat	BTU per Hour	187,660
Range	Opus 800	Total Power kW	55.0
Power Type		Temperature Range °C	120-260
Gas Type	Gas	Cooking Area (Width x Depth) mm	
••	Natural Gas	• • • • •	900×600
Unit Type	Free-standing	Temperature Control	Mechanical
Available in UK Only	No	Rating per Hob kW	7.5
UK Warranty	2 Years Parts and Labour Warranty	Oven Rating kW	10.0
Export Warranty	Contact your local dealer		
GTIN	5056105102205		
Key Specifications		Capacity	
		eapacity	
Number of Shelves included	2	Gastronorm Capacity	4 x GN1/1
Number of Shelf Positions	5		
Number of Hobs	6		
Shape of Hob	Square		
Weights and Dimensions		Supply Connections	
Weights and Dimensions Unit Height (External) mm	920	Requires Installation	Yes
<u> </u>	920 900		Yes No
Unit Height (External) mm		Requires Installation	
Unit Height (External) mm Unit Width (External) mm	900	Requires Installation Requires Electrical Supply Gas Connection BSP Gas Consumption at full rate Natural	No
Unit Height (External) mm Unit Width (External) mm Unit Depth (External) mm	900 800	Requires Installation Requires Electrical Supply Gas Connection BSP Gas Consumption at full rate Natural m <sup>3</sup> per Hour	No 3/4* 5.19
Unit Height (External) mm Unit Width (External) mm Unit Depth (External) mm Height (Internal) mm	900 800 405	Requires Installation Requires Electrical Supply Gas Connection BSP Gas Consumption at full rate Natural m <sup>3</sup> per Hour Gas Pressure Natural mbar	No 3/4* 5.19 20
Unit Height (External) mm Unit Width (External) mm Unit Depth (External) mm Height (Internal) mm Width (Internal) mm	900 800 405 715	Requires Installation Requires Electrical Supply Gas Connection BSP Gas Consumption at full rate Natural m <sup>a</sup> per Hour Gas Pressure Natural mbar Total heat input at full rate Natural kW	No 3/4* 5.19
Unit Height (External) mm Unit Width (External) mm Unit Depth (External) mm Height (Internal) mm Width (Internal) mm Depth (Internal) mm	900 800 405 715 530	Requires Installation Requires Electrical Supply Gas Connection BSP Gas Consumption at full rate Natural m <sup>3</sup> per Hour Gas Pressure Natural mbar Total heat input at full rate Natural kW Total heat input at full rate Natural	No 3/4* 5.19 20
Unit Height (External) mm Unit Width (External) mm Unit Depth (External) mm Height (Internal) mm Width (Internal) mm Depth (Internal) mm Shelf Dimensions Width mm	900 800 405 715 530 710	Requires Installation Requires Electrical Supply Gas Connection BSP Gas Consumption at full rate Natural m <sup>a</sup> per Hour Gas Pressure Natural mbar Total heat input at full rate Natural kW	No 3/4* 5.19 20 54.5
Unit Height (External) mm Unit Width (External) mm Unit Depth (External) mm Height (Internal) mm Width (Internal) mm Depth (Internal) mm Shelf Dimensions Width mm Shelf Dimensions Depth mm	900 800 405 715 530 710 512	Requires Installation Requires Electrical Supply Gas Connection BSP Gas Consumption at full rate Natural m <sup>3</sup> per Hour Gas Pressure Natural mbar Total heat input at full rate Natural kW Total heat input at full rate Natural	No 3/4* 5.19 20 54.5
Unit Height (External) mm Unit Width (External) mm Unit Depth (External) mm Height (Internal) mm Width (Internal) mm Depth (Internal) mm Shelf Dimensions Width mm Shelf Dimensions Depth mm Hob Dimensions mm Net Weight Kg	900 800 405 715 530 710 512 300 × 300	Requires Installation Requires Electrical Supply Gas Connection BSP Gas Consumption at full rate Natural m <sup>3</sup> per Hour Gas Pressure Natural mbar Total heat input at full rate Natural kW Total heat input at full rate Natural	No 3/4* 5.19 20 54.5
Unit Height (External) mm Unit Width (External) mm Unit Depth (External) mm Height (Internal) mm Width (Internal) mm Depth (Internal) mm Shelf Dimensions Width mm Shelf Dimensions Depth mm Hob Dimensions mm	900 800 405 715 530 710 512 300 × 300	Requires Installation Requires Electrical Supply Gas Connection BSP Gas Consumption at full rate Natural m <sup>3</sup> per Hour Gas Pressure Natural mbar Total heat input at full rate Natural kW Total heat input at full rate Natural	No 3/4* 5.19 20 54.5

Packed Weight Kg	149
Packed Height cm	107
Packed Width cm	100
Packed Depth cm	85

## **Available Accessories**





## Available Accessories


OA8902

SPLASHBACK/SHELF - 0G8002

## **Technical Picture**







lincat



# Lincat fift

### Lincat Limited

Whisby Road, Lincoln, LN6 3QZ,

United Kingdom

Company No: 2175448

A member company of



Customer Care

Tel: +44 1522 875500 Email: care@lincat.co.uk

#### **Export Customers**

Tel: +44 1522 875536

Email: export@lincat.co.uk

#### **Opening Hours**

Monday – Friday: 8.30am – 5pm