

RACK CONVEYOR DISHWASHERS

The Ecomax Plus rack conveyors are truly outstanding in their field, delivering ease of use and low running costs. Designed for higher volume operations, the machines ensure a gleaming finish without fail.



• Ecotronic control offering a choice of 2 rack speeds

· Push button machine draining

Stainless steel wash arms with anti-block jets and slider mechanism to open all wash pipes for easy cleaning

· Dryer section and heat recovery options available

· Blue markers for easy identification of removable parts for cleaning

· Stainless steel wash pump housing and impellor for maximum robustness and reliability

ECOMAX PLUS C815A

- Wash up to 120 racks per hour (2,160 plates)
- Compact design just 1350mm in length
- Comprises main wash and compact dual rinse sections

ECOMAX PLUS C815EA

- Wash up to 150 racks per hour (2,700 plates)
- Compact design just 1850mm in length
- Comprises prewash, main wash and compact dual rinse sections

Turn over for full machine specs

0870 168 8881

www.hobartindependent.co.uk



SPECIFICATIONS	ECOMAX PLUS	ECOMAX PLUS	
GENERAL	C815A	C815EA (PRE-WASH)	
DIMENSIONS	1350mm(w)	1850mm(w)	
	775mm(d) 2150mm(h)	775mm(d) 2150mm(h)	
Number of racks/hr Rack size	120 500 x 500mm	150 500 x 500mm	
			r
Racks supplied	1 x plate rack	1 x plate rack	
	1 x cup rack 1 x cutlery basket	1 x cup rack 1 x cutlery basket	
Max plates per rack	18	18	
Rinse booster pump	YES	YES	1
CONTROLS	ELECTRONIC	ELECTRONIC	
Class A air gap	YES	YES	1
Rinse water consumption	160ltrs/hr	180ltrs/hr	
Wash tank capacity	105ltrs	105ltrs	
Wash tank heating	12kW	12kW	
Wash pump rating	1.34kW	1.34kW ECOMAX PLUS C815A	
Wash pump flow rate	320 ltrs/min	320 ltrs/min	
Noise level	64dB	64dB	
Dryer	Optional	Optional	\cap
Drying tunnel length	650mm	650mm	
Drying tunnel loading	3.5kW	3.5kW	
Heat recovery	Optional	Optional	
Circulation	280m3/hr	280m3/hr	and sound
WATER		The second se	
Water flow pressure	1.5 – 6 BAR	1.5 – 6 BAR	
ELECTRIC			
Total connected load			
(water fed @ 40°C)	22.3kW	22.3kW	
Total connected load			
(water fed @ 10°C) DRAIN	29.8kW	29.8kW	
Drain size(diameter)	50mm	50mm ECOMAX PLUS C815EA	
Max height above floor level	180mm	180mm	

Tabling not included.

Technical details may be subject to change without prior notice

HOBART INDEPENDENT SouthgateWay,OrtonSouthgate, Peterborough, PE2 6GN

0870 168 8881 www.hobartindependent.co.uk