

# Utensil Washers

Designed to wash all manner and sizes of pots and kitchen utensils.

The five models in the Viso range are designed to wash all manner and sizes of pots and kitchen utensils as well as bakery trays and tote boxes. With rack sizes from a standard 500mm width to 1320mm wide and extra powerful self draining wash pumps, these machines can remove the most stubborn of soiling.

Double skin insulation, cantilevered opening doors and a choice of wash cycles make the entire range safe, simple and easy to use.



# Viso Utensil Washers

Pots, pans, plates & trays; our utensil washers clean up!

## Viso 50

Compact free standing, front-loading utensil washer capable of washing 600 x 400mm baking pans. Intensive 2, 4 and 6 minute wash cycles complete with high performance wash pump, type A air gap, double skinned insulation and gravity drain as standard.



Model	Code	Dimensions (mm):
VISO 50	VISO50	W - 667
With an integral detergent & rinse aid dispenser	VISO50DET	H - 1473
		D - 716 closed, 1191 open (+/-30)

## Viso 70

Free-standing front-loading utensil washer with 650mm wash chamber. Able to accept large pots and pans. Intensive 2, 4 and 6 minute wash cycles complete with high performance wash pump, type A air gap, double skinned insulation and gravity drain as standard.



Model	Code	Dimensions (mm):
VISO 70	VISO70	W - 850
With an integral detergent & rinse aid dispenser	VISO70DET	H - 2000
		D - 850 closed, 1250 open (+/-30)

## Viso 55/55H

Free standing, front-loading utensil washer with extra high 850mm wash chamber. Able to accept large pots, pans and, in particular, baking trays. Intensive 2, 4 and 6 minute wash cycles complete with high powered wash pump, type A air gap, double skinned insulation and gravity drain as standard.



Model	Code
VISO 55	VISO55
With an integral detergent & rinse aid dispenser	VISO55DET
VISO 55H	VISO55H
With an integral detergent & rinse aid dispenser	

### Dimensions (mm): Viso 55

W - 720  
H - 2000  
D - 780 closed, 1180 open (+/-30)

### Viso 55H

W - 720  
H - 2200  
D - 780 closed, 1180 open (+/-30)

## Viso 132

Extra large free standing, front-loading utensil washer with 1320 x 700mm rack size. Able to accept the largest of items. Intensive 2, 4 and 6 minute wash cycles, complete with two high powered wash pumps, type A air gap, double skinned insulation and gravity drain as standard.



Model	Code
VISO 132	VISO132
With an integral detergent & rinse aid dispenser	VISO132DET

### Dimensions (mm):

W - 1465  
H - 2000  
D - 850 closed, 1250 open (+/-30)

# Viso Utensil Washers



## Type A Air Gap

Fully compliant essential Water Board regulations.



## Double skinned sides and door

Allows for quieter operation and reduced heat loss.



## Rinse economiser

Reduces the rinse temperature when in standby mode.



## 3 Wash Programs

Intensive 2,4 and 6 minute wash cycles

## Machine Features:

1 Able to accept large pots and pans	2 High performance wash pump	3 Gravity Drain as standard	4 Free standing
---	---------------------------------	--------------------------------	--------------------

Classeq Ltd,

Classeq House, Roebuck Way, Knowlhill, Milton Keynes

Buckinghamshire MK5 8WH United Kingdom

Tel: +44 (0)844 225 9250 Email: [sales@classeq.co.uk](mailto:sales@classeq.co.uk)

[www.classeq.co.uk](http://www.classeq.co.uk)

Dimensions	Viso 50	Viso 55/55H	Viso 70	Viso 132
Width	667mm	720mm	850mm	1465mm
Depth	716mm	780mm	850mm	850mm
Depth - Door Open	1191mm	1180mm	1250mm	1250mm
Height	1473mm (+/-30mm)	1730mm (+/-30mm)	1730mm (+/-30mm)	1730mm (+/-30mm)
Height - Door Open	-	2000/2200mm† (+/-30mm)	2000mm (+/-30mm)	2000mm (+/-30mm)
Usable wash chamber height	400mm	650mm/850mm*	650mm	650mm
Water inlet height floor level	198mm (+/-30mm)*	165-225mm*	165-225mm*	165-225mm*
Drain height floor level	390mm (+/-30mm)	300mm (+/-30mm)	235mm (+/-30mm)	235mm (+/-30mm)
Drain size	50mm	50mm	50mm	50mm
Rack size	500mm x 600mm	550mm x 610mm	700mm x 700mm	1320mm x 700mm
Extraction spigot diameter	-	-	120mm	180mm
<b>Hydraulic specifications</b>				
Water supply connection	3/4"	3/4"	3/4"	3/4"
Required water pressure	1.0 to 4.0 bar	1.0 to 4.0 bar	1.0 to 4.0 bar	1.0 to 4.0 bar
Required water flow**	-	-	-	-
<b>Electrical specifications</b>				
Amps required - 3 Phase Water fed @	40° C - 16A	40° C - 16A 10° C - 16A	40° C - 20A 10° C - 20A	40° C - 25A 10° C - 25A
Rinse boiler heating Water fed @	40° C - 6.0 kW	40° C - 6.0 kW 10° C - 6.0 kW	40° C - 8.0kW 10° C - 8.0kW	40° C - 9.5kW 10° C - 9.5kW
Total Connected Load Water fed @	40° C - 7.1kW	40° C - 7.4/8.0kW† 40° C - 7.4/8.0kW†	40° C - 11kW 10° C - 11kW	40° C - 15.5kW 10° C - 15.5kW
<b>Performance</b>				
Maximum racks/hour	30	30	30	30
Operating noise level	68dB	68dB	68dB	69dB
Net weight	120kg	155kg	190kg	295kg
Wash pump size	1.1kW	1.4kW	3kW	2x3kW
Wash pump capacity	485Ltrs/min	650Ltrs/min	1200Ltrs/min	2x1200Ltrs/min
Wash tank capacity	20Ltrs	37Ltrs	68Ltrs	131Ltrs
Wash tank heating	3.0kW	3.0kW	6.0kW	8.0kW
Wash tank temperature	55°C	55°C	55°C	55°C
Rinse boiler capacity	12Ltrs	14Ltrs	14Ltrs	14Ltrs
Rinse boiler temperature	85°C	85°C	85°C	85°C
Rinse water consumption	2.5Ltrs	4Ltrs	5Ltrs	8Ltrs
<b>Components</b>				
Built in air gap	•	•	•	•
Rinse booster pump	•	•	•	•
Built in detergent dispenser	Optional	Optional	Optional	Optional
Built in rinse aid dispenser	Optional	Optional	Optional	Optional
Double skinned cabinet	•	•	•	•
Extraction Spigot	-	-	•	•