

British Manufacturing since 1957



## The Professionals Choice

# UCC20

### InstaTap Chilled Under Counter Water Dispenser



#### **FULL SPECIFICATION**



#### **UCC20 InstaTap Chilled Under Counter Water Dispenser**

Type	Under-counter chiller – Push-button Dispenser
•	UK
, , ,	
UNDER COUNTER UNIT:	
Electrical & Water Connections:	
Food Quality, flexible mains water hose	1.6 metres long (3/4"BSP)
Mains water pressure range	1 – 4 bar (15psi – 58psi)
Electrical Installation	UK standard 3-pin plug (5 amp)
Operating Parameters:	
Rated Voltage:	230V AC
	1.2A
	5°C
	30°C
Dimensions & Weights:	
	390mm
	180mm
	340mm
Weight (UC unit only) empty:	17.0kg
<b>DISPENSE FONT:</b>	
Dispense Font dimensions (W x D x H) mm	185 x 185 x 225
	150
	304 grade Stainless Steel & chrome-plated Aluminium
Font interface with UC unit (electrical & water)	1.2 metre, plug-in XLR lead (electrical) and silicone rubber
	water transfer tube (water)
Performance (Chilled):	
	1 at 5°C
	2 at 7°C
	6°C
= =: : : : : : : : : : : : : : : : : :	9°C
Litres/hour:	20 litres below 10°C
Filtration:	
In-line Filter (supplied)	Yes (not integral)
	Removes sediment & chlorine for fresh, clean tasting water
	5000 Litres
	5 micron
Standards & Approvals:	
	No (built to WRAS specification but not submitted)
Warranty & After-Sales:	
	2 Year parts & labour
Spare parts, filters & accessories	Same day despatch (if ordered before 3pm)

#### **VENTILATION & AIRFLOW:**

**IMPORTANT**: The UCCH1000 Chilled Water Dispenser must be installed correctly and provide sufficient air-flow, ventilation and adequate expulsion of warm exhaust air. Ask for our installation information and recommendations and details of our ventilation kits.

Instanta Limited
T: 01704 501114
F: 01704 501115
E: sales@instanta.com





Certificate Numbers: FM01234 & EM01234