

British Manufacturing since 1957



The Professionals Choice

WMSP15

SureFlow Plus Wall Mount Water Boiler - Stainless



FULL SPECIFICATION



WMSP15 Wall Mounted SureFlow Premium Auto Fill Water Boiler

– Stainless

Туре	Premium Wall Mount – Wall mount Water Boiler
Country of Design & Manufacture	UK
CAPACITY, WEIGHTS & DIMENSIONS:	
Capacity (Litres)	15
Unit dimensions (W x D x H) mm	370 x 250 x 530
Packed dimensions (W x D x H) mm	610 x 440 x 720
Tap protrusion mm	90mm
Product weight - empty (kg)	12.1
Product weight – full (kg)	27.2
Packed weight (kg)	TBA
CONSTRUCTION:	
Outer fabrication (body) construction	304 grade stainless steel
Tank construction	304 & 316 grade Stainless Steel
Tank wall thickness	0.9mm
ELECTRICAL:	0.01111
Power rating (kW)	3
Voltage supply	220-230 V (50-60Hz)
Electrical supply	Single-phase, N & E (min break rating of 13amp required)
Electrical Supply	Wire into double-pole fused spare (minimum cable size:
	1.5mm ²). Use of an ELCB is recommended
DUUMPING	1.5mm²). Use of all ELCD is recommended
PLUMBING:	2/4" DCD or 15mm nuch fit
Water inlet connection:	3/4" BSP or 15mm push-fit
Mains water pressure range Overflow/waste connection:	2 – 7 bar (28psi – 100psi)
Overnow/waste connection:	15mm push-fit (extend if required: pipework to have a
	continuous fall (no longer than 500mm), no more than 3
DEDEODMANICE	right-angle bends.
PERFORMANCE:	
Water temperature delivered	96°C (default) – can be adjusted if required
Heat up time to working temperature	31 mins (full tank capacity)
Output per hour (@ default temperature setting)	28 Litres (higher output/hour if set @ lower temperature)
Rapid draw-off	15 Litres
Recovery per minute	0.5 Litres
Stand-by power loss (idle mode)	0.12 kW/h
FILTRATION:	
Multi-Filter (taste & odour, sediment & reduces lime-scale)	No (available as an optional extra if required)
OTHER FEATURES:	
7 day programmable timer	Yes
Energy-saving ECO mode	Yes
Tank-baffle plates – unique design aids heat recovery &	Yes
reduces steam emissions to atmosphere	
Early warning lime-scale diagnostics (via LCD display)	Yes – Advanced
Dual safety protection	Yes - Over-boil & boil-dry protection
STANDARDS & APPROVALS:	
WRAS approved	Yes
EMC Tested and Certified (EN 55014 & EN 61000)	Yes
Electrical Safety Tested and Certified to BS standard	Yes
EN 60335-1 & 2	
WARRANTY & AFTER-SALES:	
Guarantee	2 Year parts & labour
Spare parts, filters & accessories	Same day despatch (if ordered before 3pm)
oparo parto, intero a accoccion	

Instanta Limited T: 01704 501114 F: 01704 501115 E: <u>sales@instanta.com</u>



Certificate Numbers: FM36413 & EMS75807