

CO343T - Lincat Convector Touch Electric Counter-top Convection Oven - W 660 mm - D 740 mm - 3.0 kW

Able to roast, braise, bake and reheat, a CO343T Convector convection oven is a powerful addition to any commercial kitchen.

- 4 x GN1/1 capacity
- Touchscreen control with easy-to-use icon-driven menu selections
- Easy-view traffic light status see the status of the oven at a glance, even in the noisiest kitchens
- Space for 24 programs with up to four stages, which can be adjusted individually
- Up to four-stage phased cooking for perfect results - set temperature, time and fan speed  $\,$ for each stage
- Even heat distribution thanks to electronically controlled two-speed, bi-directional fan
- Nine-hour on-screen timer, with electronic buzzer, and flashing oven lamps to indicate that cycle has finished
- Side opening door

Specifications						
Summary		Power and Performance				
Brand	Lincat	Total Power kW	3.0			
Range	Convector	Temperature Range °C	60 - 260			
Power Type	Electric	IP Rating	IP23			
Unit Type	Counter-top	Controls Position	Right hand side			
Available in UK Only	No	Temperature Control	Electronic			
UK Warranty	2 Years Parts and Labour Warranty	Timer Range mins	1 - 540			
Export Warranty	Contact your local dealer	Oven Rating kW	2.8			
GTIN	5056105121411					

Key Specifications		Capacity	
eet Height/Type	55mm/adjustable	Gastronorm Capacity	4 x GN1/1
ontinuous Plug-In Door Seal	Yes	Shelf Spacing mm	85
emovable Inner Door Glass	No	Sheet Pan Capacity	4 × 460 × 330
landle Type	Grab	Capacity Litres	72
ented Door	Yes		
Reversible Door	No		
Door Type	Left Hinged		
lumber of Cooking Phases	4		
Phased Cooking	Yes		
Shelf Timer(s) (Number)	Yes		
Grill Element/Mode	No		
Core Temp Probe	No		
Steam Injection	No		
an(s) Speed	2		
an(s) Type	Bi-Directional		
lumber of Fan(s)	1		
Euronorm Compatible	No		
Sheet Pan Compatible	Yes		
Removeable Shelf Guides	Yes		
/lanual Mode	Yes		
Programmable	Yes		
lumber of Programs	24		
Timer Type	Touchscreen		
Display Type	Touchscreen		
lumber of Shelves included	4		
lumber of Shelf Positions	4		
Type of Lighting	Halogen		
Construction/Finish	430 S/S cavity		
SN Compatible	Yes		
Weights and Dimensions		Supply Connections	
Jnit Height (External) mm	600	Requires Installation	No
Unit Width (External) mm	660	Requires Electrical Supply	Yes
Jnit Depth (External) mm	740	UK 3 Pin Plug	Yes

Weights and Dimensions		Supply Connections		
Unit Height (External) mm	600	Requires Installation	No	
Unit Width (External) mm	660	Requires Electrical Supply	Yes	
Unit Depth (External) mm	740	UK 3 Pin Plug	Yes	
Height (Internal) mm	398	Requires Hardwiring	No	
Width (Internal) mm	330	<b>Electrical Supply Rating Watts</b>	3000	
Depth (Internal) mm	550	Single Phase Amps	13	
Shelf Dimensions Width mm	530	Single Phase Voltage	230	
Shelf Dimensions Depth mm	325	USB Port	Yes	
Net Weight Kg	68.7			
Shipping				
Packed Weight Kg	83.7			
Packed Height cm	81.5			

## Available Accessories


Packed Width cm Packed Depth cm


**CO300/FS** Lincat Convector Floor Stand for CO343M/CO343T Convection Ovens - with 4 Runners - W 660 mm


100

CO300/LFSK Lincat Convector Low Floor Stand and Stacking Kit for CO343M/CO343T Convection Ovens - with 1 Shelf - W 660 mm

## **Technical Picture**









**Lincat Limited** 

Whisby Road,

Lincoln, LN6 3QZ,

United Kingdom

**Company No:** 2175448

A member company of

**Customer Care** 

**Tel:** +44 1522 875500

Email: care@lincat.co.uk

**Export Customers** 

**Tel:** +44 1522 875536

Email: export@lincat.co.uk

**Opening Hours** 

Monday - Friday:

8.30am - 5pm