



## DOMINATOR PLUS

# E3914i Induction Range

### Key features

- 4 x 5kW energy efficient heat zones
  - Instant heat and incredibly fast heat up times
- In-built pan detection
  - No heat generated until a pan is placed on the hob, meaning no wasted energy
- Heavy duty ceramic glass hob
  - Robust and spillages simply wipe clean, no scrubbing required
- Temperature is precisely controllable
  - Change from gentle simmer to rolling boil almost instantly
- Low cooking surface temperature and no naked flames
  - Safer for kitchen staff as reduced risk of burns
- Very little heat emitted into kitchen
  - Contributes to a more pleasant working environment and existing ventilation doesn't have to work as hard
- 1/1 GN fan-assisted oven
  - 5 shelf positions with 2 shelves supplied
- Wide oven temperature range of 100 - 250°C
  - Ideal to prepare a wide variety of food
- Twin oven doors with glass panels
  - Monitor cooking progress without losing heat


### Accessories

- Oven shelf
- Factory fitted, adjustable castors
- Fixed installation kit



### Similar Models

- E3913i 4 x 3.5kW induction range
- E3904i 4 x 5kW induction boiling top
- i91105 4 x 5kW induction range (GP oven)
- i91105C 4 x 5kW induction range (fan-assisted oven)



Unit on castors is the same hob height

Measurements *in mm*

## Specification details

Electrical rating (kW)	26	
Electrical supply voltage	400V 3N~	
Required electrical supply (A)	63	
Electrical current split (A)	L1: 38 L2: 38 L3: 38	
Element rating - hob (kW)	5 x 4	
Element rating - oven (kW)	6	
Heat zone diameter (mm)	270	
Minimum pan size (mm)	120	
Oven dimensions (w x d x h - mm)	530 x 535 x 380	
Oven shelf (w x d - mm)	530 x 535	
Gastronorm compatibility	1/1	
Weight (kg)	140	
Packed weight (kg)	155	
Packed dimensions (w x d x h - mm)	1000 x 1000 x 1100	
GTIN numbers	On feet	On castors

## Installation notes

Adequate ventilation must be provided to supply sufficient fresh air for combustion and to allow easy removal of any such products that may present a risk to health. Please consult current legislation for details that relate to specific locations.

Install unit on a level, fireproof surface in a well-lit, draught free position. If floor is made of a combustible material, local fire requirements must be checked to ensure compliance.

A clearance of 150mm should be observed between appliance and any combustible wall.

