Lincat Combi Ovens



LC120B/P - Lincat Visual Cooking 1.20 Propane Gas Free-standing Combi Oven - Boiler - W 899 mm - 42.0 kW [Gas] + 2.0 kW [Electric] Choose Visual Cooking where high output and precise control are required.

- Intuitive touch display SmartTouch® for programming
- Immediate production of steam with injection steam production
- CombiSmart® 10-step humidity control, and ClimaOptima® automatic humidity control functions
- Ability to create cooking programmes with up 15 steps
- Rack timer allowing accurate cooking times for different items on different shelves
- 20 x GN1/1 capacity
- Ideal for menus which require a high volume of steaming
- Two-step safety handle

Specifications

Summary		Power and Performance	
rand	Lincat	Total Power kW	2
ange	Lincat Combi Ovens	Temperature Range °C	30-300
eries	Visual Cooking	IP Rating	IPX5
ower Type	Gas	Temperature Control	Electronic
as Type	Propane Gas	Oven Rating kW	Steam connection = 42.0; Hot air
nit Type	Free-standing	Oven Rating KW	connection = 42.0
vailable in UK Only	Yes		
K Warranty	2 Years Parts and Labour Warranty		
TIN	5056105120360		
Key Specifications		Capacity	
VRAS Approved	Yes	Gastronorm Capacity	20 x GN1/1
ype of Lighting	Halogen	Portions per Day	300
lumber of Grids included	0		
Veights and Dimensions		Supply Connections	
Init Height (External) mm	1877	Requires Installation	Yes
nit Width (External) mm	899	Requires Electrical Supply	Yes
Init Depth (External) mm	831	UK 3 Pin Plug	Yes
eight (Internal) mm	1,435	Requires Hardwiring	No
Vidth (Internal) mm	460	Electrical Supply Rating Watts	2,000
epth (Internal) mm	690	Single Phase Amps	17
et Weight Kg	305	Single Phase Voltage	230
		Gas Connection BSP	3/4"
		Gas Pressure Propane mbar	30-50
		Total heat input at full rate Propane kW	42
		Total heat input at full rate Propane BTU per hour	160,000
		Water Connection Pressure Bar	2.5-6
		Drain Connection	DN 50 mm



Lincat Combi Ovens

Shipping

Packed Weight Kg325Packed Height cm205Packed Width cm100Packed Depth cm120

Available Options

INSTALLATION

LCO2001 Site Survey & Installation

COMMISSIONING

LCO3001 Commissioning

R/H DOOR INSTALL


LCO2002 Right Hinged Door Installation


Available Accessories


LCA2003	Lincat Combi Oven Roll-in Trolley - for Visual Cooking 1.20 - Including 65 mm Rack
LCA3003	Lincat Combi Oven Imperial Non-stick Container - GN1/1(325 x 530 mm) - 20 mm deep
LCA3005	Lincat Combi Oven Imperial Non-stick Container - GN1/1 (325 x 530 mm) - 40 mm deep
LCA3007	Lincat Combi Oven Imperial Non-stick Container - GN1/1 (325 x 530 mm) - 60 mm deep
LCA3009	Lincat Combi Oven Imperial Pizza and Grilling Sheet - GN1/1(325 x 530 mm)
LCA3011	Lincat Combi Oven Imperial Grilling Grid - GN1/1 (325 x 530 mm)
LCA3012	Lincat Combi Oven Imperial Potato Grid - GN1/1 (325 x 530 mm) - 28 Potato Capacity
LCA3013	Lincat Combi Oven Imperial Multi-tray - 8 Moulds - GN1/1(325 x 530 mm)
LCA3015	Lincat Combi Oven Non-stick Aluminium Baking Sheet - GN1/1(325 x 530 mm)
LCA3017	Lincat Combi Oven Non-stick Perforated Aluminium Baking Sheet - GN1/1(325 x 530 mm)
LCA3019	Lincat Combi Oven Silicone Baking Mat - GN1/1 (325 x 530 mm)
LCA3021	Lincat Combi Oven Steamfry Basket - GN1/1 (325 x 530 mm)
LCA3023	Lincat Combi Oven Rack for Spare Ribs - GN1/1 (325 x 530 mm)
LCA3024	Lincat Combi Oven Chicken Grid - GN1/2 (325 x 265 mm) - 4 Chicken Capacity
LCA3025	Lincat Combi Oven Chicken Grid - GN1/1(325 x 530 mm) - 8 Chicken Capacity
LCA4001	Lincat Combi Oven Software Key - Quick Select Recipes (QSR)
LCA4002	Lincat Combi Oven Software Key - Advanced Rack Timer - Tailored Menu Handling
LCA5001	Lincat Combi Oven Condenser Hood - for Visual Cooking 1.06/1.10/1.20 not Stacked Units
LCA7001	Lincat Combi Oven Roll-in Plate Rack - for Visual Cooking 1.20 - 48 Plate Capacity
LCA7002	Lincat Combi Oven Roll-in Plate Rack - for Visual Cooking 1.20 - 57 Plate Capacity
LCA7005	Thermal Blanket for Roll-in Trolley for Visual Cooking 1.20
LCC1002	Hydro Shield 6000 (XL) Water Filter Cartridge - Recommended for Visual Cooking 1.20/2.06/2.10/2.20 and all Combi Ovens in hard water areas
LCC1004	Hydro Shield 6000 (XL) Water Filter Kit - Including Filter, Filter Head and Hose - Recommended for 1.20/2.06/2.10/2.20 + all Ovens in hard water areas
LCC2003	Lincat Protect Intense Detergent - 2 x 5I
LCC2005	Lincat Protect Cleaning Package - 6 x 5I Intense Detergent and 2 x 5I Rinse Aid
LCC2006	Lincat Protect Rinse Aid - 2 x 5l


Product Code: LC120B/P Page Number: 2 Print Date: 20/01/2021


Technical Picture















Lincat Limited

Whisby Road,

Lincoln, LN6 3QZ,

United Kingdom

Company No: 2175448

A member company of

Customer Care

Tel: +44 1522 875500

Email: care@lincat.co.uk

Export Customers

Tel: +44 1522 875536

Email: export@lincat.co.uk

Opening Hours

Monday - Friday:

8.30am - 5pm