

E3800DXBrattPan

Key features

- Stainless steel pan with duplex steel base
 - Delivers even heating across the base of the pan
- Versatile cooking performance
 - Able to carry out six different cooking methods
- · Manual tilt via front located handle
 - Safe, smooth pan tilting
- Incremental opening lid
 - See what's cooking without unnecessary heat loss
- Precise temperature control from 100 300°C
 - Responsive and accurate controls
- Automatic power cut-off when pan is tilted
 - Additional safety feature for added peace of mind
- Integrated water faucet
 - Easy to add water to pan as and when required
- · Laser-etched control icons
 - Permanent, indelible markings

Accessories

- Steaming tray
- 1/1 GN compatible cradle
- Factory fitted, adjustable castors
- Fixed installation kit

Similar Models


- E9781 100 litre bratt pan
- G3800DX Gas bratt pan
- G9781 100 litre electric bratt pan








Measurements in mm







Unit is the same non neight or reet and castors

Specification details

Electrical rating (kW)	7.6	
Electrical supply voltage	400V 3N~	
Electrical current split (A)	L1: 11.2 L2: 11.2 L3: 11.2	
Pan dimensions (w x d x h - mm)	720 x 430 x 200	
Water capacity (litres)	60	
Water connection (BSP)	1/2"	
Weight (kg)	118	
Packed weight (kg)	131	
Packed dimensions (w x d x h - mm)	1000 x 1000 x 1100	
GTIN numbers	On feet	On castors

Installation notes

Adequate ventilation must be provided to supply sufficient fresh air for combustion and to allow easy removal of any such products that may present a risk to health. Please consult current legislation for details that relate to specific locations.

Install unit on a level, fireproof surface in a well-lit, draught free position. If floor is made of a combustible material, local fire requirements must be checked to ensure compliance.

A clearance of 150mm should be observed between appliance and any combustible wall.

