

DOMINATORPLUS

G3121 Six Burner Boiling Top

Key features

- Energy efficient, high performance 5.3kW burners - Quick heat up, reduced waiting time
- Semi-sealed, pressed stainless steel hob - Easy to remove and keep clean
- Three twin cast iron pan supports - Long-lasting and robust
- Mounted upon open stand
- Under shelf provides useful storage space
- Laser-etched control icons
 - Permanent, indelible markings

Accessories


- Fully integrated extended flue
- Fixed stand
- Factory fitted, adjustable castors
- Fixed installation kit

Similar Models


- G9084 Four burner boiling top
- G3124 Six burner boiling top
- G3101 Six burner oven range




G3121 Sik Burner Gas Boiling Top









Measurements in mm unit on castors is the same nob height

Installation notes

Adequate ventilation must be provided to supply sufficient fresh air for combustion and to allow easy removal of any such products that may present a risk to health. Please consult current legislation for details that relate to specific locations.

Install unit on a level, fireproof surface in a well-lit, draught free position. If floor is made of a combustible material, local fire requirements must be checked to ensure compliance.

A clearance of 150mm should be observed between appliance and any combustible wall.

Specification details

Total rating (natural and propane - kW - Nett)	31.8	
Total rating (natural and propane - btu/hr - gross)	119,400	
Inlet size (natural and propane)	3/4" BSP	
Flow rate - natural (m³/hr)	3.30	
Flow rate - propane (kg/hr)	2.30	
Inlet pressure (natural and propane - mbar)	20 / 37	
Operating pressure (natural and propane - mbar)	15 / 37	
Hob burner rating * (natural and propane - kW)	5.3 x 6	
Hob burner rating * (natural and propane - btu/hr)	19,900 x 6	
Weight (kg)	75	
Packed weight (kg)	83	
Packed dimensions (w x d x h - mm)	950 x 1000 x 500	
GTIN numbers	Nat Gas	LPG

