





F79/010 - IMC WasteStation Macerator and Dewaterer - with Airbreak

Reliable, efficient, safe and easy to operate, the WasteStation allows operators to quickly and effectively remove waste, creating a safer and cleaner kitchen.

- A solution for your business process up to 700 kg waste per hour, the equivalent of 1450 covers
- Transport savings reduce waste collection costs by up to 80% by reducing the food waste volume and weight requiring collection
- Storage savings by reducing the waste volume, on site waste storage facility requirements are also reduced
- Labour savings reduce staff time processing and managing waste, fast efficient disposal of food waste as and when you need to, with no schedule
- Self-cleaning operation WasteStation can undertake a thorough clean, ensuring the whole system is free of food and grease

- Self-emptying eliminates the need for staff to empty the auger assembly, reducing labour times required to operate the machine. Intelligent electronic sensor detects when the bin is full
- Visual control panel kitchens are a noisy environment, so WasteStation incorporates a simple LED display to allow monitoring of the state of the equipment during operation
- Energy savings compact design and short processing times ensure low operating costs and minimal use of kitchen floor space
- Maximise kitchen hygiene fully enclosed system prevents food entering the unit, keeping the machine clean and free of waste, and reducing operational noise. Following each operation, the machine undertakes a quick selfrinse cycle, preventing any build-up of food
- With airbreak

Summary		Power and Performance	
Brand	IMC	Total Power kW	4.1
Range	WasteStation	НР	1.5
Power Type	Electric	IP Rating	IP55
Unit Type	Free-standing	Operating Decibels	83
Available in UK Only	No		
UK Warranty	2 Years Parts and Labour Warranty		
Export Warranty	Contact your local dealer		
Mounting	Free-standing		
GTIN	5056105197034		
Key Specifications		Capacity	
WRAS Approved	WRAS Compliant	Type of Waste	Tough waste
Airbreak	Yes	Covers Per Sitting	1450
Manual or Auger Feed	Manual	Capacity Kg per Hour	700
Self Cleaning	Yes		





Weights and Dimensions		Supply Connections	
Unit Height (External) mm	1000	Requires Installation	Yes
Unit Width (External) mm	900	Requires Electrical Supply	Yes
Unit Depth (External) mm	700	UK 3 Pin Plug	No
Net Weight Kg	192	16A Commando Plug	No
		Requires Hardwiring	Yes
		Electrical Supply Rating Watts	4,100
		Three Phase Amps	8.62
		Three Phase Voltage	380-415
		Water Supplied From	Mains Fed
		Water Connection Pressure Bar	Head of water not less than 0.18 bar
		Drain Connection	2" waste drain
		Water Connection	3/4" BSP
		Water Consumption Litres/min	12

Shipping

 Packed Weight Kg
 211.2

 Packed Height cm
 152

 Packed Width cm
 90

 Packed Depth cm
 115

Available Accessories

A13/125 Waste Scraper for WasteStation

K12/357 Waste Caddy for WasteStation and WastePro II



Lincat Limited Customer Care

Whisby Road, **Tel:** +44 1522 875500

Lincoln, LN6 3QZ, **Email:** care@lincat.co.uk

United Kingdom

Company No: 2175448

A member company of

Export Customers

Tel: +44 1522 875536

Email: export@lincat.co.uk

Opening Hours

Monday - Friday:

8.30am - 5pm