

Self Cleaning





F79/240 - IMC WasteStation Compact -2.45 kW - Single Phase

Reliable, efficient, safe and easy to operate, the single phase WasteStation Compact allows operators with even the smallest kitchens to quickly and effectively remove waste, creating a safer and cleaner kitchen.

- A solution for your business process up to 200 kg waste per hour, the equivalent of 400 covers per sitting. As fast as you can input the waste, the WasteStation Compact can process it.
- Reduce your carbon footprint reduce the amount of food waste being sent to landfill. By removing water from food waste this reduces the final volume of waste to be disposed of.
- Save on valuable floor space with a unit which is more compact than bulky alternative models, without having to upgrade to a remote dewaterer.
- ▼ Transport savings reduce waste collection costs by up to 80% by reducing the food waste volume and weight requiring collection
- Storage savings by reducing the waste volume, on site waste storage facility requirements are also reduced
- ✔ Labour savings reduce staff time processing and managing waste, fast efficient disposal of food waste as and when you need to, with no schedule

- Self-cleaning operation WasteStation can undertake a thorough clean, ensuring the whole system is free of food and grease
- Self-emptying eliminates the need for staff to empty the auger assembly, reducing labour times required to operate the machine. Intelligent electronic sensor detects when the bin is full
- Visual control panel kitchens are a noisy environment, so WasteStation incorporates a simple LED display to allow monitoring of the state of the equipment during operation
- Energy savings compact design and short processing times ensure low operating costs and minimal use of kitchen floor space
- Maximise kitchen hyglene fully enclosed system prevents food entering the unit, keeping the machine clean and free of waste, and reducing operational noise. Following each operation, the machine undertakes a quick selfrinse cycle, preventing any build-up of food
- Single phase installation

Specifications			
Summary		Power and Performance	
Brand	IMC	Total Power kW	2.45
Range	WasteStation	HP	3.2
Power Type	Electric	IP Rating	IP24
Unit Type	Free-standing	Operating Decibels	83
Available in UK Only	No		
UK Warranty	2 Years Parts and Labour Warranty		
Export Warranty	Contact your local dealer		
Mounting	Free-standing		
GTIN	5056105197942		
Key Specifications		Capacity	
WRAS Approved	WRAS Compliant	Type of Waste	Soft waste
Airbreak	Yes	Covers Per Sitting	400
Manual or Auger Feed	Manual	Capacity Kg per Hour	200





Weights and Dimensions		Supply Connections	
Unit Height (External) mm	1044	Requires Installation	Yes
Unit Width (External) mm	600	Requires Electrical Supply	Yes
Unit Depth (External) mm	700	UK 3 Pin Plug	No
Net Weight Kg	165	16A Commando Plug	Yes
		Requires Hardwiring	No
		Electrical Supply Rating Watts	2,400
		Single Phase Amps	10
		Single Phase Voltage	240
		Water Supplied From	Mains fed
		Water Connection Pressure Bar	Head of water not less than 0.18 Bar
		Drain Connection	2" waste drain
		Water Connection	3/4" BSP
		Water Consumption Litres/min	10

Shipping

 Packed Weight Kg
 181.5

 Packed Height cm
 0

 Packed Width cm
 0

 Packed Depth cm
 0

Available Accessories

A13/159 Waste Scraper for WasteStation Compact
K12/469 Waste Caddy for WasteStation Compact



Lincat Limited Customer Care

Whisby Road, **Tel:** +44 1522 875500

Lincoln, LN6 3QZ, **Email:** care@lincat.co.uk

United Kingdom

Company No: 2175448

A member company of

Export Customers

Tel: +44 1522 875536

Email: export@lincat.co.uk

Opening Hours

Monday - Friday:

8.30am - 5pm