

Self Cleaning





F79/250 - IMC WasteStation Compact -2.45 kW - Three Phase

Reliable, efficient, safe and easy to operate, the three phase WasteStation Compact allows operators with even the smallest kitchens to quickly and effectively remove waste, creating a safer and cleaner kitchen.

- A solution for your business process up to 200 kg waste per hour, the equivalent of 400 covers per sitting. As fast as you can input the waste, the WasteStation Compact can process it.
- Reduce your carbon footprint reduce the amount of food waste being sent to landfill. By removing water from food waste this reduces the final volume of waste to be disposed of.
- Save on valuable floor space with a unit which is more compact than bulky alternative models, without having to upgrade to a remote dewaterer.
- ▼ Transport savings reduce waste collection costs by up to 80% by reducing the food waste volume and weight requiring collection
- Storage savings by reducing the waste volume, on site waste storage facility requirements are also reduced
- ✔ Labour savings reduce staff time processing and managing waste, fast efficient disposal of food waste as and when you need to, with no schedule

- Self-cleaning operation WasteStation can undertake a thorough clean, ensuring the whole system is free of food and grease
- Self-emptying eliminates the need for staff to empty the auger assembly, reducing labour times required to operate the machine. Intelligent electronic sensor detects when the bin is full
- Visual control panel kitchens are a noisy environment, so WasteStation incorporates a simple LED display to allow monitoring of the state of the equipment during operation
- Energy savings compact design and short processing times ensure low operating costs and minimal use of kitchen floor space
- Maximise kitchen hyglene fully enclosed system prevents food entering the unit, keeping the machine clean and free of waste, and reducing operational noise. Following each operation, the machine undertakes a quick selfrinse cycle, preventing any build-up of food
- Three phase installation

Summary		Power and Performance		
Brand	IMC	Total Power kW	2.45	
Range	WasteStation	HP	3.2	
Power Type	Electric	IP Rating	IP24	
Unit Type	Free-standing	Operating Decibels	83	
Available in UK Only	No			
UK Warranty	2 Years Parts and Labour Warranty			
Export Warranty	Contact your local dealer			
Mounting	Free-standing			
GTIN	5056105197058			
Key Specifications		Capacity		
WRAS Approved	WRAS Compliant	Type of Waste	Soft waste	
Airbreak	Yes	Covers Per Sitting	400	
Manual or Auger Feed	Manual	Capacity Kg per Hour	200	





Weights and Dimensions		Supply Connections	Supply Connections	
Unit Height (External) mm	1044	Requires Installation	Yes	
Unit Width (External) mm	600	Requires Electrical Supply	Yes	
Unit Depth (External) mm	700	UK 3 Pin Plug	No	
Net Weight Kg	165	16A Commando Plug	No	
		Requires Hardwiring	Yes	
		Electrical Supply Rating Watts	2,400	
		Three Phase Amps	7.55	
		Three Phase Voltage	400	
		Water Supplied From	Mains Fed	
		Water Connection Pressure Bar	Head of water not less than 0.18 Bar	
		Drain Connection	2" waste drain	
		Water Connection	3/4" BSP	
		Water Consumption Litres/min	10	

Shipping

 Packed Weight Kg
 181.5

 Packed Height cm
 0

 Packed Width cm
 0

 Packed Depth cm
 0

Available Accessories

A13/159 Waste Scraper for WasteStation Compact
K12/469 Waste Caddy for WasteStation Compact



Lincat Limited Customer Care

Whisby Road, **Tel:** +44 1522 875500

Lincoln, LN6 3QZ, **Email:** care@lincat.co.uk

United Kingdom

Company No: 2175448

A member company of

Export Customers

Tel: +44 1522 875536

Email: export@lincat.co.uk

Opening Hours

Monday - Friday:

8.30am - 5pm