



UM50D - Lincat Seal Counter-top Upright Heated Merchandiser -Rotating Rack - Two doors - W 562 mm - 1.4 kW

Robust stainless steel construction - hygienic and easy to clean

Power and Performance

- Minimum food holding temperature of 72°C
- Thermostatic control up to 95°C

Tempt customers with perfect pizzas, pies and pastries on the Seal Upright Heated Merchandiser's rotating chrome plated rack.

- Rotating chrome plated rack for attractive appearance and ease of cleaning
- Humidity feature keeps food in perfect condition for longer, minimising waste
- Suitable for back-service applications

Specifications

Summary

Brand	Lincat	Total Power kW	1.40
Range	Seal	Temperature Range °C	72-95
Power Type	Electric	IP Rating	IP33
Unit Type	Counter-top	Temperature Control	Mechanical
Available in UK Only	No		riconanical
UK Warranty	2 Years Parts and Labour Warranty		
Export Warranty	Contact your local dealer		
GTIN	5056105104445		
	3030103104443		
Key Specifications			
Number of Shelves included	3		
Number of Shelf Positions	3		
Service Type	Front service		
Rack Type	Rotating		
Type of Lighting	Fluorescent		
Heated Base	Yes		
Weights and Dimensions		Supply Connections	
	783		No
Unit Height (External) mm	783 562	Requires Installation	No Yes
Unit Height (External) mm Unit Width (External) mm	562	Requires Installation UK 3 Pin Plug	Yes
Unit Height (External) mm Unit Width (External) mm Unit Depth (External) mm	562 562	Requires Installation UK 3 Pin Plug Requires Hardwiring	Yes No
Unit Height (External) mm Unit Width (External) mm Unit Depth (External) mm Height (Internal) mm	562 562 370	Requires Installation UK 3 Pin Plug Requires Hardwiring Electrical Supply Rating Watts	Yes No 1,400
Unit Height (External) mm Unit Width (External) mm Unit Depth (External) mm	562 562	Requires Installation UK 3 Pin Plug Requires Hardwiring	Yes No
Unit Height (External) mm Unit Width (External) mm Unit Depth (External) mm Height (Internal) mm Width (Internal) mm	562 562 370 554	Requires Installation UK 3 Pin Plug Requires Hardwiring Electrical Supply Rating Watts Single Phase Amps	Yes No 1,400 6.1
Unit Height (External) mm Unit Width (External) mm Unit Depth (External) mm Height (Internal) mm Width (Internal) mm Depth (Internal) mm	562 562 370 554 554	Requires Installation UK 3 Pin Plug Requires Hardwiring Electrical Supply Rating Watts Single Phase Amps	Yes No 1,400 6.1
Unit Height (External) mm Unit Width (External) mm Unit Depth (External) mm Height (Internal) mm Width (Internal) mm Depth (Internal) mm Shelf Dimensions Width mm Net Weight Kg	562 562 370 554 554 3 × 370	Requires Installation UK 3 Pin Plug Requires Hardwiring Electrical Supply Rating Watts Single Phase Amps	Yes No 1,400 6.1
Unit Height (External) mm Unit Width (External) mm Unit Depth (External) mm Height (Internal) mm Width (Internal) mm Depth (Internal) mm Shelf Dimensions Width mm	562 562 370 554 554 3 × 370	Requires Installation UK 3 Pin Plug Requires Hardwiring Electrical Supply Rating Watts Single Phase Amps	Yes No 1,400 6.1
Unit Height (External) mm Unit Width (External) mm Unit Depth (External) mm Height (Internal) mm Width (Internal) mm Depth (Internal) mm Shelf Dimensions Width mm Net Weight Kg	562 562 370 554 554 3 × 370	Requires Installation UK 3 Pin Plug Requires Hardwiring Electrical Supply Rating Watts Single Phase Amps	Yes No 1,400 6.1
Unit Height (External) mm Unit Width (External) mm Unit Depth (External) mm Height (Internal) mm Width (Internal) mm Depth (Internal) mm Shelf Dimensions Width mm Net Weight Kg Shipping	562 562 370 554 554 554 3 x 370 47	Requires Installation UK 3 Pin Plug Requires Hardwiring Electrical Supply Rating Watts Single Phase Amps	Yes No 1,400 6.1


Packed Depth cm


66.5






Technical Picture







Lincat frifri

Lincat Limited

Whisby Road, Lincoln, LN6 30Z,

United Kingdom

Company No: 2175448

A member company of



Customer Care

Tel: +44 1522 875500

Email: care@lincat.co.uk

Export Customers

Tel: +44 1522 875536

Email: export@lincat.co.uk

Opening Hours

Monday – Friday: 8.30am – 5pm