




## C Range | undercounter



C612 &amp; C615 WS

C652  
(shown with tray insert  
- not included)

## S/S CONTAINER INSERTS

## MH101491B

Capacity 5 x 1/1  
gastronom  
containers –  
maximum  
depth 65mm


£250



## MH103454B

Capacity 8 x 1/1  
gastronom  
containers –  
maximum  
depth 40mm

£195



- **2 year warranty**
- **NEW** C612 & C615 WS undercounter 500 x 600 rack, tray/dishwashers
- **NEW** C652 front loader 500 x 600 rack, tray/dishwasher
- **NEW** four button bright LED display with soft touch controls, twin traffic lights giving instant status updates & operational self-diagnostics
- **NEW** alarms menu with hi-level information retrieval
- **NEW** enhanced wash action from quick release triple wash & rinse arm design
- **NEW** Stainless steel surface scrap tray filters supplied as standard
- C615 WS with automatic continuous internal water softener
- Drain pump & breaktank supplied as standard
- Range offers a substantial usable height of 375mm to cater for large washware
- Three standard cycle time options with further options available
- Cycle times can be tailored to site requirements
- Automatic self-cleaning at end of service
- Selectable energy saving mode
- Selectable thermostop ensures optimum rinse temperatures
- Patented dual flow wash pump with **soft start** – reducing power consumption whilst retaining wash efficiency
- Moulded wash tank for easy cleaning
- Moulded rack guide giving partial double skin
- Accurate detergent & rinse aid peristaltic dosing pumps as standard
- Supplied with one 500 x 600 pegged rack & one 500 x 500 open rack
- Compatible with 500 x 500 racks



**NEW four button bright LED display with soft touch controls  
& twin traffic lights giving instant status updates**

## Technical

- Standard voltage 230V – single phase (can be supplied for 3 phase – please specify at time of order)
- Suitable for hot (max 50°C) or cold water supply, typically at 2 to 4 bar dynamic supply pressure, refer to specification sheets for individual requirements
- Wash temperature 60°C (adjustable)
- Rinse temperature 82°C (adjustable)
- Cycle times between 70 & 240 secs, dependent on model

**Requires a waste up stand for correct operation.**

**Restrictive waste connections should be avoided for all installations.**

**Machines supplied 13 amp will come with moulded plug and cable.**

**Machines configured for 13 amp supply or fitted to cold water supply will not be capable of running repeated short cycles. The cycle time will automatically be extended to allow for recovery of correct operating temperatures.**

Model	Rack size mm	Useable Height mm	Dimensions mm W x D x H	Cycle Options	Power kW	Amps Required	Price
<b>C612</b>	500 x 600	375	580 x 700 x 840 <sup>#</sup>	3 Cycles	2.8/4.7/6.7	13/20/30 <sup>##</sup>	<b>£4,590</b>
<b>C615 WS</b>	500 x 600	375	580 x 700 x 840 <sup>#</sup>	3 Cycles	2.8/4.7/6.7	13/20/30 <sup>##</sup>	<b>£5,100</b>
<b>C652</b>	500 x 600	375	580 x 700 x 1100 <sup>†</sup>	3 Cycles	2.8/4.7/6.7	13/20/30 <sup>##</sup>	<b>£5,150</b>

# Height excludes adjustable feet which will add 10 to 20mm. † Height excludes adjustable feet which will add 135 to 195mm.

## Machines will be supplied for 30 amp supply as standard. If supplied 13 amp machine will come fitted with moulded plug and cable.

20 amp machines will be supplied with original cable and without plug. Standard 13 amp UK 3 pin plugs will be **unsuitable** for cable supplied.

See page 11 for ancillary items.