



BGBF5P - Lincat Blu Blast Chiller - 5 Trays

Perfect for large batch cooking, where large quantities of food need to be brought down to storage temperature quickly

- ✔ Quickly and efficiently pull down the temperature of cooked foods
- ✔ Perfect for large batch cooking, where large quantities of food need to be brought down to storage temperature quickly
- ✔ Reduce a product's core temperature from 90°C to 3°C within 90 minutes
- ✔ With shock freezing cycle - allows the nutritional properties, appearance and flavour of a product to be maintained after thawing
- ✔ Core probe needle as standard
- ✔ Indirect air flow guarantees a perfect temperature throughout the unit
- ✔ GN1/1 and Euronorm 600 x 400 compatible - load 5 trays onto the side racks
- ✔ Side racks removable without tools for easy cleaning
- ✔ Easy-to-use digital controls - simple buttons for soft blast chilling, hard blast chilling, and shock freezing cycles, as well as manual time/temperature controls
- ✔ Auto-defrost function
- ✔ Radiused interior corners enable easy cleaning
- ✔ Reversible self-closing door with 105 degree stop
- ✔ High efficiency 60mm cyclopentane insulation - zero ODP (Ozone Depletion Potential) and only a low GWP (Global Warming Potential), providing excellent thermal efficiency
- ✔ Wide magnetic gasket gives effective seal, easily removable for cleaning
- ✔ Hygienic and robust design - Grade 304 stainless steel interior and exterior, radiused interior corners to promote easy cleaning

Specifications

Summary

Brand	Lincat
Range	Blu
Power Type	Electric
Unit Type	Free-standing
Available in UK Only	No
UK Warranty	2 Years Parts and Labour (3 Years on Compressor)
Export Warranty	Contact your local dealer
GTIN	5056105123361

Power and Performance

Total Power kW	0.8
Temperature Range °C	+20 to -40
Temperature Control	Electronic
Cooling Capacity Watts	2,095W / 615W
Climate Class	5

Key Specifications

Lockable Door	No
Number of Doors	1
Reversible Door	Yes
Number of Shelf Positions	5
Refrigerant Type	R452a
Construction/Finish	304 Grade S/S Ext/Int
Base Mounting	Castors
Insulation Material/Thickness	Cyclopentane / 60 mm
Maximum Ambient Temperature °C	38
Auto Defrost	Yes
HACCP Compliant	Yes
Number of Shelves	0
Shelf Supports	Anti-tilt
Integral Handle	Yes
Self Close Door	Yes

Capacity

Gastronorm Capacity	GN1/1, Euronorm
Chilling Capacity kg	14
Chilling Time mins	90
Freezing Capacity kg	8
Freezing Time mins	270

Weights and Dimensions		Supply Connections	
Unit Height (External) mm	850	Requires Installation	No
Unit Width (External) mm	800	Requires Electrical Supply	Yes
Unit Depth (External) mm	800	UK 3 Pin Plug	Yes
Net Weight Kg	105	Requires Hardwiring	No
		Electrical Supply Rating Watts	800
		Single Phase Amps	5
		Single Phase Voltage	230

Shipping	
Packed Weight Kg	125
Packed Height cm	102
Packed Width cm	85
Packed Depth cm	84



Lincat Limited

Whisby Road,
Lincoln, LN6 3QZ,
United Kingdom

Company No: 2175448

A member company of



Customer Care

Tel: +44 1522 875500
Email: care@lincat.co.uk

Export Customers

Tel: +44 1522 875536
Email: export@lincat.co.uk

Opening Hours

Monday – Friday:
8.30am – 5pm