



## BPSM7 - Lincat Blu Upright Fridge - Single Door

The perfect solution for professional kitchens requiring a high volume of refrigerated storage.

- ✔ Perfect solution for professional kitchens requiring a high volume of refrigerated storage
- ✔ Accurate electronic temperature control with easy-to-use digital controls to ensure safe storage of foods
- ✔ Electronic controller ensures excellent temperature control and easy to manage operation in the busiest environment (up to 43°C)
- ✔ Generous GN2/1 capacity
- ✔ Load gastronorms directly onto the shelf supports for ease of loading, or use the shelves supplied for flexible chilled storage
- ✔ Hygienic and robust design - Grade 304 stainless steel interior and exterior, with embossed shelf supports and radiused interior corners to promote easy cleaning
- ✔ Hygienic and robust design - stainless steel inside and out, radiused interior corners and embossed shelf supports to promote easy cleaning
- ✔ 75mm cyclopentane insulation and R290 gas - zero ODP (Ozone Depletion Potential) and only a low GWP (Global Warming Potential), providing excellent thermal efficiency
- ✔ Supplied with 3 shelves. 24 shelf positions allow added flexibility
- ✔ Fan assisted for optimal air distribution, ensures efficient and safe operation even when the shelves are fully loaded
- ✔ Full length grab handle
- ✔ User reversible door
- ✔ Auto-defrost function
- ✔ Heavy duty 2 swivel castors with 2 braked for easy manoeuvring and safety
- ✔ Designed to fit through a standard door for ease of positioning
- ✔ Removable Monobloc cooling unit - in the event of an issue with the cooling function, the Monobloc can be detached for repair away from the kitchen or to replace.

### Specifications

#### Summary

<b>Brand</b>	Lincat
<b>Range</b>	Blu
<b>Power Type</b>	Electric
<b>Unit Type</b>	Free-standing
<b>Available in UK Only</b>	No
<b>UK Warranty</b>	2 Years Parts and Labour (3 Years on Compressor)
<b>Export Warranty</b>	Contact your local dealer
<b>GTIN</b>	5056105123309

#### Power and Performance

<b>Total Power kW</b>	0.3
<b>Temperature Range °C</b>	-2 to +8
<b>Temperature Control</b>	Electronic
<b>Cooling Capacity Watts</b>	425
<b>Energy Grade</b>	C
<b>Annual Energy Consumption kWh/Annum</b>	564
<b>Climate Class</b>	5
<b>Energy Consumption kW/24hrs</b>	1.544

Key Specifications		Capacity	
Lockable Door	No	Gastronorm Capacity	GN2/1
Number of Doors	1	Capacity Litres	700
Shelf Material	Plastic coated steel		
Reversible Door	Yes		
Number of Shelf Positions	24		
Refrigerant Type	R290		
Construction/Finish	S/S 441(int / ext)		
Base Mounting	Castors		
Insulation Material/Thickness	Cyclopentane / 75 mm		
Maximum Ambient Temperature °C	+40		
Auto Defrost	Yes		
HACCP Compliant	No		
Number of Shelves	3		
Shelf Supports	Embossed		
Integral Handle	Yes		
Self Close Door	No		

Weights and Dimensions		Supply Connections	
Unit Height (External) mm	2120	Requires Installation	No
Unit Width (External) mm	720	Requires Electrical Supply	Yes
Unit Depth (External) mm	800	UK 3 Pin Plug	Yes
Net Weight Kg	120	Requires Hardwiring	No
		Electrical Supply Rating Watts	300
		Single Phase Amps	1.6
		Single Phase Voltage	230

Shipping	
Packed Weight Kg	125
Packed Height cm	228
Packed Width cm	78
Packed Depth cm	86



**Lincat Limited**

Whisby Road,  
Lincoln, LN6 3QZ,  
United Kingdom

**Company No:** 2175448

A member company of



**Customer Care**

**Tel:** +44 1522 875500  
**Email:** care@lincat.co.uk

**Export Customers**

**Tel:** +44 1522 875536  
**Email:** export@lincat.co.uk

**Opening Hours**

**Monday – Friday:**  
8.30am – 5pm