





Manual or Auger Feed

Self Cleaning

Manual

F79/703 - IMC WasteStation Compact -2.95 kW - Three Phase

Reliable, efficient, safe and easy to operate, the three phase WasteStation Compact 2 allows operators with even the smallest kitchens to quickly and effectively remove waste, creating a safer and cleaner kitchen.

- A solution for your business process up to 400 kg waste per hour, the equivalent of 850 covers per sitting. As fast as you can input the waste, the WasteStation Compact can process it.
- Reduce your carbon footprint reduce the amount of food waste being sent to landfill. By removing water from food waste this reduces the final volume of waste to be disposed of.
- Save on valuable floor space with a unit which is more compact than bulky alternative models, without having to upgrade to a remote dewaterer.
- ▼ Transport savings reduce waste collection costs by up to 80% by reducing the food waste volume and weight requiring collection
- Storage savings by reducing the waste volume, on site waste storage facility requirements are also reduced
- ✔ Labour savings reduce staff time processing and managing waste, fast efficient disposal of food waste as and when you need to, with no schedule

- Self-cleaning operation WasteStation can undertake a thorough clean, ensuring the whole system is free of food and grease
- Self-emptying eliminates the need for staff to empty the auger assembly, reducing labour times required to operate the machine. Intelligent electronic sensor detects when the bin is full
- Visual control panel kitchens are a noisy environment, so WasteStation incorporates a simple LED display to allow monitoring of the state of the equipment during operation
- Energy savings compact design and short processing times ensure low operating costs and minimal use of kitchen floor space
- Maximise kitchen hygiene fully enclosed system prevents food entering the unit, keeping the machine clean and free of waste, and reducing operational noise. Following each operation, the machine undertakes a quick selfrinse cycle, preventing any build-up of food
- Three phase installation

400

Specifications Power and Performance Summary Brand IMC Total Power kW 2 95 Range WasteStation ΗP 3.95 **Power Type IP Rating** IP55 Electric **Unit Type Operating Decibels** Free-standing 83 Available in UK Only No **UK Warranty** 2 Years Parts and Labour Warranty **Export Warranty** Contact your local dealer Mounting Free-standing GTIN 5056105196723 **Key Specifications** Capacity WRAS Approved Type of Waste WRAS Compliant Medium waste Airbreak **Covers Per Sitting** Yes 850

Capacity Kg per Hour





Weights and Dimensions		Supply Connections	Supply Connections	
Unit Height (External) mm	1044	Requires Installation	Yes	
Unit Width (External) mm	600	Requires Electrical Supply	Yes	
Unit Depth (External) mm	700	UK 3 Pin Plug	No	
Net Weight Kg	165	16A Commando Plug	No	
		Requires Hardwiring	Yes	
		Electrical Supply Rating Watts	2,950	
		Three Phase Amps	L1=4.3; L2=4.3; L3=4.3	
		Three Phase Voltage	400	
		Water Supplied From	Mains Fed	
		Water Connection Pressure Bar	Head of water not less than 0.18 Bar	
		Drain Connection	2" waste drain	
		Water Connection	3/4" BSP	
		Water Consumption Litres/min	10	

Shipping

 Packed Weight Kg
 230

 Packed Height cm
 130

 Packed Width cm
 120

 Packed Depth cm
 80

Available Accessories

A13/159 Waste Scraper for WasteStation Compact
K12/469 Waste Caddy for WasteStation Compact



Lincat Limited Customer Care

Whisby Road, **Tel:** +44 1522 875500

Email: care@lincat.co.uk

Lincoln, LN6 3QZ, United Kingdom

Company No: 2175448

A member company of

er Care Export Customers

Tel: +44 1522 875536

Email: export@lincat.co.uk

Opening Hours

Monday - Friday:

8.30am - 5pm