

Technical specification



EP700F: 600 Ltr Cabinet Fish Refrigerator

41-232

Single door fish cabinet

About the product

With EcoPro G3 Cabinets you get the best of both worlds: high performance coupled with low energy consumption, from the Refrigeration Experts.

Available to finance with our awardwinning <u>interest-free credit</u> and <u>leasing</u> options

Learn more about our <u>EcoPro G3</u> range

Features and benefits

- Fitted with our new and improved +stayclear condenser which helps increase product life and reduce energy consumption, +stayclear helps your low energy fridge stay a low energy fridge. Now fitted across the cabinet and counter range as standard
- Foster Shield provides advanced temperature control and hygienic design, protecting from the dangers of unsafe food storage. With air distribution optimised by CFD design technology, efficient operation is assured, even when shelves are fully loaded
- With PureControl, the G3's controller display uses pure LEDs, incorporating InGaN technology, which means it achieves higher resolution, lasts longer all while using less power. Through the simple addition of a gateway, you're connectivity-ready
- High quality 304 stainless steel is used as standard on all doors and unit covers for G3 the gold standard in performance stainless steel meaning the heaviest usage touchpoints on the product are covered
- The EP700F optimises fish storage conditions with the cooling system designed to prevent surface drying of the fish
- Operates efficiently in ambient temperatures of up to 43°C

Technical

Temperature	Fish -1/+1°C
Refrigerant	R290
Electrical supply	230/50/1
Fuse rating (A)	10
Current (A)	2.3
Power (W)	335
Refrigerant mass (g)	80

Build

Cabinet type	Fish
Finish ext/int	304 S/S & 304 S/S
Number of sections	1
Section configuration	Right hinge
System	Integral

4

З

Dimensions		Energy
Height (mm)	2080	Climate Class
Width (mm)	700	GWP
Depth (mm)	820	
Gross volume (ltr)	600	
Leg type	Braked castors	
GN size	2/1	
Gross weight (kg)	104	
Net weight (kg)	97.5	

Footnotes

- Adequate airflow and service space must be kept above the top of cabinet: 100mm
 Depth with door open is 1500mm

Thank you for your interest in this product. We hope you now have everything you need to choose Foster, however if you have any further questions, please do not hesitate to contact us.

Foster Refrigerator, Oldmedow Road, King's Lynn, Norfolk, PE30 4JU +44 (0)1553 691122 | sales@foster-gamko.com | <u>www.fosterrefrigerator.com</u>

All images shown are for illustration purpose only. All images and photographs are not intended to be relied upon for, nor to form part of, any contract unless specifically incorporated in writing into the contract. Solely the dimensions and specifications incorporated in the quotation or purchase order confirmation shall be contractually binding.