

Technical specification



EP1440M: 1350 Ltr Cabinet Refrigerator

41-174

Double door meat storage cabinet

About the product

With EcoPro G3 Cabinets you get the best of both worlds: high performance coupled with low energy consumption, from the Refrigeration Experts.

Available to finance with our awardwinning <u>interest-free credit</u> and <u>leasing</u> options

Learn more about our <u>EcoPro G3</u> range

Features and benefits

- Fitted with our new and improved +stayclear condenser which helps increase product life and reduce energy consumption, +stayclear helps your low energy fridge stay a low energy fridge. Now fitted across the cabinet and counter range as standard
- Foster Shield provides advanced temperature control and hygienic design, protecting from the dangers of unsafe food storage. With air distribution optimised by CFD design technology, efficient operation is assured, even when shelves are fully loaded
- With PureControl, the G3's controller display uses pure LEDs, incorporating InGaN technology, which means it achieves higher resolution, lasts longer all while using less power. Through the simple addition of a gateway, you're connectivity-ready
- High quality 304 stainless steel is used as standard on all doors and unit covers for G3 the gold standard in performance stainless steel meaning the heaviest usage touchpoints on the product are covered
- Market leading usable capacity, now supplied with 8 shelves as standard making your money go further holds more than a conventional fridge
- Operates efficiently in ambient temperatures of up to 43°C

Technical

Temperature	Meat -2/+2°C	Cabinet type	Standard
Refrigerant	R290	Finish ext/int	S/S & Alu
Electrical supply	230/50/1	Number of sections	2
Fuse rating (A)	10	Section configuration	Left hinge-Ri
Current (A)	1.4	System	Integral
Power (W)	540		
Refrigerant mass (g)	150		

		_	
Dimensions		Energy	
Height (mm)	2080	Climate Class	5
Width (mm)	1440	GWP	3
Depth (mm)	855		
Gross volume (ltr)	1350		
Net volume (Itr)	959.8		
Leg type	Braked castors		
GN size	2/1		
Gross weight (kg)	166.5		
Net weight (kg)	157		

Footnotes

- 150mm castors are not available if product is supplied less condensing unit
- Adequate airflow and service space must be kept above the top of cabinet: 100mm
- Depth with door open is 1500mm

Build

oinet type	Standard
sh ext/int	S/S & Alu
nber of tions	2
tion figuration	Left hinge-Right hinge
tem	Integral

Thank you for your interest in this product. We hope you now have everything you need to choose Foster, however if you have any further questions, please do not hesitate to contact us.

Foster Refrigerator, Oldmedow Road, King's Lynn, Norfolk, PE30 4JU +44 (0)1553 691122 | sales@foster-gamko.com | <u>www.fosterrefrigerator.com</u>

All images shown are for illustration purpose only. All images and photographs are not intended to be relied upon for, nor to form part of, any contract unless specifically incorporated in writing into the contract. Solely the dimensions and specifications incorporated in the quotation or purchase order confirmation shall be contractually binding.