

## **Product specification**



## EP1/3H: 435 Ltr Counter Refrigerator

43-176

Three door refrigerator counter

## Features and benefits

- A reduced footprint the more compact design of G3 counters allow them to fit in the tightest of kitchen spaces without losing capacity
- Taking the travel out of food preparation and customised to your needs, G3 counters offer unrivalled flexibility and quality.
- High performance cyclopentane foam maintains thermal efficiency for longer
- Fully floating lock provides durable security and prevents lock breakage if the key is left in
- New and improved 'Airlines' ventilation system cools the compressor which reduces running time, saving you energy
- With PureControl, the G3's controller display uses pure LEDs, incorporating InGaN technology, which means it achieves higher resolution, lasts longer all while using less power. Through the simple addition of a gateway, you're connectivity-ready
- High quality 304 stainless steel is used as standard on all doors and unit covers for G3 the gold standard in performance stainless steel meaning the heaviest usage touchpoints on the product are covered
- Operates efficiently in ambient temperatures of up to 43°C

Technical		Build	
Temperature	Refrigerator +1/+4°C	Finish ext/int	304 S/S & Alu
Refrigerant	R290	Number of sections	3
Electrical supply	230/50/1	Section configuration	Left hinge-Left hinge-Right
Fuse rating (A)	10	System	· ·
Current (A)	0.8	Worktop	
Power (W)	182	redures	
Refrigerant mass (g)	110		
Electrical supply Fuse rating (A) Current (A) Power (W) Refrigerant	R290 230/50/1 10 0.8 182	sections Section configuration System	3

Dimensions		Energy	
Height (mm)	865	Energy grade	A
Width (mm)	1815	Climate Class	5
Depth (mm)	700	EEI	22.26
Gross volume (ltr)	435	GWP	3
Net volume (ltr)	250.6	AEC (kWh)	541
Leg type	Braked castors	Daily energy consumption	1.48
GN size	1/1	(kWh)	
Gross weight (kg)	214		
Net weight (kg)	198		

## Footnotes

- Castors not available if product supplied less condensing unit
- 100mm leg option: height ranges from 835 to 865mm (replacement for standard castors). 150mm legs: height ranges from 885 to 935mm
- Adequate airflow must be kept around the counter: 150mm
- Depth with door open is 1113mm

Thank you for your interest in this product. We hope you now have everything you need to choose Foster, however if you have any further questions, please do not hesitate to contact us.

Foster Refrigerator, Oldmedow Road, King's Lynn, Norfolk, PE30 4JU +44 (0)1553 691122 | sales@foster-gamko.com | <u>www.fosterrefrigerator.com</u>

All images shown are for illustration purpose only. All images and photographs are not intended to be relied upon for, nor to form part of, any contract unless specifically incorporated in writing into the contract. Solely the dimensions and specifications incorporated in the quotation or purchase order confirmation shall be contractually binding.