



## F79/100 - IMC WasteStation Macerator and Dewaterer - without Airbreak

Reliable, efficient, safe and easy to operate, the WasteStation allows operators to quickly and effectively remove waste, creating a safer and cleaner kitchen.

- ✓ **A solution for your business** - process up to 700 kg waste per hour, the equivalent of 1450 covers
- ✓ **Transport savings** - reduce waste collection costs by up to 80% by reducing the food waste volume and weight requiring collection
- ✓ **Storage savings** - by reducing the waste volume, on site waste storage facility requirements are also reduced
- ✓ **Labour savings** - reduce staff time processing and managing waste, fast efficient disposal of food waste as and when you need to, with no schedule
- ✓ **Self-cleaning operation** - WasteStation can undertake a thorough clean, ensuring the whole system is free of food and grease
- ✓ **Self-emptying** - eliminates the need for staff to empty the auger assembly, reducing labour times required to operate the machine. Intelligent electronic sensor detects when the bin is full
- ✓ **Visual control panel** - kitchens are a noisy environment, so WasteStation incorporates a simple LED display to allow monitoring of the state of the equipment during operation
- ✓ **Energy savings** - compact design and short processing times ensure low operating costs and minimal use of kitchen floor space
- ✓ **Maximise kitchen hygiene** - fully enclosed system prevents food entering the unit, keeping the machine clean and free of waste, and reducing operational noise. Following each operation, the machine undertakes a quick self-rinse cycle, preventing any build-up of food

### Specifications

#### Summary

<b>Brand</b>	IMC
<b>Range</b>	WasteStation
<b>Power Type</b>	Electric
<b>Unit Type</b>	Free-standing
<b>Available in UK Only</b>	No
<b>UK Warranty</b>	2 Years Parts and Labour Warranty
<b>Export Warranty</b>	Contact your local dealer
<b>Mounting</b>	Free-standing
<b>GTIN</b>	5056105197041

#### Power and Performance

<b>Total Power kW</b>	4.1
<b>HP</b>	5.5
<b>IP Rating</b>	IP55
<b>Operating Decibels</b>	83

#### Key Specifications

<b>Airbreak</b>	No
<b>Manual or Auger Feed</b>	Manual
<b>Self Cleaning</b>	Yes

#### Capacity

<b>Type of Waste</b>	Tough waste
<b>Covers Per Sitting</b>	1450
<b>Capacity Kg per Hour</b>	700

### Weights and Dimensions

Unit Height (External) mm	1000
Unit Width (External) mm	900
Unit Depth (External) mm	700
Net Weight Kg	280

### Supply Connections

Requires Installation	Yes
Requires Electrical Supply	Yes
UK 3 Pin Plug	No
16A Commando Plug	No
Requires Hardwiring	Yes
Electrical Supply Rating Watts	4,100
Three Phase Amps	8.62
Three Phase Voltage	380-415
Water Supplied From	Mains Fed
Water Connection Pressure Bar	Head of water not less than 0.18 bar
Drain Connection	2" waste drain
Water Connection	3/4" BSP
Water Consumption Litres/min	12

### Shipping

Packed Weight Kg	308
Packed Height cm	160
Packed Width cm	90
Packed Depth cm	120

### Available Accessories

<b>A13/125</b>	Waste Scraper for WasteStation
<b>K12/357</b>	Waste Caddy for WasteStation and WastePro II



#### Lincat Limited

Whisby Road,  
Lincoln, LN6 3QZ,  
United Kingdom

**Company No:** 2175448

A member company of



#### Customer Care

**Tel:** +44 1522 875500  
**Email:** care@lincat.co.uk

#### Export Customers

**Tel:** +44 1522 875536  
**Email:** export@lincat.co.uk

#### Opening Hours

**Monday – Friday:**  
8.30am – 5pm