BTGHT12 TOWER SERIES HEATED

cossiga


BTGHT12




PRODUCT FEATURES


- Deck forced heating
- Single glazed
- o Sliding rear doors
- Solid front or sliding front doors
- Four adjustable shelves flat or angled
- Ticket strips on shelves and base
- Under shelf and canopy LED lights

Maximum shelf load weight 15kg spread evenly









Prior to installation see, installation guidelines, ventilation requirements and drainage options documents

A AutoCAD R Revit

MODEL	CABINET				SHELVING	OPERATING TEMP	SHELF	BASE TRAY	TOTAL FOOD	DISPLAY M ²	INTERNAL VOLUME M ³	FREQUENCY	POWER CONNECTION ELECTRICAL POV CORD 2200M			AL POWER	VOLTAGE	PACKED FOR SHIPPING			
	LENGTH [MM]	DEPTH [MM]	HEIGHT [MM]										KW 230V					LENGTH [MM]	DEPTH [MM]	HEIGHT [MM]	
BTGHT12 BTGHT12-SD	1200	750	1380	182	4 + BASE	75-85	1090 X 445	1140 x 510	255	2.52	0.60	50/60 HZ	2.20	9.6	15 AMP	3 PIN PLUG	220-240V	1300	830	1550	185

BTGHT12-SD



CABINET DIMENSIONS & SPECIFICATIONS