

# **Customize Your Pro Cart to**

Order your Pro Cart in any possible combination of Hot, Cold and Passive. Add additional modules

## **Hot Module**

#### **PCMHX**

- Safely maintain food temperatures between 150°F (65,6°C) to 165°F (73,9°C) with gentle, non-radiant heat.
- Adjustable temperature from 70°F (21°C) to 185°F (85°C).
- Heats from room temperature to 165°F (73,9°C) in 15 minutes.



## **Cold Module**

### **PCMCX**

- Thermoelectric cooling technology is safe for transport.
- Cools down to 32.5°F (0.28°C) without a compressor.
- Adjustable temperature from 32.5°F (0.28°C) to 70°F (21°C).



# Passive Module PCMPX

- CFC-free, polyurethane insulation maximizes hot or cold retention for 4+ hours without electricity.
- Most cost-effective solution.
- Perfect for short term holding and transport.



# **Your Needs**

for greater flexibility.



**Touch Screen** 

Save Up to 30% on energy cost vs. other electric cabinets.





# **Electrical Specifications**

(Per Compartment)

	HOT M	ODULE	COLD MODULE			
REQUIRED VOLTAGE	100-230 VAC		100-230 VAC			
AMPS	4.43a @ 115v	2.22a @ 220v	4.43a @ 115v	1.7 a @ 230v		
WATTS	507w @ 115v	510w @ 230v	509w @ 115v	391w @ 230v		
HERTZ	50,	/60	50/60			
PHASE	Sin	gle	Single			
PLUG BODY FOR THESE COUNTRIES	US, Canada, Mexico, China, Europe, UK, Ireland, Australia, South Africa, Japan					

<sup>\*</sup> If country is not listed, please call Cambro Customer Service for details.









Durable, Heavy-Duty Stainless Steel Hinge





Ergonomic, Molded-In Handles

Spring-Loaded Magnetic Door Catch (close door hands-free)

Nylon Paddle-Style Latches

6" (15 cm) Nylon Casters PCU800 and PCU1000 only.



2x 6 No lock pin 6" (15 cm) Heavy Duty Casters PCU2000 only.



2x With lock pin

# The Pro Cart Ultra® Pan Carriers



Total capacity 8, 4" (10 cm) deep GN 1/1 Food Pans



Total capacity 10, 4" (10 cm) deep GN 1/1 Food Pans



20, 4" (10 cm) deep

GN 1/1 Food Pans

**Holding Capacity** 

PCU800

PCU1000

PCU2000

#### **FOOD PAN DEPTHS**

				Ī								
GN FOOD PANS	2 1	/2" (6,5	cm)	4	" (10 cr	n)	6'	' (15 cn	n)	8	' (20 c	m)
GN 1/1	12	14	28	8	10	20	6	6	12	4	4	8
GN 1/2	24		28	16		20	12		12	8		8
GN 1/3	36		36	24		24	18		18	12		12





CODE	DESCRIPTION	DIMENSIONS W x D x H	PRODUCT WEIGHT (LBS/KG)		
PCU800					
PCU800HH	2 active hot compartments		101.94 / 46,24		
PCU800HC	1 active hot compartment (top), 1 active cold compartment (bottom)	21.9" x 34" x 59.1" (55,63 x 86,36 x 150,1 cm)	110.69 / 50,21		
PCU800CC	2 active cold compartments	(55,05 x 80,50 x 150,1 till)	119.44 / 54,18		
PCU800PP	2 passive compartments		89.88 / 40,77		
PCU1000		·			
PCU1000HH	2 active hot compartments		143.5 / 65,1		
PCU1000HC	1 active hot compartment (top), 1 active cold compartment (bottom)	22" x 34" x 67"	152.25 / 69,06		
PCU1000CC	2 active cold compartments	(55,88 x 86,36 x 170,18 cm)	161 / 73,03		
PCU1000PP	2 passive compartments		131.44 / 60		
PCU2000		·			
PCU2000HH	2 active hot compartments		189.94 / 86,16		
PCU2000HC	1 active hot compartment (top), 1 active cold compartment (bottom)	30" x 38" x 68"	198.69 / 90,12		
PCU2000CC	2 active cold compartments	(76,20 x 96,52 x 172,72 cm)	207.44 / 94,1		
PCU2000PP	2 passive compartments		177.88 / 80,69		
Modules		·			
PCMCX	Cold Module	_	20.72 / 9,42		
PCMHX	Hot Module	_	11.97 / 5,44		
PCMPX	Passive Module	_	5.95 / 2,7		

Case Pack: 1 Color: Charcoal Gray (615). Other configurations and Security Package available. Tow Hitch Package Available for PCU2000 Only.











For more information about Cambro products visit www.cambro.com or contact your Distributor, Cambro Sales Representative or the Cambro Customer Service Department.





