

GLASS DOOR REFRIGERATOR COMPACT KG220R DR G U

Product series: Compact Item number: 154220030

The HOSHIZAKI COMPACT KG220R DR G U is a GLASS DOOR REFRIGERATOR on castors with a net usable volume of $77\,\mathrm{Ltr.}$

The COMPACT series offers a rare combination: These cabinets are food-safe, space-saving, and come with excellent energy ratings for their class. With a footprint of only 59.5 x 66.7 cm, these small space storage cabinets are easy to fit in, especially when space is limited. These specifications make the series such a popular choice for those operators who do not require heavy-duty Gastronorm equipment.



Thanks to the Hoshizaki air distribution system, temperatures are correct and uniform throughout the entire cold room, ensuring perfectly food-safe temperatures at all times

Low-Running Energy Costs

The Energy Efficiency Class of the COMPACT KG220R DR G U is A. The COMPACT series offers a range of extremely energy-efficient refrigeration units for small spaces.

Comfortable Work Environment

Contributes to a healthier work environment with low noise levels 38.8 dB(A), when the compressor is running. Low heat emission due to short compressor running times.

Hygiene & Ergonomic Design

The COMPACT series features several design extras, implemented to simplify daily cleaning routines. One of the features for optimized operator safety is the full-height integrated handles.

The COMPACT KG220R DR G U comes with:

Refrigerant: The GLASS DOOR REFRIGERATOR uses HC refrigerant R600a

Air circulation system

Right-hand hinged door

Integrated full-height door handle

Internal LED light

Reversible door

Door lock for extra security

White shelves

Automatic defrost with re-evaporation of defrost water

SPECIFICATIONS

Product title	GLASS DOOR REFRIGERATOR	Energy Consumption (kWh/Year)	429
Temperature Range	+1/+12°C	Energy Efficiency Class Standard	ISO 22041-2019
Volume, Gross (ltr.)	123	Energy Efficiency Class	A
Net Usable Volume (ltr.)	77	Energy Efficiency Index EEI	21.6
Exterior	Stainless	Sound Level – dB(A)	38.8
Interior	White Finish	Climate Class	4 (max. ambient temp. of 30 °C with 55% RH)
Dimensions W x D x H (mm)	595 x 667 x 833		NII)
Weight, Packed (kg)	58	Refrigerant (kg) CO2 equivalent (kg)	0.029
weight, Facked (kg)	30		0.087
Insulation (mm)	52 (polyurethane)	CN on Trans Sing (many)	Shelf 483.8 x 433 mm
Refrigerant	R600a	GN or Tray Size (mm) Maximum number of shelves Number of shelves Equipped with	9
GWP	2		
	3		2
Ref. capacity at -10°C (Watt)	82		Right hand hinged reversible glass door with lock, 2 white shelves, bottom shelf 484.7 (W) x 300 (D) mm, LED lighting. Exterior: Stainless. Interior: PS lining in white
Power Supply	230V, 50 Hz		
Connection Load (Watt)	100		
		Door Type	Glass door