


GLASS DOOR REFRIGERATOR COMPACT KG220R DR G U

Product series: Compact Item number: 154220030



These small space storage cabinets are easy to fit in especially where space is of a premium. This makes the COMPACT series a very popular choice amongst small kitchen operators who do not require heavy duty gastronorm refrigeration. The COMPACT KG220R DR G U is a GLASS DOOR REFRIGERATOR with a net internal volume of 77 ltr. The dimensions are mm.



This compact storage cabinet is easy to fit into your kitchen design, especially when space is of a premium.

HIGH STANDARD HYGIENE

The one piece inner lining with its smooth surfaces and seamless construction allows for a straight forward easy cleaning routine.

UNIFORM TEMPERATURES

Automatic defrost and a smart air distribution system ensures correct and uniform temperatures at all times preserving the taste, texture and nutritional content of your fresh goods.

FULL HEIGHT INTEGRATED HANDLE

Easy grip and easy access for cleaning.

EASY CLEANING

Rounded corners and base, seamless surfaces and removable door seal ensures cleaning routines become a quick and simple task.



SPECIFICATIONS

Des duet title	CLACC DOOR REFRICERATOR	Francis and committee (IAMI) (Vaca)	400
Product title	GLASS DOOR REFRIGERATOR	Energy consumption (kWh/Year)	429
Temperature range	+1/+12°C	Energy Efficiency Class Standard	ISO 22041-2019
Volume, gross (ltr.)	123	Energy Efficiency Class	A
Net usable volume (ltr.)	77	Energy Efficiency Index EEI	21.6
Exterior	Stainless	Sound level dB(A)	38.8
Interior	White Finish	Climate class	4
Dimensions W x D x H (mm)	595 x 667 x 833	Refrigerant (kg)	0.029
Weight, packed (kg)	58	CO2 equivalent (kg)	0.087
Insulation (mm)	52 mm (polyurethane)	Tray size	Shelf 483.8 x 433 mm
Refrigerant	R600a	Maximum number of shelves	9
GWP	3	Number of shelves	2
Refrigeration capacity at -10°C (Watt)	82	Equipped with	Right hand hinged reversible glass door with lock, 2 white shelves, bottom shelf 484.7 (W) x 300 (D) mm, LED lighting. Exterior: Stainless. Interior: PS lining in white
Power supply	230V, 50 Hz		
Connection load (Watt)	100	Door Type	Glass door