

G-SERIES MULTIDECK TECHNICAL DATASHEET



G70*

G100

G125

Dimensions (mm)

	G70*	G100	G125
Width	710	960	1250
Depth	650	650	650
Height	1910	1910	1910
Total Display Area - Hinged Front Door Models (M ²)	0.64	0.83	1.15
Total Display Area - Sliding Front Door Models (M ²)	-	0.79	1.12

Capacity

	G70*	G100	G125
Capacity (ltrs / cu. ft)	240 / 8.5	333 / 11.8	441 / 15.6
Capacity (330ml cans)	189	270	357

KEY FEATURES

- Natural hydrocarbon refrigerant
- Choice of superior thermal efficient self-closing or hinged doors
- Designed and engineered to operate efficiently up to 25°C ambient
- Ceiling mounted LED strip lighting
- Panoramic glass ends
- Double wheel castors
- Adjustable shelves
- Removable ticket strips

OPTIONS

- Additional shelving
- Front hinged doors
- Front sliding doors
- Undershelf LED strip lighting to all shelves
- Food tray slide
- Solid or glass rear loading doors
- Choice of RAL coloured finishes
- Chameleon wrap
- Remote refrigeration system
- Multiplexed units



GEM G-SERIES MULTIDECKS TECHNICAL DATA

G Series		G70-HFD	G100-HFD	G125-HFD	G100-SFD	G125-SFD
Temperature (Class : M2)		+3/+5°C	+3/+5°C	+3/+5°C	+3/+5°C	+3/+5°C
Climate Class		3	3	3	3	3
Power Supply		230V/50Hz/1Ph				
Fuse (Amps)		13	13	13	13	13
Noise level (dBA)		<50	<50	<50	<50	<50
Weight (kg)	SCD	228	248	286	244	280
	WCD	168	198	236	194	230

Fittings

Shelves		4	4	4	4	4
Shelf Size (w x d)		641 x 305	892 x 305	1182 x 305	892 x 305	1182 x 305
Base Size (w x d)		643 x 335	891 x 335	1184 x 335	891 x 335	1184 x 335

Electrical / Energy Data

Refrigerant		R290	R290	R290	R290	R290
Energy Efficiency Class		B	C	C	B	B
Energy Efficiency Index (EEI)		19.3	20.3	24.7	15.6	19.1
Energy Consumption (kW / 24hrs)		3.16	3.73	5.3	2.9	4.1
Power Rating (W)		494	672	831	672	831

IMPORTANT NOTES:

* Front Hinged Door Only

Performance complies with 3M2 classification as prescribed in BS EN23953-2:2015. M2 refers to product temperatures of no greater than +7°C and no lower than -1°C when loaded in accordance with the standard and recorded under test conditions.

Williams is committed to a policy of continual product development and innovation. As such, we reserve the right to change product specifications stated without prior notice.

All refrigeration equipment requires adequate ventilation for efficient and effective performance.

Williams Refrigeration
Bryggen Road,
North Lynn Industrial Estate
King's Lynn, Norfolk. PE30 2HZ

T +44(0) 1553 817 000
Spares: +44(0) 1553 817 017
E info@williams-refrigeration.co.uk
W www.williams-refrigeration.co.uk

