

ONYX TECHNICAL DATASHEET



CPC2 CPC3 CPC4 CPC5

Dimensions (mm)	CPC2		CPC3		CPC4		CPC5	
	External	Internal	External	Internal	External	Internal	External	Internal
Width	955	854	1420	1320	1885	1785	2350	2250
Depth	860	583	860	583	860	583	860	583
Height	1100	647	1100	647	1100	647	1100	647
Door Opening		392		392		392		392
Capacity	cu.ft/ltrs							
Capacity cu.ft/ltrs	12.5/355		21.6/613		29.2/828		36.8/1043	

KEY FEATURES

- Foodsafe stainless steel exterior and interior
- CoolSmart controller
- Designed and engineered to operate efficiently up to a 43°C ambient
- Self closing doors
- Precision injected, high density 75mm polyurethane insulation. Provides excellent thermal efficiency with low GWP (Global Warming Potential) and zero ODP (Ozone Depletion Potential)
- Heavy duty, non-marking swivel castors with brakes
- Barrel locked doors
- High performance, efficient commercial refrigeration system
- Unique air flow design with protective 1°C air curtain
- Removable, easy to clean crumb tray and lift off night cover
- Removable internal fittings including racking and shelf supports
- Connection to third party supervisory communication systems such as BMS is possible using proprietary equipment. Please contact Williams for more information.

OPTIONS

- Bank of 2 drawers
- Hinged cover
- Granite worktop
- Polypropylene worktop
- 1/3 x 150mm Gastronorm pans with lids
- Stainless steel back



ONYX TECHNICAL DATA

	CPC2	CPC3	CPC4	CPC5
Temperature (°C)	+1/+4°C	+1/+4°C	+1/+4°C	+1/+4°C
Power Supply	230V/50Hz/1Ph	230V/50Hz/1Ph	230V/50Hz/1Ph	230V/50Hz/1Ph
Fuse (Amps)	13	13	13	13
Defrost	Automatic Hot Gas	Automatic Hot Gas	Automatic Hot Gas	Automatic Hot Gas
Noise level (dBA)	67	64	64	68

Fittings

Shelves	4	6	8	10
Trayslides per door	4	4	4	4
1/3 GN Pans (not included)	4	7	10	12

Electrical / Energy Data - Standard Refrigerant

Refrigerant	R290	R290	R290	R290
Start Up (Amps)	16	21	21	28
Running (Amps)	2.88	4.04	4.53	4.68
Heat Rejection (Watts)*	907	1428	1428	2503

IMPORTANT NOTES:

*Evaporating at -10°C in 32°C Ambient

Williams is committed to a policy of continual product development and innovation. As such, we reserve the right to change product specifications stated without prior notice.

Williams Refrigeration
Bryggen Road,
North Lynn Industrial Estate
King's Lynn, Norfolk. PE30 2HZ

T +44(0) 1553 817 000
Spares: +44(0) 1553 817 017
E info@williams-refrigeration.co.uk
W www.williams-refrigeration.co.uk

