


# REFRIGERATOR COMPACT K420L C DR G U

Product series: Compact Item number: 161422030



These small space storage cabinets are easy to fit in especially where space is of a premium. This makes the COMPACT series a very popular choice amongst small kitchen operators who do not require heavy duty gastronorm refrigeration. The COMPACT K420L C DR G U is a REFRIGERATOR with a net internal volume of 265. The dimensions are mm.

#### COMPACT AND HIGHLY VERSATILE

This compact storage cabinet is easy to fit into your kitchen design, especially when space is of a premium.

#### HIGH STANDARD HYGIENE

The one piece inner lining with its smooth surfaces and seamless construction allows for a straight forward easy cleaning routine.

#### UNIFORM TEMPERATURES

Automatic defrost and a smart air distribution system ensures correct and uniform temperatures at all times preserving the taste, texture and nutritional content of your fresh goods.

### FULL HEIGHT INTEGRATED HANDLE

Easy grip and easy access for cleaning.

#### **EASY CLEANING**

Rounded corners and base, seamless surfaces and removable door seal ensures cleaning routines become a quick and simple task.

## SPECIFICATIONS

Product title	REFRIGERATOR	Energy consumption (kWh/Year)	310
Temperature range	+1/+12°C	Energy efficiency class standard	ISO 22041-2019
Volume, gross (ltr.)	343	Energy efficiency class	В
Net usable volume (ltr.)	265	Energy Efficiency Index EEI	29.62
Exterior	White Finish	Sound level – dB(A)	39.8
Interior	White Finish	Climate class	4
Dimensions W x D x H (mm)	595 x 645 x 1900	Legs / Castors	H = 125 mm (C2)
Weight, packed (kg)	87	Refrigerant (kg)	0.048
Insulation (mm)	52 (polyurethane)	CO2 equivalent (kg)	0.144
Refrigerant	R600a	Tray size (mm)	Shelf 483.8 x 433 mm
GWP	3	Maximum number of shelves	26
Ref. capacity at -10°C (Watt)	122	Number of shelves	5
Power supply	230V, 50 Hz	Equipped with	Right hand hinged reversible door with lock, 5 white shelves, bottom shelf 484.7 (W) x 300 (D) mm. Exterior: White. Interior: PS lining in white
Connection load (Watt)	120		
		Door Type	Insulated Door