

# **MODEL: 0E8021**



Combining raw power with energy efficiency, the Opus 800 4 Zone Induction Hob delivers 90% efficiency compared to 55% with a solid electric hot plate and 50% with a gas hob. Designed to suite with Opus 800 series and available with Opus 800 stands and pedestals, the hob is suitable for any busy commercial kitchen, large pubs and restaurants, large hospitals, school canteens, care homes and high volume production kitchens. The hob features an automatic pan detection function which cuts power when no pan is present, preventing harm to users and saving energy at the same time. Built to last, it also comes with multiple internal cooling fans and overheat protection.



### PRODUCT OPTIONS AND ACCESSORIES

- OA8956/C Lincat Opus 800 Free-standing Floor Stand with Castors for units W 800 mm
- OA8956 Lincat Opus 800 Free-standing Floor Stand with Legs for units W 800 mm
- OA8974/C Lincat Opus 800 Free-standing Pedestal with Doors and Castors - for units W 800 mm
- OA8974 Lincat Opus 800 Free-standing Pedestal with Doors and Legs

   for units W 800 mm

### **PRODUCT FEATURES**

- Four powerful 3.5kW, 270mm width induction zones
- Automatic pan detection function cuts power when no pan is present, preventing harm to users, while saving energy
- Multiple internal cooling fans and overheat protection for long service life
- Easy to change filter built into the base of the unit
- No open flames so no radiating heat reduce ambient temperature of kitchen for a more comfortable working temperature
- Delivers 90% efficiency compared to 55% with a solid electric hot plate and 50% with a gas hob
- Designed to suite with Opus 800 series and available with Opus 800 stands and pedestals









**MODEL: 0E8021** 

WEIGHTS & DIMENSIONS	
Width	800 mil
Depth	800 mil
Height	308 mil
Weight	48 kg

SHIPPING DETAILS	
Ship Width	90 cm
Ship Depth	85 cm
Ship Height	45 cm
Ship Weight	52.8 kg
Number of Shipment Parcels	1
Ship Method	Small Parcel (FedEx, UPS, DHL)
Shipping Package Type	Pieces
Shipping Origin Zip Code	LN6 3QZ, UNITED KINGDOM
Quick Ship Product	No

# **PRODUCT CERTIFICATIONS**



ENERGY SPECS	
Primary Energy Type	Electric
Electrical Amps Per Conductor	L1=22; L2=22; L3=22
Electrical Total Amperage	66 A
Electrical Volts	400V
Electrical Total Wattage	15200 W
Electrical Kilowatts	15.2 kW
Electrical Phase	3-Phase

Electrical Plug Type	Hardwired
Number of Electrical Plugs	Not Applicable
Electrical Connection Type	Direct Hardwired
Number of Electrical Conductor Wires	1
Dedicated Circuit Required	Yes
Electrical Remarks	Three

ADDITIONAL SPECIFICATIONS	
Construction Materials	Stainless Steel
Control Type	Electronic
Cooking Plate Finish Material Type	Ceran Glass
Number of Heating Zones	4
Number of Hot Top Burners	4
Number of Shelves	Not Applicable
Open or Sealed Burners	Not Applicable
Ventless Cooking Technology	No

Lincat reserves the right to modify specifications or discontinue models without incurring obligation. Dimensions nominal.

Document Auto-Generated January 09, 2025







**MODEL: 0E8021** 

SELECT COOKING EQUIPMENT	NUMBER OF		POWER RATING	ARRANGE- MENT	WIDTH	DEPTH
Induction Burner 1		4	5.3	Center	270 mm	270 mm
SELECT BASE EQUIPMENT  Not Applicable For This Item	NUMBER OF		CUBIC CAPACITY EACH	WIDTH	DEPTH	HEIGHT
BIDDING SPECIFICATIONS						

Bidding Specifications Not Available.








**MM - 14 KW** 

**MODEL: 0E8021** 

# **TECHNICAL DRAWING**







Lincat reserves the right to modify specifications or discontinue models without incurring obligation. Dimensions nominal.

Document Auto-Generated January 09, 2025