



HOPLCNCE

FUNCTIONAL CHARACTERISTICS

Display	LCD 2,4" IPS
Supply	Electric
Timer	-
Number of motors	1
Motor speeds	10
Max cooking temperature	260°C
Core probe	-
Cooking chamber material	AISI 304
Opening door	Left handle
Chimney	30mm with carbon filter
Humidification	Direct injection
Air injection	HOP V-Dry
Self-washing	Yes

STANDARDS	
Certification	CE
TRAYS	
Trays rack	French fries basket + Breaded tray + Tray extractable
Max tray load	French fries basket 2.5Kg Breaded tray 2Kg Tray extractable 3Kg
DIMENSIONS	
Oven size with handle WxDxH (mm)	732x871x593
Oven size without handle WxDxH (mm)	732x804x593
Chamber size WxDxH (mm)	455x320x285
Unit weight (kg)	73
PACKAGING	
Packaging	Pallet + Carton Box
Packaging size WxDxH (mm)	770x930x635
Wooden box packaging size (optional)	770x930x635
ELECTRICAL DATA	
Heaters 9 kW 50/60Hz	
Power	9,5 kW
Frequency	50 Hz
Power supply	400V 3~N
Amperage	15A
Power cord req.	5G1,5
WATER CONNECTION REQUIREMENTS	
Humidification Water inlet	3/4" M Gas threaded
Washing Water inlet	8mm quick fitting
Water drain	30mm
Max water hardness	5°f
Water pressure requirement min-max	150-200 kPa

CONSUMPTION

Humidification Water	-
Rinse Water @2barG	7,9 l
Short Washing Water @2barG	24,9 l
Long Washing Water @2barG	31,1 l
Short Washing Detergent *	70 g
Long Washing Detergent *	140 g

CONNECTIVITY

USB	USB 2.0
Bluetooth	-
Wi-Fi	Standard
Cloud	Standard

ACCESSORIES

French fries basket	85GRI00342
Basket support	85GRI00340
French fries extractable basket	85GRI00347
Breaded extractable basket	85GRI00364
Crumbs tray	10VAS00144
Crumbs grid	85GRI00372
Tray extractable	85GRI00370
Basket handle (1 piece)	85MNG00036
Water softner cover	WS10
Water softner 6800L	WS11
Water softner 12000L	WS12
Water pressure adapter	WPA
Water shower kit	S1
Detergent 6KG	DT2
Detergent 10KG	DT4